

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس






09906500074-66765968-66765923











ایمیل









Info@Hikvisiontehran.com










CONTACT US





HIKVISIONTEHRAN.COM

Turbo HD Camera - DVR			
Items	Description	User Price	
Turbo HD - 1MP			
1	DS-2CE16C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 4,120,000	
2	DS-2CE56C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 4,080,000	
3	DS-2CE56C0T-IRPF 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS	IRR 4,240,000	
Turbo HD - 2MP			
5	DS-2CE16D0T-IF 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	IRR 6,240,000	
6	DS-2CE56D0T-IPF 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - True Day/Night, Smart IR	IRR 5,060,000	









7	DS-2CE16D0T-IR	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	IRR 6,600,000	
8	DS-2CE56D0T-IRP	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR	IRR 5,400,000	
9	DS-2CE56D0T-IRM	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	ناموجود	
10	DS-2CE16D0T-IT1	,2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	ناموجود	
11	DS-2CE16D0T-IT3	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens - IP66 weatherproof	ناموجود	
12	DS-2CE56D0T-IT1	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	ناموجود	
13	DS-2CE16D0T-VFIR3F	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 16,840,000	
14	DS-2CE56D0T-VFIR3F	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 16,840,000	
15	Turbo HD - 2MP built-in PoC			
16	DS-2CE16D0T-IRE	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 7,980,000	
17	DS-2CE16D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu. IP66, 2.8/3.6/6mm Lens	ناموجود	










18	DS-2CE56D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 8,280,000	
19	DS-2CE56D0T-IT3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 8,880,000	
20	DS-2CE16D0T-VFIR3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu , IP66 - Lens 2.8 - 12 mm @ F1.4	ناموجود	
21	DS-2CE56D0T-VFIR3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu IP66 - Lens 2.8 - 12 mm @ F1.4	ناموجود	
22	Turbo HD - 2MP built-in PoC - Starlight Value Series			
23	DS-2CE16D8T-ITE	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	ناموجود	
24	DS-2CE56D8T-ITME	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 13,860,000	
25	DS-2CE16D8T-IT3E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67 , 2.8/3.6/6mm Lens	ناموجود	
26	DS-2CE16D8T-IT3ZE	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , 2.8 mm to 12 mm motorized vari-focal lens - IP67	ناموجود	
27	DS-2CE56D8T-IT1E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	IRR 14,550,000	









28	DS-2CE38D8T-PIR	2.0 megapixel progressive scan CMOS - Ultra-Low Light PIR Cube Camera - Color: 0.005 Lux @ (F1.2, AGC ON) , 0 Lux with IR - 2.8 mm, 3.6 mm fixed focal lens - Backlight Compensation: WDR/BLC/OFF - Motion Detection: 4 programmable motion areas	ناموجود	
29	Turbo HD - 3MP			
30	DS-2CE56F1T-IT3	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 10,820,000	
31	DS-2CE56F7T-IT3Z	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized vari-focal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 27,720,000	
32	Turbo HD - 5MP			
33	DS-2CE16H0T-ITF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 11,770,000	
34	DS-2CE16H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 12,840,000	
35	DS-2CE16H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,860,000	
36	DS-2CE16H0T-IT5F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,950,000	
37	DS-2CE16H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 23,910,000	
38	DS-2CE56H0T-ITMF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	ناموجود	

39	DS-2CE56H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,170,000	
40	DS-2CE56H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,540,000	
41	DS-2CE56H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 23,560,000	
42	Turbo HD - 5MP - built-in PoC			
43	DS-2CE16H1T-ITE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 11,770,000	

44	DS-2CE16H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 12,840,000	
45	DS-2CE16H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 13,860,000	
46	DS-2CE16H1T-IT5E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 14,950,000	
47	DS-2CE16H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	ناموجود	
48	DS-2CE56H1T-ITME	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 11,400,000	
49	DS-2CE56H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 13,170,000	
50	DS-2CE56H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 13,540,000	
51	DS-2CE56H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	ناموجود	
52	DS-2CC52H1T-FITS	5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, Built-in microphone, 1-ch audio output	ناموجود	
53	TURBO HD 5MP (TURBO HD 5.0) PIR Series			

54	DS-2CE11H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	ناموجود	
55	DS-2CE12H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	ناموجود	
56	DS-2CE71H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 10,440,000	
57	Turbo HD - 8MP			
58	DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 39,490,000	
59	DS-2CE18U8T-IT3	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 41,570,000	
60	Turbo HD PTZ Camera			
61	DS-2AE5223TI-A (24VAC)	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	ناموجود	
62	DS-2AE7230TI-A (24VAC)	High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30x optical zoom, focal length 4-120mm - 16x digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	ناموجود	
63	Turbo HD DVR 720P / 1080p lite			
64	DS-7208HGHI-F1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u> : 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> 2-ch (up to 10-ch) Up to 2 MP resolution - Support H.264+/H.264 IP cameras - <u>Audio input</u> 1-ch - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	IRR 26,200,000	

65	DS-7216HGHI-K1	<p>Analog video input 16-ch - <u>Encoding resolution</u> 1080p lite/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u>: 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity</p>	IRR 32,360,000	
66	Turbo HD DVR 1080p / 3MP / 4MP lite			
67	DS-7204HQHI-K1	<p>Analog video input 4-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity</p>	IRR 22,180,000	
68	DS-7108HQHI-K1	<p>Analog video input 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity</p>	IRR 30,820,000	
69	DS-7208HQHI-K1/Eco	<p>Analog video input 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - ECO CASE</p>	ناموجود	
70	DS-7208HQHI-K1	<p>Analog video input 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity</p>	IRR 33,450,000	
71	DS-7116HQHI-K1	<p>Analog video input 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity</p>	IRR 48,940,000	
72	7216HQHI-K1-Eco	<p>Analog video input 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - ECO CASE</p>	IRR 55,200,000	
73	DS-7216HQHI-K1	<p>Analog video input 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity</p>	IRR 57,380,000	
74	DS-7216HQHI-K2	<p>Analog video input 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u>: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk</p>	IRR 58,800,000	

75	DS-7224HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 32-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	ناموجود	
76	DS-7232HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 110,540,000	
77	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite			
78	DS-7204HUHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 35,830,000	
79	DS-7208HUHI-K1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 51,240,000	
80	DS-7216HUHI-K2	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 101,740,000	
81	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)			
82	DS-7204HUHI-K1/P	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 x 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable	IRR 39,210,000	
83	DS-7208HUHI-K2/P	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	IRR 73,140,000	
84	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			
85	DS-7204HTHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 8 MP resolution - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 41,570,000	







86











DS-7208HTHI-K2










Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 x 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk











IRR 80,830,000





















Network Camera - NVR			
Items	Description	User Price	
Lite Mini Bullet Series			
1	DS-2CD1023G0E-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 20,000,000	
2	DS-2CD1023G0-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 20,140,000	
3	DS-2CD1043G0-I 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 27,560,000	
4	DS-2CD1053G0-I 5.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1920@12.5fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, True 120db WDR	IRR 29,040,000	
Lite Dome Series			
6	DS-2CD1323G0E-I 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 19,510,000	
7	DS-2CD1123G0E-I 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	ناموجود	











8	DS-2CD1123G0-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	IRR 21,560,000	
9	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 28,980,000	
10	Mini Bullet Series			
11	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m	IRR 26,400,000	
12	DS-2CD2023G0-I	2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 31,450,000	
13	DS-2CD2043G0-I	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 35,920,000	
14	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams,IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m	IRR 31,030,000	
15	DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ناموجود	
16	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ناموجود	
17	Dome Series			
18	DS-2CD2123G0-IS	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	IRR 33,920,000	
19	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 36,750,000	











20	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof -housing, HIK-Connect cloud service - S: Audio/Alarm IO connectors	IRR 32,400,000	
21	DS-2CD2163G0-IS	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048 @20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 43,820,000	
22	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @ 15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 51,590,000	
23	Bullet Series			
24	DS-2CD2T43G0-IS	1/3" Progressive Scan CMOS, 2688 x 1520 @ 30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 40,070,000	
25	DS-2CD2T63G0-IS	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048 @ 20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	ناموجود	
26	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048 @ 20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 48,760,000	
27	DS-2CD2T83G0-IS	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @ 15 fps 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	ناموجود	
28	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @ 15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 57,950,000	
29	Exir Dome Series			
30	DS-2CD2322WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 30,260,000	













31	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 36,000,000	
32	Mini Dome Series			
33	DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	ناموجود	
34	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO	IRR 48,430,000	
35	DS-2CD2543G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	IRR 49,060,000	
36	DS-2CD2563G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	ناموجود	
37	Lite Bullet Vari-Facal Motorized Series			
38	DS-2CD1623G0-I	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 41,130,000	
39	DS-2CD1623G0-IZ	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 45,940,000	
40	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 49,470,000	
41	Lite Dome Vari-Facal Series			
42	DS-2CD1723G0-I	2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	ناموجود	
43	DS-2CD1743G0-I	4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	IRR 44,520,000	
44	Bullet Vari-Facal Motorized Series			














45	DS-2CD2620F-I	2 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	ناموجود	
46	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 48,060,000	
47	DS-2CD2643G0-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS - 2688 x1520@30fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.264+, H.264 - Three streams - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 74,200,000	
48	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens	ناموجود	
49	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens	ناموجود	
50	Dome Vari-Facal Motorized Series			
51	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 35,800,000	
52	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - Z: Motorized VF lens	ناموجود	
53	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8" 2MP progressive scan CMOS Up to 1920 x 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA,Micro SD (Up to 128 GB), Reset Button 1 Audio I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - Z: Motorized VF lens	ناموجود	
54	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Max IR distance: 30 meters - 3-Axis adjustment - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8 to 12 mm Varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 behavior analyses, and face detection - Digital Noise Reduction 3D DNR - Z: Motorized VF lens	IRR 74,200,000	
55	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	










56	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	
57	Fish Eye Series			
58	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 87,110,000	
59	Cube Smart Series			
60	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 28,270,000	
61	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 x 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 34,980,000	
62	Pin Hole Series			
63	DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
64	Hologen Series			
65	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optionaln - (Black, Silver, Golden) -W: Built-in Wi-Fi	ناموجود	
66	2Q Smart Series			
67	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 24,870,000	
68	DS-2CV2Q21FD-IW	2 MP CMOS PT Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - Default: No SD card included. - 32GB-T: Include 16GB sd card.	ناموجود	
69	2U Smart Series			








70	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 17,300,000	
71	Mini PTZ Series			
72	DS-2CD2F52F-IS	5MP CMOS ICR Infrared Network Dome Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 38,940,000	
73	IP PTZ Camera			
74	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	ناموجود	
75	DS-2DE4220IW-DE	2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	ناموجود	
76	DS-2DE4225IW-DE	2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 x 1080@30fps resolution- Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	IRR 124,010,000	
77	DS-2DE5220IW-AE	2MP 20X Network IR PTZ Dome Camera - 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s - 150m IR Distance - Hi-PoE&24VAC	ناموجود	
78	DS-2DE5230W-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	ناموجود	
79	DS-2DE7184-AE	2MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 100m IR Distance, Hi-PoE&24VAC	ناموجود	
80	DS-2DE7220IW-AE	22MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
81	DS-2DE7230IW-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	











82	DS-2DE7232IW-AE	2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
83	DS-2DE7320IW-AE	3MP 20x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 20x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	
84	DS-2DE7330IW-AE	3MP 30x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 30x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	
85	DS-2DE7420IW-AE	4MP 20x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,20x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
86	DS-2DE7430IW-AE	4MP 30x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,30x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
87	DS-2DE7530IW-AE	5MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
88	PanoVu Mini Series IR Network PTZ Camera			
89	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 x 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° x 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 x 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4x optical zoom, 8x digital zoom	ناموجود	
90	NVR-Monitor			
91	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 130,800,000	
92	NVR 4 Channel			
93	DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 16,520,000	
94	DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 27,290,000	










95	DS-7604NI-E1	IP video input : 4-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
96	DS-7604NI-E1/4P	IP video input : 4-ch / 4-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
97	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 25,520,000	
98	DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 36,480,000	
99	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
100	DS-7604NI-K1/4P	IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
101	NVR 8 Channel			
102	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 20,770,000	
103	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 39,680,000	
104	DS-7608NI-E2	IP video input :8-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 32,400,000	
105	DS-7608NI-E2/8P	IP video input :8-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
106	DS-7608NI-Q1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 30,730,000	
107	DS-7608NI-Q1/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	











108	DS-7608NI-Q2	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
109	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 31,600,000	
110	DS-7608NI-K2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
111	NVR 16 Channel			
112	DS-7616NI-E2	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
113	DS-7616NI-E2/8P	IP video input :16-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
114	DS-7616NI-E2/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
115	DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 37,070,000	
116	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 38,780,000	
117	DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 79,000,000	
118	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 42,160,000	
119	DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
120	DS-7716NI-E4	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
121	DS-7716NI-E4/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	









122	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 82,950,000	
123	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 97,520,000	
124	DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
125	NVR 32 Channel			
126	DS-7732NI-E4	IP video input :32-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 103,500,000	
127	DS-7732NI-E4/16P	IP video input :32-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
128	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 102,340,000	
129	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 148,300,000	
130	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 122,340,000	
131	DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 157,580,000	

Accessories				
Items	Description	User Price		
Switches				
1	DS-3E0105P-E L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	ناموجود		
2	DS-3E0109P-E L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	IRR 30,200,000		
3	DS-3E0318P-E L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	ناموجود		
4	DS-3E0326P-E L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	ناموجود		
5	DS-3E1310P-E L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	ناموجود		
6	DS-3E1318P-E 802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission,VLAN configurable Port trunk, multicast and port mirroring,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mouted design for convenient installation	ناموجود		
Cables				
8	DS-1LN6-UE-W UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 39,110,000		

9	DS-1LN6-UU	<p>UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange</p>	IRR 43,050,000	
10	Brackets			
11	DS-1602ZJ	<p>Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 5,700,000	
12	DS-1602ZJ-pole	<p>Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	ناموجود	
13	DS-1605ZJ	<p>Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm</p>	ناموجود	
14	DS-1661ZJ	<p>Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: -116.5×200mm-Weight: -600g</p>	IRR 6,240,000	
15	DS-1662ZJ	<p>Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 7,160,000	
16	DS-1663ZJ	<p>Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	ناموجود	
17	DS-1693ZJ	<p>Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner</p>	ناموجود	
18	DS-1681ZJ	<p>Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 2,080,000	
19	DS-1273ZJ-135B	<p>Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx</p>	Call	

20	Keyboard			
21	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	IRR 289,080,000	
22	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	IRR 69,280,000	
23	Tester			
24	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	ناموجود	
25	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 113,990,000	
26	Access Control			
27	DS-K2804	Four-door Access Controller, Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magneticx4, Door Switchx4, Case Inputx4; Output interface: Door Switch Relayx4, Alarm Relayx4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards information and 50,000 access control events	Call	
28	DS-K1100 Series Card Reade			
29	DS-K1101MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	Call	
30	DS-K1102M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	Call	
31	DS-K1102MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	Call	
32	DS-K1104M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	Call	

33	DS-K1801M	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
34	DS-K1801MK	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
35	Card Sender			
36	DS-K1F100-D8E	Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	Call	
37	Pro Magnetic Lock			
38	DS-K4T100	Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	Call	
39	DS-K4H250S	Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
40	DS-K4H250D	Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mAx2 24V/250mAx2	Call	
41	Eco Magnetic Lock			
42	DS-K4H188S	Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
43	Pro Bracket for Magnetic Lock			
44	DS-K4T100-U2	Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	Call	
45	DS-K4H250-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
46	DS-K4H250-U	U-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
47	Eco Bracket for Magnetic Lock			

48	DS-K4H188-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	Call	
49	Door release button			
50	DS-K7P01	aluminum alloy panel, metal button, Dimension(LxWxH): 86x86x20mm(3.39x3.39x0.79")	Call	
51	DS-K1T8 Series			
52	DS-K1T803MF	LCD Display Standalone Access Control Terminal, Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc	Call	
53	DS-K1T200 Series			
54	DS-K1T200MF-C	2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal, Built-in Mifare card reading module and 2 Megapixels camera, Max. 9500 fingerprints, Max. 100,000 cards No.and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
55	DS-K1T105 Series			
56	DS-K1T105M-C	2.8 inch LCD-TFT Screen Standalone Access Control Terminal, Built-in Mifare card (EM card) reading module, 2 Megapixels camera, Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
57	DS-K1T801M	Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
58	DS-K1T802M	LCD Display Screen Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
59	Card			
60	S50+TK4100	EM + Mifare	Call	
61	Adapters			
62	Power Adapter	12V/1A	IRR 440,000	



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل








Info@Hikvisiontehran.com













CONTACT US









HIKVISIONTEHRAN.COM










Hilook-DVR




Items	Description	User Price	
1	THC-B110-M 1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	IRR 3,500,000	
2	THC-B120-P 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 5,850,000	
3	THC-B120-M 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 6,850,000	
4	THC-B140-P 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 6,250,000	
5	THC-B140-M 4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 7,550,000	
6	THC-B220 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 7,650,000	
7	THC-B220-M 2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 8,900,000	









8	THC-B240	4MP high-performance CMOS - 2560 x1440 resolution- 2.8 mm - fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 8,700,000	
9	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu , IP66, 2.8/3.6/6mm Lens ,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 9,850,000	
10	THC-T110-P	1 MP high-performance CMOS, 1280 x 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	IRR 3,250,000	
11	THC-T120-PC	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 4,950,000	
12	THC-T120	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 5,350,000	
13	THC-T120-M	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 6,850,000	
14	THC-T140-P	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 5,900,000	
15	THC-T140	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 6,350,000	
16	THC-T140-M	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66-METAL	IRR 7,350,000	
17	THC-T220-P	2 MP high-performance CMOS-1920 x 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 5,250,000	
18	THC-T220-M	2 MP high-performance CMOS-1920 x 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 7,750,000	











19	THC-T240-P	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 6,750,000	
20	THC-T240-M	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 8,350,000	
21	Vari-Focal Series			
22	THC-B320-VF	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,,DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 13,600,000	
23	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 15,900,000	
24	THC-D320-VF	2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output- ,IK10-Full Metal	IRR 10,500,000	
25	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 11,900,000	
26	THC-T320 VF	2MP CMOS Sensor, 40m IR, EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 9,800,000	
27	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 11,200,000	
28	Turbo HD PTZ Camera			
29	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 920 × 1080 resolution 25x optical zoom, 16x digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 8D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	ناموجود	
30	PTZ-T4215I-D	1/2.8" HD progressive scan CMOS 920 × 1080 resolution 5x optical zoom, 16x digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 8D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	ناموجود	








31	PTZ-T5225I-A	1/2.8" HD progressive scan CMOS1920 x 1080 resolution 25x optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance3D intelligent positioning Switchable turbo HD and CVBS outputs	ناموجود	
32	DVR 4 Channel			
33	DVR-104G-F1	4-ch 1080p Mini 1U Lite H.264 DVR,5 signals input adaptively (HDTV/1/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 10,200,000	
34	DVR-204G-F1	Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 1-ch Up to 960P resolution), 1 SATA (6TB)interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 12,500,000	
35	DVR-204Q-F1	Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920x1080P: 12 fps/ch, 260 1U case-- HDMI outputHD1080p-Metal	IRR 13,200,000	
36	DVR-204Q-K1	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/1/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	IRR 15,200,000	
37	DVR-204U-F1	Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch IP video input(up to 6MP resolution) , 1 SATA (6 TB) - interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-- HDMI output HD1080p-Metal	IRR 19,800,000	
38	DVR-204U-K1	Self-adaptive HDTV/1/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV1 video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV1 signal	IRR 23,200,000	
39	DVR 8 Channel			
40	DVR-108G-F1	8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/1/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 16,200,000	

41	DVR-208G-F1	Recording Capability HD1080p Lite 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 19,800,000	
42	DVR-208Q-F1	Recording Capability 3MP 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case- HDMI output HD1080p-Metal	IRR 27,600,000	
43	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 29,800,000	
44	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- HDMI output 4K-Metal	IRR 43,500,000	
45	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 47,200,000	
46	Digital Video Recorder			
47	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 24,500,000	
48	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 28,600,000	
49	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case- HDMI output 1ch 4k-Metal	IRR 43,000,000	
50	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 46,800,000	

51	DVR-216Q-K2	<p>One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite</p>	IRR 51,200,000	
52	DVR-216U-F2	<p>Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-</p>	IRR 73,800,000	
53	DVR-216U-K2	<p>DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD – CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording</p>	IRR 78,900,000	

Hilook-NVR			
Items	Description	User Price	
1	IPC-B120 1/2.8" progressive scan CMOS-1920 x 1080@30fps -2.8 mm fixed lens- H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 14,200,000	
2	IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 16,300,000	
3	IPC-B140H 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 19,400,000	
4	IPC-B220 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 14,550,000	
5	IPC-B220-D 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 13,200,000	
6	IPC-T120 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR - H.264+&H.264-,2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 11,200,000	
7	IPC-T120-D 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 9,850,000	
8	IPC-T220-H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 13,900,000	

9	IPC-T240H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,--Support mobile monitoring via Hik-Connect *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 16,800,000	
10	IPC-D120	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 13,200,000	
11	IPC-D120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, --2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 15,800,000	
12	IPC-D140H	4.0 MP IR NetworkDome Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, 120 dB WDR.	IRR 16,700,000	
13	Vari-Focal Series			
14	IPC-B620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 28,300,000	
15	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 29,400,000	
16	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic--IP67	IRR 35,200,000	
17	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 38,600,000	
18	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 25,000,000	
19	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 23,700,000	

20	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 26,800,000	
21	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 28,300,000	
22	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 29,200,000	
23	PanoVu Mini Series IR Network PTZ Camera			
24	PTZ-P332ZI-DE3	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkage Up to 10 m IR radius Panoramic Camera Three 1/2.8" progressive scan CMOS I 3-ch 1920 x 1080@30fps resolution Horizontal FOV: 128.5° x 3 PTZ Camera 1/2.8" progressive scan CMOS I Up to 1920 x 1080@30fps resolution I 4x optical zoom, 8x digital zoom	ناموجود	
25	IP PTZ Camera			
26	PTZ-N2204I-DE3	1/2.8" progressive scan CMOS .Up to 1920 x 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance IK10, IP66 Support H.265+/H.265 video compression	ناموجود	
27	PTZ-N2404I-DE3	1/3" progressive scan CMOS .Up to 2560 x 1440@25fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance. IK10, IP66 Support H.265+/H.265 video compression	ناموجود	
28	PTZ-N4215-DE3	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	ناموجود	

29	PTZ-N4215I-DE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compressionUp to 24 programmable privacy masks Support ROI	ناموجود	
30	PTZ-N4225I-DE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IRUp to 100 m IR distance 25x optical zoom, 16x digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI	ناموجود	
31	PTZ-N5225I-AE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 150 m IR distance 25x optical zoom, 16x digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 24 VAC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI Support smart detection	ناموجود	
32	Network Video Recorder			
33	NVR-104-B	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p	IRR 10,200,000	
34	NVR-104-B/4P	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB , 4 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	ناموجود	
35	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 13,700,000	
36	NVR-108-B/8P	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB ,8 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	IRR 24,750,000	
37	NVR-104MH-C	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 16,500,000	

38	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	IRR 26,300,000	
39	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 22,400,000	
40	NVR-208MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 25,200,000	
41	NVR-108M-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB), 8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	IRR 42,500,000	
42	NVR-108M-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 36,000,000	
43	NVR-108M-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 16,200,000	
44	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP), Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 25,500,000	
45	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video), Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,800,000	
46	NVR-216MH-C/16P	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video) Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, -Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 69,400,000	



HOME - Bussiness		
Items	Description	User Price
Modem Router		
1	X6200-EU Linksys X6200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 433Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 12,400,000
2	XAC1200-EK Linksys XAC1200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 867Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 18,230,000
3	XAC1900-EK Linksys XAC1900 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 1300Mbps + 600Mbps; 4 x 10/100/1000 Ports; 2 x USB Ports; MIMO3x3; External Antennas	IRR 28,260,000
Wireless Router E-series		
5	E900-EE Linksys E900 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 2,990,000
6	E1200-M2 Linksys E1200 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 4,490,000
7	E1700-EK Linksys E1700 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100/1000 Ports; No USB; MIMO2x2; External Antennas	IRR 5,430,000
8	E2500-M2 Linksys E2500 Wireless-N Router; 802.11a/b/g/n; Dual Band; Max 300Mbps; 4 x 10/100/100 Ports; 1xUSB; MIMO2x2; Internal Antennas	IRR 6,550,000
Wireless Router EA-series		
9		

10	EA2750-M2	Linksys EA2750 Wireless-N Router; 802.11a/b/g/n; Dual Band Concurrent; Max 300Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,170,000
11	EA6100-EK	Linksys EA6100 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,260,000
12	EA6350-EK	Linksys EA6350 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 15,350,000
13	EA6900-M2	Linksys EA6900 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO3x3; External Antennas	IRR 21,930,000
14	EA7500-EU	Linksys EA7500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO3x3; External Antennas	IRR 25,270,000
15	EA8500-EU	Linksys EA8500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1733Mbps + 800Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 32,760,000
16	EA9500-EU	Linksys EA9500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2166Mbps + 1000Mbps; 8x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 53,360,000
17	Wireless Router WRT-series		
18	WRT1900ACS-EU	Linksys WRT1900ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 22,280,000
19	WRT1200AC-EU	Linksys WRT1200AC Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO2x2; External Antennas	IRR 17,780,000
20	WRT3200ACM-EU	Linksys WRT3200ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2600Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 35,560,000
21	WRT32X-EU	LINKSYS WRT32X WIFI ROUTER,AC3200 DUAL-BAND WI-FI GAMING ROUTER WITH KILLER PRIORITIZATION ENGINE; 4 Gigabit ports; 4 detach Antenna; 2 USB Ports	IRR 39,320,000
22	USB Adapter		
23	AE1200-EE	Linksys AE1200 Wireless-N USB Adapter; Single Band; Max 300Mbps	IRR 2,430,000
24	AE2500-EE	Linksys AE2500 Wireless-N USB Adapter; Dual Band; Max 300Mbps	IRR 3,900,000

25	AE6000-EE	Linksys AE6000 Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 3,900,000
26	WUSB6100M-EU	Linksys WUSB6100M Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 6,550,000
27	WUSB6300-EK	Linksys WUSB6300 Wireless-AC USB Adapter; Dual Band; Max 867Mbps	IRR 5,990,000
28	USB3GIG-EJ	Linksys USB 3.0 Gigabit Ethernet Adapter	IRR 2,990,000
29	Range Extender		
30	RE3000W-EK	Linksys RE3000W Range Extender; Single Band; 802.11b/g/n; Max 300Mbps; 1x10/100 Port	IRR 5,270,000
31	RE4100W-EU	Linksys RE4100W Range Extender; Dual Band; 802.11a/b/g/n; Max 300Mbps; 1x10/100 Port	IRR 6,360,000
32	RE6300-EU	Linksys RE6300 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 433Mbps; 1x10/100/1000 Port	IRR 9,300,000
33	RE6400-EU	Linksys RE6400 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port	IRR 9,730,000
34	RE6500-EU	Linksys RE6500 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 4x10/100/1000 Port; Audio Jack; Desktop	IRR 12,540,000
35	RE6700-EG	Linksys RE6700 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port; Audio Jack; Power Out	IRR 13,480,000
36	Switches (HOME)		
37	SE2500-EU	Linksys SE2500 Gigabit Switch; 5x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 4,120,000
38	SE2800-EU	Linksys SE2800 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 5,782,000
39	SE4008	Linksys SE4008 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving; Stacks over WRT1900AC	IRR 6,550,000
40	Switches (Business)		
41	LGS105-EU	5-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,100,000

42	LGS108-EU	8-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,900,000
43	LGS116-EU	16-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop; Wall Mount; Fanless; Power Saving; Adapter Included	IRR 15,110,000
44	LGS124-EU	24-Ports Gigabit ,Unmanaged, QOS, Metal, RackMount; 24x10/100/1000 Ports	IRR 21,520,000
45	LGS308-EU	8-Ports Gigabit; Smart, Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 9,770,000
46	LGS318-EU	18-Ports Gigabit 2 Combo Ports (RJ45 + SFP) , Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON, VLAN 802.1Q	IRR 22,590,000
47	LGS326-EU	26-Ports Gigabit, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 27,060,000
48	LGS528-EU	28-Ports Gigabit , Layer 3 Static Routing, 28Ports , 2 Combo Ports (RJ45 + SFP) Advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE-	IRR 43,760,000
49	LGS552-EU	52-Ports Gigabit , Layer 3 Static Routing, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports:	IRR 78,150,000
50	Switches POE		
51	LGS108P-EU	8-Ports Gigabit ,Unmanaged, 4 Ports POE, 50W, QOS, Metal,Wall Mount	IRR 13,020,000
52	LGS116P-EU	Gigabit ,Unmanaged, 16-Port (8POE), 80W, QOS, Metal, Wall Mount	IRR 21,160,000
53	LGS124P-EU	Gigabit, Unmanaged, 24-Port (12POE), 120W, QOS, Metal, RackMount	IRR 32,810,000
54	LGS308P-EU	8-Ports Gigabit ,Smart, 8Port POE 802.3af & 802.3at, 72W, Advances QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 18,310,000
55	LGS318P-EU	Gigabit ,Smart, 18-Ports (16POE) 802.3af & 802.3at, 125W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON.VLAN 802.1Q	IRR 46,650,000
56	LGS326P-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 192W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 65,000,000

57	LGS326MP-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 384W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 68,800,000
58	LGS528P-EU	28-Ports Gigabit , Layer 3 Static Routing, 24Ports POE 192W Budget, 2 Combo Ports (RJ45 + SFP),, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE	IRR 71,070,000
59	LGS552P-EU	Gigabit , Layer 3 Static Routing, 52-Ports (48 POE) 375W, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 52GE	IRR 117,230,000
60	Access Point		
61	LAPN300-EU	Single Band; 802.11n; Max 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 12,010,000
62	LAPN600-EU	Dual Band; 802.11n; Max 300 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 18,850,000
63	LAPAC1200-EU	Dual Band; 802.11ac; Max 867 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 23,250,000
64	LAPAC1750-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO 3x3	IRR 31,650,000
65	LAPAC1750 PRO-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 2*GigaEthernet; MIMO 3x3; High Gain Antenna	IRR 49,040,000
66	LAPAC2600-EU	Linksys Business Dual-Band Access Point AC2600	IRR 52,750,000
67	WAP300N-EE	Dual Band; 802.11n;Max 300Mbps;Bridge; Adapter only; Desktop;1*Fast Ethernet ; MIMO 2*2	IRR 5,610,000
68	WHW0302-ME new	LINKSYS VELOP	IRR 50,880,000
69	WAP750AC	Linksys WAP750AC AC750 Wi-Fi Access Point	IRR 8,930,000
70	VPN Router		
71	LRT214-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 1xWAN Port; Metal Case	IRR 19,140,000

72	LRT224-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 2xWAN Port; Metal Case; Load Balance; Smart Backup; Aggregate WAN1 + WAN2	IRR 19,930,000
73	Poe Injector		
74	LACPI30-EU	Linksys PoE Injector; 802.3af and 802.3at; 30Watts; Gigabit Ethernet; Wall Mount	IRR 5,470,000

**Equip Rack****Items****Description****User Price****ER Standing Rack IP42**

1	ERS - 4761	رک 47 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار،درب پشت فلزی	86,500,000
2	ERS - 4281	رک 42 یونیت-عمق 100-عرض 80 - درب جلو مشبک، درب پشت 2 لنگه مشبک	106,500,000
3	ERS - 4261	رک 42 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	66,500,000
4	ERS - 4268	رک 42 یونیت-عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	61,000,000
5	ERS - 4266	رک 42 یونیت-عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	53,200,000
6	ERS - 3761	رک 37 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	61,000,000
7	ERS - 3868	رک 37 یونیت-عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	53,000,000
8	ERS - 3866	رک 37 یونیت-عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	48,500,000
9	ERS - 3261	رک 32 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	58,000,000

10	ERS - 3268	رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۵۱,۵۰۰,۰۰۰
11	ERS - 3266	رک ۳۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۴۶,۵۰۰,۰۰۰
12	ERS - 2861	رک ۲۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۳,۵۰۰,۰۰۰
13	ERS - 2868	رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۵,۰۰۰,۰۰۰
14	ERS - 2866	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۰,۵۰۰,۰۰۰
15	ERS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۴۵,۵۰۰,۰۰۰
16	ERS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۹,۰۰۰,۰۰۰
17	ERS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۶,۰۰۰,۰۰۰
18	ERS - 1868	رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۶,۰۰۰,۰۰۰
19	ERS-1766	رک ۱۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۳۳,۵۰۰,۰۰۰
20	ERS-1468	رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۲,۵۰۰,۰۰۰
21	ERS-1466	رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۹,۵۰۰,۰۰۰
22	ER Wall Mount		
23	ERW - 1266	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۱۲,۵۰۰,۰۰۰
24	ERW - 0966	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۱۰,۶۰۰,۰۰۰
	ERW - 0666	رک دیواری - ۶ یونیت- عمق ۶۰ ، عرض ۶۰	۷,۳۰۰,۰۰۰
25	ERW - 0664	رک دیواری - ۶ یونیت- عمق ۴۵ ، عرض ۶۰	۶,۹۰۰,۰۰۰

26	ERW - 0465D	DVR رک دیواری - ۴ یونیت - عمق ۵۰ ، عرض ۶۰	Call
34	ER OUTDOOR RACK		
35	ERO - 0745	OUTDOOR رک ۷ یونیت - عمق ۴۵	۳۳,۰۰۰,۰۰۰
36	ERO - 0966	OUTDOOR رک ۹ یونیت - عمق ۶۰	۳۹,۰۰۰,۰۰۰
37	ERO - 1266	OUTDOOR رک ۱۲ یونیت - عمق ۶۰	۵۵,۰۰۰,۰۰۰
38	ERO - 1866	OUTDOOR رک ۱۸ یونیت - عمق ۸۰	۷۲,۰۰۰,۰۰۰
39	شامل تخفیف نمی گردد OUTDOOR لازم به ذکر است رک های		
40	ER MAIN FRAME		
41	ERM - 4202	رک ۴۲ یونیت - آزمایشگاهی - دو پنل	CALL
42	ERM - 4201	رک ۴۲ یونیت - آزمایشگاهی - تک پنل	CALL
43	ERM - 3202	رک ۳۲ یونیت - آزمایشگاهی - دو پنل	CALL
44	Shelf		
45	ERA - SSW	طبقه ثابت رک های دیواری	۱,۰۰۰,۰۰۰
46	ERA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۱,۶۰۰,۰۰۰
47	ERA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۲,۲۰۰,۰۰۰
48	ERA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۲,۸۰۰,۰۰۰
49	ERA - SM 60	سینی متحرک رک ۶۰ سانتیمتر	۳,۶۰۰,۰۰۰
50	ERA - SM 80	سینی متحرک رک ۸۰ سانتیمتر	۳,۶۰۰,۰۰۰
51	ERA - SM 10	سینی متحرک رک ۱۰۰ سانتیمتر	۳,۶۰۰,۰۰۰
52	Power Module		
53	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۱,۲۵۰,۰۰۰
54	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۸۳۰,۰۰۰
55	Accessories		
56	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۲,۰۰۰,۰۰۰

57	ERA - SCR - 20	پیچ و کزنات مخصوص رک بسته ۱۰ تایی	۱۲۰,۰۰۰
58	ERA - TR - 20	حرارت سنج یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان	۱۴,۰۰۰,۰۰۰
59	ERA - FN - 20	فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۱,۰۰۰,۰۰۰
60	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ	۶۷۰,۰۰۰
61	ERA - CM - 20	نگهدارنده عمودی کابل	۱۲۰,۰۰۰
62	ERA - CM - 30	نگهدارنده کابل درپوش دار	۶۵۰,۰۰۰
63	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۳۹۰,۰۰۰
64	Blank Panel		
65	ERA - BLA - 10	بلانک پنل ، ۱ یونیت	۳۰۰,۰۰۰
66	ERA - BLA - 20	بلانک پنل ، ۲ یونیت	۴۰۰,۰۰۰
67	ERA - BLA - 30	بلانک پنل ، ۳ یونیت	۵۵۰,۰۰۰
68	ERA - BLA - 40	بلانک پنل ، ۴ یونیت	۶۵۰,۰۰۰
69	ERA - BLA - 50	بلانک پنل ، ۱ یونیت فرچه ای	۷۰۰,۰۰۰
70	Doors		
71	EDM - 4261	درب مشبک ۴۲ یونیت ساده عرض ۶۰ به همراه قفل	۷,۵۰۰,۰۰۰
72	EDM - 3801	تفاوت قیمت درب مشبک ۳۸ یونیت تک لنگه با درب شیشه ای	۷,۵۰۰,۰۰۰
73	EDM - 3201	تفاوت قیمت درب مشبک ۳۲ یونیت تک لنگه با درب شیشه ای	۷,۵۰۰,۰۰۰
74	EDM - 2801	تفاوت قیمت درب مشبک ۲۸ یونیت تک لنگه با درب شیشه ای	۷,۵۰۰,۰۰۰
لازم به ذکر است درب مشبک شامل تخفیف نمی گردد			