

هایک ویژن تهران




نمایندگی رسمی هایک ویژن در ایران









09906500074






تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران

Hikvisiontehran







Turbo HD Camera - DVR








Items	Description	User Price	
Turbo HD - 2MP			
DS-2CE16D0T-ITPF 2.8	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	IRR 7,920,000	
DS-2CE16D0T-ITPFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 11,600,000	
DS-2CE16D0T-ITF	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	تماس بگیرید	









DS-2CE16D0T-ITFS	<p>2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 12,980,000	
DS-2CE16D0T-EXIPF(2.8)	<p>2 MP Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)</p>	IRR 7,550,000	
DS-2CE16D0T-EXIF	<p>2 MP Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens.. Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)</p>	IRR 10,050,000	
DS-2CE17D0T-IT1F	<p>2 MP Fixed Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 14,760,000	
DS-2CE17D0T-IT3F (2.8)	<p>2 MP Fixed Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 16,390,000	
DS-2CE16D0T-VFIR3F	<p>2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm</p>	IRR 26,370,000	
DS-2CE76D0T-ITPF	<p>2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 7,920,000	
DS-2CE76D0T-ITPFS	<p>2 MP Audio Fixed Turret Camera 2 MP coaxial audio camera, Enhancing safety with discreet and economical built-in microphone, Transmits audio over the coaxial cable. EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 11,560,000	








DS-2CE76D0T-ITMFS	<p>2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 14,760,000	
DS-2CE76D0T-ITMF	<p>2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 13,720,000	
DS-2CE56D0T-VFIR3F	<p>2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4</p>	IRR 26,370,000	
Turbo HD - 2MP - ColorVu			
DS-2CE70DF0T-PF ColorVu	<p>2 MP ColorVu Indoor Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution, 24/7 color imaging with F1.0 aperture 3D DNR technology delivers clean and sharp images.2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)</p>	IRR 16,580,000	
DS-2CE70DF3T-PF ColorVu	<p>2 MP ColorVu Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution,24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images,2.8 mm, 3.6 mm, 6 mm fixed focal lens,Up to 40 m white light distance for bright night imaging,One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 19,090,000	
DS-2CE12DF3T-F (2.8)	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 27,130,000	
DS-2CE72DFT-FC	<p>2 MP ColorVu Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution,24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images,2.8 mm, 3.6 mm, 6 mm fixed focal lens,Up to 40 m white light distance for bright night imaging,One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 10,520,000	








DS-2CE72DF3T-F 3.6 ColorVu	<p>2 MP ColorVu Fixed Turret Camera</p> <p>High quality imaging with 2 MP, 1920 × 1080 resolution,24/7 color imaging with F1.0 aperture</p> <p>Clear imaging against strong back light due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images,2.8 mm, 3.6 mm, 6 mm fixed focal lens,Up to 40 m white light distance for bright night imaging,One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p>	IRR 21,100,000	
DS-2CE10DF3T-FS	<p>2 MP ColorVu Fixed Mini Bullet Camera</p> <p>2 MP full time color bullet camera, 24/7 full color imaging, Warm supplemental light with 20 m range</p> <p>Clear imaging even against strong back lighting due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 24,110,000	
DS-2CE72DF3T-F ColorVu	<p>2 MP ColorVu Fixed Turret Camera</p> <p>High quality imaging with 2 MP, 1920 × 1080 resolution,24/7 color imaging with F1.0 aperture</p> <p>Clear imaging against strong back light due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images,2.8 mm, 3.6 mm, 6 mm fixed focal lens,Up to 40 m white light distance for bright night imaging,One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p>	IRR 21,100,000	
DS-2CE10DFT-F ColorVu	<p>2 MP ColorVu Fixed Mini Bullet Camera</p> <p>2 MP full time color bullet camera, 24/7 full color imaging, Warm supplemental light with 20 m range</p> <p>Clear imaging even against strong back lighting due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 19,400,000	
Turbo HD - 2MP - Ultra Low Light Series			
DS-2CE76D3T-ITPF	<p>2 MP Ultra Low Light Indoor Fixed Turret Camera, 2 MP turret camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.005 lux</p> <p>Clear imaging even against strong back lighting due to 120 dB true WDR technology,3D DNR technology delivers clean and sharp images, EXIR 2.0: advanced infrared technology with 30 m IR distance, 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 14,250,000	
DS-2CE76D3T-ITMF	<p>2 MP Ultra Low Light Fixed Mini Bullet Camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.005 lux</p> <p>Clear imaging even against strong back lighting due to 120 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 16,880,000	
DS-2CE78D0T-ITFS	<p>2 MP Ultra Low Light Fixed Mini Bullet Camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.005 lux</p> <p>Clear imaging even against strong back lighting due to 120 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 16,880,000	




DS-2CE16D3T-ITF	<p>2 MP Ultra Low Light Fixed Mini Bullet Camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 16,880,000	
DS-2CE16D8T-IT3E	<p>2 MP Ultra Low Light Fixed Mini Bullet Camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	تماس بگیریید	
Turbo HD - 5MP			
DS-2CE16H0T-ITF	<p>5 MP Fixed Mini Bullet Camera, 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 14,190,000	
DS-2CE16H0T-ITPF	<p>5 MP Fixed Mini Bullet Camera, 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 13,040,000	
DS-2CE16H0T-ITFS	<p>5 MP Audio Fixed Mini Bullet Camera, 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone, Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE16H0T-ITPFS	<p>5 MP Audio Fixed Mini Bullet Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 15,200,000	








DS-2CE16H0T-IT1F	<p>5 MP Fixed Mini Bullet Camera, 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE16H0T-IT3F	<p>5 MP Fixed Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE16H0T-IT5F	<p>5 MP Fixed Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE17H0T-IT1F	<p>5 MP Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 2.4 mm, 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 20,040,000	
DS-2CE17H0T-IT3FS(2.8MM)	<p>5 MP Fixed Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 23,200,000	
DS-2CE17H0T-IT3F	<p>High quality imaging with 5 MP, 2560 × 1944 resolution 2.8 mm, 3.6 mm, 6 mm, 8mm, 12mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 17,350,000	
DS-2CE17H0T-IT5F	<p>5 MP Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 80 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	IRR 20,280,000	






DS-2CE16H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 28,750,000	
DS-2CE10HFT-F28 (2.8)	5 MP Fixed Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 24,630,000	
DS-2CE12HFT-F28 (2.8)_	5 MP Fixed Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 27,950,000	
DS-2CE76H0T-ITMF	5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	تماس بگیریید	
DS-2CE76H0T-ITMFS	5 MP coaxial audio camera, Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 19,520,000	
DS-2CE76H0T-ITPF 2.8	5 MP Indoor Fixed Turret Camera 5 MP turret camera EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	تماس بگیریید	
DS-2CE76H0T-ITPFS	5 MP Indoor Fixed Turret Camera 5 MP turret camera EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 13,530,000	
DS-2CE78H0T-IT1F (2.4MM)	5 MP turret camera EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	تماس بگیریید	

DS-72HFT-F28 (2.8)	<p>5 MP Fixed Bullet Camera 5 MP bullet camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE78H0T-IT3F	<p>5 MP turret camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	IRR 21,090,000	
DS-2CE56H0T-IT1F (2.4)	<p>5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67</p>	تماس بگیریید	
DS-2CE56H0T-IT3F	<p>5 MP Fixed Bullet Camera 5 MP bullet camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE56H0T-ITMF	<p>5 MP Fixed Bullet Camera 5 MP bullet camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	تماس بگیریید	
DS-2CE78H0T-IT3F	<p>5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67</p>	IRR 21,090,000	
DS-2CE56H0T-IT3ZF	<p>5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67</p>	تماس بگیریید	
Turbo HD - 8MP			

DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	تماس بگيريد	
DS-2CE18U8T-IT3	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 63,400,000	
Turbo HD PTZ Camera			
DS-2AE4225TI-D	High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology -Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 × optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66)	تماس بگيريد	
Turbo HD DVR 1080p / 3MP / 4MP lite			
DS-7204HQHI-K1	Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	تماس بگيريد	
DS-7204HTHI-K1	Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	تماس بگيريد	
IDS-7204HQHI-M1/S	4-ch 1080p 1U H.265 AcuSense DVR 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/1/AHD/CVI/CVBS/IP) Up to 6 network cameras can be connected.	IRR 35,400,000	
DS-7208HQHI-K1	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	تماس بگيريد	

IDS-7208HQHI-M1/S	<p>8-ch 1080p 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/1/4CIF/CVBS/IP) Up to 12 network cameras can be connected.</p>	IRR 56,110,000	
DS-7116HQHI-K1	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity</p>	IRR 66,600,000	
DS-7208HGHI-F1	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	تماس بگیریید	
DS-7208HGHI-F2	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	تماس بگیریید	
DS-7208HTHI-K2	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	تماس بگیریید	
DS-7216HGHI-K1	<p>16-ch 1080p Lite 1U H.265 DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0.H.265 Pro+/H.265 Pro/H.265 video compressionHDTV/1/4CIF/CVBS/IP video inputAudio via coaxial cable Up to 18-ch IP camera inputs (up to 5 MP)Up to 1080p Lite@15 fps encoding capability Max. 1200 m for 720p HDTV signal</p>	IRR 48,040,000	
DS-7216HQHI-K1	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 102,170,000	

DS-7216HQHI-K2	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	تماس بگیرید	
IDS-7232HQHI-M2/S	Analog video input 32-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	تماس بگیرید	
DS-7232HQHI-K2	Analog video input 32-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 218,660,000	
Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite			
DS-7204HUHI-K1	Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - Frame rate: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 53,850,000	
IDS-7204HUHI-M1/S	Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - Frame rate: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 54,300,000	
DS-7208HUHI-M1/S	8-ch 5 MP 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/HD/CVI/CVBS/IP)	IRR 87,060,000	
DS-7216HUHI-M2/S	Analog video input 16-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 167,870,000	

DS-7316HUHI-F4/N	Analog video input 16-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 316,530,000	
DS-7208HUHI-K1	Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate:8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	تماس بگیریید	
DS-7216HUHI-K2	Analog video input 16-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 167,870,000	
Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)			
DS-7204HUHI-K1/P	Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - Frame rate: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch 2K (2560 × 1440)/60Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable	IRR 47,750,000	
DS-7208HUHI-K2/P	Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	تماس بگیریید	

هایک ویژن تهران




نمایندگی رسمی هایک ویژن در ایران








09906500074








تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران








Hikvisiontehran






Network Camera - NVR

Items	Description	User Price	
Lite Mini Bullet Series			
DS-2CD1023G0E-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 21,380,000	
DS-2CD1021G0E-I	Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)/(N), H.265 / H.264+ & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE Rs. 0.001Is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary.	تماس بگیرید	
DS-2CD1023G0-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) -	IRR 21,380,000	

DS-2CD1023G0-IUF	High quality imaging with 2 MP resolution, Efficient H.265+ compression technology , Clear imaging against strong back light due to DWDR technology , Water and dust resistant (IP67) , EXIR 2.0: advanced infrared technology with long IR range , Support up to 256 GB SD card storage , Built-in microphone for real-time audio security	IRR 31,770,000	
DS-2CD1047G0-L ColorVu Lite	4 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 38,760,000	
DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 31,500,000	
DS-2CD1057G0-L	5MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7	IRR 45,920,000	
DS-2CD1053G0-I	5 MP Fixed Bullet Network Camera High quality imaging with 5 MP resolution. Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR ₃ (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	IRR 31,370,000	
Lite Dome Series			
DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 20,940,000	
DS-2CD1323G0-IUF (2.8)	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone	IRR 27,110,000	

DS-2CD1327G0-L ColorVu	2 MP ColorVu Lite Fixed Turret Network Camera,High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology,Water and dust resistant (IP67), 24/7 colorful imaging	3,216,000	
DS-2CD1347G0-L ColorVu	High quality imaging with 4 MP resolution. Excellent low-light performance.Efficient H.265+ compression technology. Water and dust resistant (IP67). 24/7 colorful imaging.	IRR 57,790,000	
DS-2CD1123G0E-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 23,190,000	
DS-2CD2525FWD-I	2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection Sub built-in microphone, audio and alarm interface available	IRR 49,840,000	
DS-2CD2126G2-ISU 2.8mm	2 MP AcuSense Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle classification based on deep learning -SU: Built-in microphone for real-time audio security, Audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 63,530,000	
DS-2CD2123G2-I (2.8)	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 41,920,000	
DS-2CD2125FHWD-IS	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10)	تماس بگیرید	

DS-2CD2H25FWD-I2S	<p>High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10)</p>	IRR 108,180,000	
DS-2CD1143G0-I	<p>4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)</p>	IRR 34,790,000	
DS-2CD1143G0-IUF	<p>4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)</p>	IRR 39,620,000	
DS-2CD1153G0-I	<p>5 MP Fixed Dome Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range</p>	IRR 43,860,000	
Mini Bullet Series			
DS-2CD2025FWD-I	<p>2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP67), Robust structure design with full metal material.</p>	تماس بگیریید	
DS-2CD2021G1-I (2.8)	<p>High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage</p>	IRR 38,930,000	
DS-2CD2023G2-I (2.8)	<p>High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning</p>	IRR 42,810,000	








<p>DS-2CD2027G2-L (2.8)</p>	<p>High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology 24/7 colorful imaging Focus on human and vehicle classification based on deep learning Water and dust resistant (IP67)</p>	<p>IRR 55,340,000</p>	
<p>DS-2CD2043G2-I (2.8)</p>	<p>4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	<p>IRR 53,920,000</p>	
<p>DS-2CD2043G0-IU (2.8)</p>	<p>4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	<p>IRR 55,990,000</p>	
<p>DS-2CD2043G2-I2.8mm</p>	<p>4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning</p>	<p>تماس بگیریید</p>	
<p>DS-2CD2045FWD-I</p>	<p>4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal material.</p>	<p>تماس بگیریید</p>	
<p>DS-2CD2047G2-L (2.8)</p>	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)</p>	<p>IRR 47,650,000</p>	







DS-2CD2063G2-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	تماس بگیریید	
DS-2CD2063G2-I2.8mm	6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning -U: Built-in microphone for real-time audio security Water and dust resistant (IP67)	تماس بگیریید	
DS-2CD2083G2-I (2.8)	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	تماس بگیریید	
DS-2CD2083G2-I2.8mm	8 MP AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning -U: Built-in microphone for real-time audio security Water and dust resistant (IP67)	تماس بگیریید	
DS-2CD2087G2-LU (2.8MM)	4 K ColorVu Fixed Bullet Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology Focus on human and vehicle classification based on deep learning 24/7 colorful imaging Built-in microphone for real-time audio security (-U)	IRR 110,790,000	
Dome Series			
DS-2CD2143G2-IU	4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	IRR 44,980,000	




DS-2CD2347G2-L (2.8)	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)</p>	IRR 61,480,000	
DS-2CD2347G2-LU (2.8)	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)</p>	IRR 63,530,000	
DS-2CD1353G0-I (2.8 MM)	<p>5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security</p>	IRR 41,640,000	
DS-2CD1357G0-L	<p>5MP ColorVu Lite Fixed Turret Network Camera High quality imaging with 5 MP resolution ☑ Excellent low-light performance ☑ Efficient H.265+ compression technology ☑ Water and dust resistant (IP67) ☑ 24/7 colorful imaging</p>	IRR 45,920,000	
DS-2CD2145FWD-IS	<p>4 MP Powered-by-DarkFighter Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10)</p>	تماس بگیریید	
DS-2CD2146G2-I	<p>4 MP AcuSense Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time auto security(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)</p>	تماس بگیریید	






DS-2CD2147G2-LSU (2.8mm)	<p>4 MP ColorVu Fixed Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology 24/7 colorful imaging Focus on human and vehicle targets classification based on deep learning -SU: Built-in microphone for real-time audio security, audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)</p>	تماس بگیریید	
DS-2CD2163G2-IU	<p>6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone</p>	تماس بگیریید	
DS-2CD2166G2-I (2.8mm)	<p>6 MP AcuSense Fixed Dome Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)</p>	تماس بگیریید	
DS-2CD2183G2-IU	<p>8 MP AcuSense Vandal Fixed Dome Network Camera High quality imaging with 8 MP resolution Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	تماس بگیریید	
DS-2CD2186G2-I (2.8mm)	<p>4K Acusense Fixed Dome Network Camera High quality imaging with 8 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)</p>	تماس بگیریید	
DS-2CD2183G0-IS	<p>8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors</p>	تماس بگیریید	

DS-2CD2185FWD-IS	<p>4K Fixed Dome Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials.</p>	تماس بگيريد	
Bullet Series			
DS-2CD2T43G0-IS	<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range</p>	تماس بگيريد	
DS-2CD2T43G0-I8	<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range</p>	تماس بگيريد	
DS-2CD2T43G2-2I (2.8)	<p>High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67). -2I: up to 60 m Focus on human and vehicle targets classification based on deep learning-- 2.8mm</p>	IRR 58,630,000	
DS-2CD2T43G2-4I (4mm)	<p>High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67). -4I: up to 80 m Focus on human and vehicle targets classification based on deep learning-- 4mm</p>	IRR 65,480,000	
DS-2CD2T45FWD-IS lenz4	<p>4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	تماس بگيريد	





DS-2CD2T45FWD-I82.8mm	<p>4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials</p>	تماس بگیریید	
DS-2CD2T46G2-4I (2.8mm)	<p>4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)</p>	تماس بگیریید	
DS-2CD2T46G2-ISU/SL2.8mm	<p>4 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Active strobe light and audio alarm to warn intruders off</p>	تماس بگیریید	
Ds-2CD2T47G2-L	<p>4 MP ColorVu Fixed Bullet Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)</p>	تماس بگیریید	
DS-2CD2T63G0-I8	<p>6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range</p>	تماس بگیریید	
DS-2CD2T63G2-4I(4MM)	<p>High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)</p>	IRR 64,510,000	
DS-2CD2T66G2-2I (2.8mm)	<p>6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)</p>	تماس بگیریید	

DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	تماس بگیریید	
DS-2CD2T83G2-4I(4MM)	High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 57,670,000	
DS-2CD2T86G2-4I (2.8mm)	4K AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	IRR 77,840,000	
Exir Dome Series			
DS-2CD2327WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	تماس بگیریید	
DS-2CD2345FWD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	تماس بگیریید	
Mini Dome Series			
DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	تماس بگیریید	





DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO	تماس بگیریید	
DS-2CD2525FWD-I	2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection	IRR 49,840,000	
Lite Bullet Vari-Facal Motorized Series			
DS-2CD1623G0-I	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	تماس بگیریید	
DS-2CD1623G0-IZ	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	تماس بگیریید	
DS-2CD1643G0-IZ	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 61,800,000	
DS-2CD1653G0-I	5 MP Varifocal Bullet Network Camera. High quality imaging with 5 MP resolution; Efficient H.265+ compression technology; Clear imaging even with strong	تماس بگیریید	
Lite Dome Vari-Facal Series			
DS-2CD1743G0-IZ	4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens	IRR 69,240,000	

DS-2CD1753G0-I	<p>5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range</p>	تماس بگیریید	
Bullet Vari-Facal Motorized Series			
DS-2CD2625FWD-IZS	<p>2MP Powered by DarkFighter Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.</p>	IRR 110,210,000	
DS-2CD2632F-I	<p>3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+ , dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P</p>	IRR 60,500,000	
DS-2CD2643G2-IZS	<p>4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology, (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning</p>	IRR 96,030,000	
DS-2CD2645FWD-IZS	<p>4 MP Powered-by-DarkFighter Varifocal Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring</p>	تماس بگیریید	
DS-2CD2663FG0-IZS	<p>6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z: Motorized VF lens</p>	تماس بگیریید	
DS-2CD2683G2-IZS	<p>8 MP AcuSense Motorized Varifocal Bullet Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	IRR 90,690,000	


DS-2CD2685FWD-IZS	<p>8 MP AcuSense Motorized Varifocal Bullet Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	تماس بگیریید	
DS-2CD2683G0-IZS	<p>8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens</p>	تماس بگیریید	
DS-2CD2686G2-IZS (2.8-12mm)	<p>High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)</p>	تماس بگیریید	
Dome Vari-Facal Motorized Series			
DS-2CD2743G2-IZS	<p>4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials</p>	IRR 97,950,000	
DS-2CD2745FWD-IZS	<p>4 MP Powered-by-DarkFighter Varifocal Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials</p>	تماس بگیریید	
DS-2CD2783G2-IZS	<p>8 MP AcuSense Motorized Varifocal Dome Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	IRR 83,742,500	

DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 ×2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	تماس بگیریید	
DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	تماس بگیریید	
DS-2CD2786G2-IZS	4K AcuSense Varifocal Dome Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)	تماس بگیریید	
Fish Eye Series			
DS-2CD2955FWD-I	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range	IRR 126,380,000	
DS-2CD6332FWD-IS	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range	تماس بگیریید	
DS-2CD2955FWD-IS	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	تماس بگیریید	


Cube Smart Series

DS-2CD2420F-I(W)	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB- IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker -Support Wi-Fi, support WPS configuration with one touch - Support PIR(Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	تماس بگیریید	
DS-2CD2421G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	تماس بگیریید	
DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	تماس بگیریید	
DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	تماس بگیریید	


Pin Hole Series

DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	تماس بگیریید	
--------------	---	--------------	---






2Q Smart Series






DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	تماس بگیریید	
-----------------	--	--------------	---






2U Smart Series









DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	تماس بگيريد	
-----------------	--	-------------	---









IP PTZ Camera










DS-2DE4A225IW-DE	4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome High quality imaging with 2 MP resolution,Excellent low-light performance via powered-by, DarkFighter technology, Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to monitor zones of interest,25x optical zoom allows for closer viewing of subjects in expansive areas,Up to 50m IR range ensures safety at night (IP66)	IRR 124,900,000	
DS-2DE4220IW-DE	2MP 20× Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	call	
DS-2DE4225IW-DE T5	2MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 × 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	157,470,000	
DS-2DE4425IW-DE T5	4MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 × 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	210,020,000	
DS-2DE5432IW-AE-S5	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm Face capture: Up to 5 faces captured at the same time	تماس بگيريد	









<p>DS-2DE5220IW-AE</p>	<p>DS-2DE5220IW-AE 2MP 20x Network IR Speed Dome</p> <p>2.54cm(1/2.8") Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR</p> <p>3D intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply</p>	<p>231,170,000</p>	
<p>DS-2DE4A320IW-DE</p>	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance</p>	<p>IRR 274,170,000</p>	
<p>DS-2DF6A236X-AEL</p>	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance</p>	<p>IRR 520,800,000</p>	
<p>DS-2CDE5432IW-AE</p>	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm Face capture: Up to 5 faces captured at the same time</p>	<p>IRR 229,050,000</p>	
<p>DS-2DE5230W-AE</p>	<p>2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s</p>	<p>call</p>	
<p>DS-2CD5220IW-AE</p>	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance</p>	<p>IRR 231,170,000</p>	



DS-2DF5276-AE3	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance</p>	IRR 562,530,000	
DS-2DF5276-AEL	<p>5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance</p>	IRR 447,450,000	
DS-2DE7232IW-AE	<p>2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression</p>	call	
NVR-Monitor			
DS-7600NI-E1/A	<p>Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed</p>	IRR 164,300,000	
NVR 4 Channel			
DS-7104NI-Q1/M	<p>IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity</p>	26,860,000	
DS-7104NI-Q1	<p>4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output</p>	تماس بگیریید	

DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 50,140,000	
DS-7604NI-K1/4P	IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 58,960,000	
NVR 8 Channel			
DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 38,480,000	
DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
DS-7608NI-Q2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	call	

DS-7608NI-Q1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity for each disk	IRR 35,500,000	
DS-7608NI-Q2	Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 61,800,000	
DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	54,810,000	
DS-7608NI-K1/8P	8-ch 1U 8 PoE 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 69,090,000	
DS-7608NI-K2	8-ch 1U 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity 1 HDMI and 1 VGA interfaces, both interfaces support independent video output 2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD) Up to 80 Mbps incoming bandwidth	تماس بگیریید	
NVR 16 Channel			
DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 48,200,000	
DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	69,950,000	
DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 107,470,000	

DS-7616NI-K1	Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity Up to 160 Mbps incoming bandwidth	تماس بگيريد	
DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	78,210,000	
DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس بگيريد	
DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 138,740,000	
DS-7716NI-Q4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 208,700,000	
DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 141,175,000	
DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call	
Network Video Recorders- Ultra Series			
DS-8616NI-K8	16-ch 2U 4K NVR,Up to 16 channel IP cameras can be connected,Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected,2 HDMI (different source) and 2 VGA (different source) interfaces,8 HDD can be used for continuous video recording,Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition)	IRR 147,000,000	
NVR 32 Channel			
DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس بگيريد	

DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس بگیرید	
DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	176,640,000	
IDS-7732NXI-I4/8S	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 508,940,000	
DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 265,500,000	
DS-8632NI-K8	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 218,820,000	
IDS-9632NXI-I8/4F	32-ch 2U 4K DeepinMind NVR H.265+/H.265/H.264+/H.264 video formats Up to 32 channel IP cameras can be connected 8 HDD can be used for continuous video recording Intelligent analytics based on deep learning algorithm	IRR 2,274,450,000	
DS-9632NI-I8	32-ch 2U 4K NVR Up to 64 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces	IRR 626,320,000	
DS-9632NI-I16	32-ch 3U 4K NVR Up to 32 channel IP cameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions	715,640,000	

<p>DS-9664NI-I8</p>	<p>64-ch 2U 4K NVR Up to 64 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera</p>	<p>682,530,000</p>	
<p>DS-9664NI-I16</p>	<p>64-ch 3U 4K NVR Up to 64 channel IP cameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions</p>	<p>1,029,160,000</p>	

هایک ویژن تهران

نماینده رسمی هایک ویژن در ایران















09906500074









تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران

Hikvisiontehran

Accessories

	Items	Description	User Price	
Switches				
1	DS-3E0105P-E/M	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af PoE power budget 35W	Call	
2	DS-3E0105P-E	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	Call	
3	DS-3E0109P-E/M	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af, PoE power budget 60W	Call	
4	DS-3E0109P-E	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	Call	
5	DS-3E0318P-E	L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	Call	
6	DS-3E0326P-E	L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	Call	
7	DS-3E1310P-E	L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	Call	
8	DS-3E1318P-E	802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss, Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission, VLAN configurable Port trunk, multicast and port mirroring, WEB management, Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation	Call	
Cables				
10	DS-1LN6-UE-W	UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 46,940,000	
11	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 51,660,000	
12	Brackets			

13	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 12,000,000	
14	DS-1602ZJ-pole	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	Call	
15	DS-1605ZJ	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	Call	
16	DS-1661ZJ	Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: -116.5×200mm-Weight: -600g	IRR 7,490,000	
17	DS-1662ZJ	Pendant mount , Hik white , Aluminum alloy , Ø116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 8,600,000	
18	DS-1663ZJ	Ceiling mount , Hik white , Aluminum alloy , Ø116.5×57mm-Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
19	DS-1693ZJ	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	Call	
20	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 2,640,000	
21	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Ø135×182×120mm Suitable for: DS-2CD27xx	Call	
22	Keyboard			
23	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	Call	
24	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	Call	
25	Tester			
26	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	Call	
27	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 138,420,000	
28	POE INJECTOR			
	DS-POE-60W ULTRA INJECTOR	Hikvision DS-POE-60W PoE Injector for Hikvision PTZ.	IRR 19,000,000	
	Adapters			

29	AD-121/P	12V-1A	IRR 420,000	
30	AD-122/P	12V -2A	IRR 450,000	
31	AD-122/PL	12V-2A	IRR 480,000	
32	AD-125/PL	12V -5A	IRR 800,000	
33	AD-12A/M	12V -10A-METAL	IRR 1,180,000	
34	AD-12F/M	12V -15A-METAL	IRR 1,600,000	
35	AD-12K/MF	12V -20A-METAL WITH FAN	IRR 1,840,000	
36	AD-12U/MF	12V -30A-METAL WITH FAN	IRR 2,550,000	

هایک ویژن تهران

نمایندگی رسمی هایک ویژن در ایران

09906500074












تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران

























Hikvisiontehran











DAHUA - camera,xvr










Items	Description	User Price	با گارانتی الماس	با گارانتی فراگستر	
CVI		(با گارانتی پارس ارتباط)	USER PRICE ایران	گارانتهی فراگستر	
1	DH-HAC-HFW1500THP-I8-0360B 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30	IRR 16,650,000	IRR 15,600,000		
2	DH-HAC-HDW1500TRQP-A 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera * The parameters and datasheets below can only be applied to 1500-S2 series. * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. > Max 25 fps@5MP (16:9 video output) > Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable	IRR 14,280,000	IRR 13,300,000	IRR 13,000,000	
3	DH-HAC-HDW1500TLMQP-0280B-S2 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera* The parameters and datasheets below can only be applied to 1500-S2 series. * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. > Max 25 fps@5MP (16:9 video output)> Quick-to-install eyeball saves installation time > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)	IRR 15,220,000			
	DH-HAC-HFW1500TP-0280B-S2		IRR 12,200,000		












	DH-HAC-HFW1500TP-0360B-S2		IRR 15,060,000			
4	DH-HAC-HFW1500TP-A-S2-0360B	<p>SMP HDCVI IR Bullet Camera. Max. 20fps@5MP</p> <ul style="list-style-type: none"> · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V 	IRR 15,610,000			
5	DH-HAC-HFW1500DP(S)	<p>5Megapixel 1/2.7" CMOS 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P 3.6mm fixed lens & 6mm Fixed Lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable Supports OSD Menu Max. IR length 80m, Smart IR IP67, DC12V</p>	IRR 21,010,000	IRR 18,700,000		
6	DH-HAC-HDW1500TQP-A(S)	<ul style="list-style-type: none"> · Max 25 fps@5MP (16:9 video output) · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens (2.8 mm, 6 mm optional) · Built-in mic(-A) · Max. IR length 40 m, Smart IR 				
7	DH-HAC-HFW1500SLP	<ul style="list-style-type: none"> · 1/2.7" Progressive CMOS · HD and SD output switchable · Day/Night (ICR), BLC / HLC / DWDR / AGC · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12 · 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P 				
8	DH-HAC-HFW1500RP-Z-IRE6	<ul style="list-style-type: none"> · Max. 20fps@5MP(2592x1944). 1/2.7" Progressive CMOS · 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P · HD and SD output switchable. Built-in mic · 2.7-12mm motorized lens · IP67, DC12V · Max. IR length 60m, Smart IR 	IRR 30,150,000			
9	DH-HAC-HFW1500CMP	<p>HAC-HFW1500CM-A-POC</p> <p>5MP Starlight HDCVI POC IR Bullet Camera</p> <p>* In order to use the SMP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.</p> <p>>The parameters and datasheets below can only be applied to 1500-S2 series.> Max 25 fps@5MP (16:9 video output)> CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)> Max. IR length 30m, Smart IR> Built-in mic> IP67, PoC (only CVI/12V+30% D</p>	IRR 16,650,000			
10	DH-HAC-HFW1500TLP	<p>5MP Starlight HDCVI IR Bullet Camera</p> <p>* The parameters and datasheets below can only be applied to 1500-S2 series</p> <p>* In order to use the SMP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.> Max 25 fps@5MP (16:9 video output)</p> <p>> CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm, 6 mm optional)</p> <p>> Max. IR length 40 m, Smart IR> IP67, DC12V</p>	IRR 15,870,000			
11	DH-HAC-HFW1400DP-S3-0360B	<ul style="list-style-type: none"> · 1/3" 4.1Megapixel CMOS · 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P · 3.6mm fixed lens, HD and SD output switchable · DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR · OSD Menu, Max. IR length 80m, Smart IR, IP67, DC12V 	IRR 17,260,000			
12	DH-HAC-HFW1400TP-A	<p>4MP HDCVI IR Bullet Camera</p> <ul style="list-style-type: none"> · Max. 30fps@4MP · Built-in mic · IP67, DC12V, · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional), · Max. IR length 30m, Smart IR 				
13	DH-HAC-HFW1400SP	<ul style="list-style-type: none"> · Max 30fps@4MP(2560x1440) · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V 				












14	DH-HAC-HFW1400TP(S)	<ul style="list-style-type: none"> Max. 30fps@4MP · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V 					
15	DH-HAC-HFW1400CMP	<ul style="list-style-type: none"> 4MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V 	IRR 12,820,000				
16	DH-HAC-HFW1400RP(S)	<ul style="list-style-type: none"> Megapixel camera with 1/3" CMOS sensor and HD-CVI (High Definition Composite Video Interface). length 20m, Smart IR-D-WDR - Wide Dynamic Range 2D-DNR - Digital Noise Reduction.BLC/HLC - Back Light / High Light Compensation ICR - Movable InfraRed filter.Sharpness - sharper image outlines AGC - Automatic Gain Control.Privacy zones.Mirror - Mirror image Auto White Balance-OSD menu available via recorder.IP67 					
17	DH-HAC-HDW1400TRQP-A-0280B-S3	<ul style="list-style-type: none"> 1/2.7 inch Progressive CMOS Max 30fps@4MP, 2.8mm fixed lens, Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 25m, Smart IR, IP50, DC12V 	IRR 9,620,000				
18	DH-HAC-HDW1400MP	<ul style="list-style-type: none"> · 4MP HDCVI IR Eyeball Camera · Max 30fps@4MP · IP67, DC12V · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR 					
19	DH-HAC-HDW1400EMP-A	<ul style="list-style-type: none"> · Max. 30fps@4MP(2560x1440) · Built-in mic · IP67, DC12V · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR 					
20	DH-HAC-HDW1409TP-A-LED	<ul style="list-style-type: none"> 4MP Full-color Starlight HDCVI Eyeball Camera · Full-color starlight · 40 m LED distance, · Max. 30fps@4MP · CVI/CVBS/AHD/TVI switchable, · Built-in mic (-A) · 3.6 mm fixed lens (2.8 mm optional) · IP67, 12V±30% DC 					
21	DH-HAC-HDW1400TP-Z-A	<ul style="list-style-type: none"> · Max 30fps@4MP(2560x1440) · HD and SD output switchable · Built-in mic · IP67, DC12V · 2.7-12mm motorized lens · Max. IR length 60m, Smart IR 					
22	DH-HAC-HDW1400TRQP-0280B-S3	<ul style="list-style-type: none"> 1/2.7 inch Progressive CMOS Max 30fps@4MP 2.8mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 25m, Smart IR, IP50, DC12V 	IRR 8,070,000				
2MP FIX LENS							
24	DH-HAC-HFW1230DP(S)	<ul style="list-style-type: none"> 1/2.8" 2.1Megapixel CMOS (Starlight)25/30fps@1080P, 25/30/50/60fps@720P3.6mm Fixed lensDWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNRHD and SD output switchableOSD MenuMax. IR length 80m, Smart IRIP67, DC12V 					
25	DH-HAC-HDW1500EMP-A	<ul style="list-style-type: none"> · Max. 20fps@5MP(2592x1944) · Built-in mic · IP67, DC12V · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR 					












26	DH-HAC-HDW1509TLP-A-LED	<ul style="list-style-type: none"> 5MP Full-color Starlight HDCVI Eyeball Camera - Full-color starlight - 20 m LED distance, - Max. 20fps@5MP - CVI/CVBS/AHD/TVI switchable, - Built-in mic (-A) - 3.6 mm fixed lens (2.8 mm optional) - IP67, 12V±30% DC 	IRR 19,610,000				
27	DH-HAC-HFW1509TLMP-A-LED	<ul style="list-style-type: none"> 5MP Full-color HDCVI Bullet Camera -> Max 25 fps@5MP (16:9 video output) > 120 dB true WDR, 3D NR 24/7 color imaging > 40 m illumination distance> CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional)> IP67, 12 	IRR 21,420,000				
28	DH-HAC-HFW1509TLMP-LED	<ul style="list-style-type: none"> - 40 m LED distance - Max. 20fps@5MP - CVI/CVBS/AHD/TVI switchable - Built-in mic (-A) - 3.6 mm fixed lens - IP67, 12V±30% DC 	IRR 19,820,000	IRR 17,900,000			
	HAC-HDw1509TLQP-LED-0280B	<ul style="list-style-type: none"> 5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output)> 120dB true WDR, 3D NR > 24/7 color imaging> 20 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional) > IP67, 12 V DC > Quick to install eyeball saves installation time 	IRR 22,200,000	IRR 18,800,000			
29	HAC-HDw1509TLQP-A-LED	<ul style="list-style-type: none"> 5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output)> 120dB true WDR, 3D NR > 24/7 color imaging> 20 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional) > IP67, 12 V DC > Quick to install eyeball saves installation time 	IRR 21,420,000				
30	DH-HAC-HDW1500TP-Z-A	<ul style="list-style-type: none"> - Max. 20fps@5MP(2592x1944). 1/2.7"Progressive CMOS - 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P - HD and SD output switchable- Built-in mic - 2.7-12mm motorized lens - IP67, DC12V - Max. IR length 60m, Smart IR 					
31	DH-HAC-HFW1200RP	<ul style="list-style-type: none"> - 2MP HDCVI IR Bullet Camera - Max 30fps@1080P(1920x1080) - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 20m, Smart IR - IP67, DC12V 					
32	DH-HAC-HDW1230TLP-A	<ul style="list-style-type: none"> - 2MP Starlight HDCVI IR Eyeball Camera - Max. 30fps@1080P - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 40m, Smart IR - IP67, DC12V, Built in Mic 					
33	DH-HAC-HDW1230EMP-A	<ul style="list-style-type: none"> - 2MP Starlight HDCVI IR Eyeball Camera - Max. 30fps@1080P - HD and SD output switchable, - Built-in mic - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 50m, Smart IR - IP67, DC12V 					
34	DH-HAC-HDW1239TP-A-LED-0280B-S2	<ul style="list-style-type: none"> - Full-color starlight - 40m LED distance - Max. 30fps@1080P - CVI/CVBS/AHD/TVI switchable - 3.6mm fixed lens (2.8mm Optional) - IP67, 12V±30% DC 	IRR 16,830,000				
35	HAC-HFW1231TMP-I8-A(S)	<ul style="list-style-type: none"> 2MP HDCVI IR Bullet Camera-> Max 30 fps@1080P 2MP Starlight HDCVI IR Bullet Camera > 3.6 mm fixed lens (2.8 mm, 6 mm optional)Day/Night Auto switch by ICR BLC BLC/WDR/HLC-WDR 130 dBIP67, DC 12 V 					









36	DH-HAC-HFW1209TLMQ-LED-0360B	<p>2MP Full-color HDCVI Bullet Camera</p> <p>1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens</p> <p>Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on WDR(130db), Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu, Ejector</p>	IRR 11,710,000				
37	DH-HAC-ME1500CP	<p>5MP HDCVI Active Deterrence Camera</p> <p>> Max 20fps@5MP > HD and SD output switchable > 2.8mm fixed lens (3.6mm optional), > Max. IR length 20m, Smart IR > Built-in PIR, 14±1m/110° detecting range/angle > Active deterrence with white light & siren, > IP67, DC12V</p>					
38	DH-HAC-ME1200EP-LED	<p>2MP HDCVI Active Deterrence Camera · Max 30fps@1080P</p> <p>· HD and SD output switchable, · 2.8mm/3.6mm fixed lens · 10m/110° detecting range/angle · Max. IR length 20m, Smart IR · IP67, DC12V</p>					
39	DH-HAC-HDW1200RP	<p>2MP HDCVI IR Eyeball Camera</p> <p>· Max 30fps@1080p(1920x1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm optional) · Max. IR length 20m, Smart IR · DC12V</p>					
40	DH-HAC-HDBW1200EP	<p>2MP HDCVI IR Dome Camera</p> <p>· Max 30fps@1080P · IP67, IK10, DC12V · HD and SD output switchable · 3.6mm fixed lens (2.8mm optional) · Max. IR length 30m, Smart IR</p>					
41	DH-HAC-HDW1200EMP-A-S4	<p>2MP HDCVI IR Eyeball Camera</p> <p>· Max 30fps@1080P(1920x1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR · IP67, DC12V. Built in mic</p>	IRR 12,420,000				
42	DH-HAC-HDW1200EMP-A-0280B-S5	<p>2MP HDCVI IR Eyeball Camera</p> <p>· Max 30fps@1080P(1920x1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR · IP67, DC12V. Built in mic</p>	IRR 11,370,000	IRR 11,500,000			
43	DH-HAC-HDW1209TLQP-LED-0280B	<p>2MP Full-color Starlight HDCVI Eyeball Camera</p> <p>· Full-color starlight · 20 m illumination distance, · Max. 30fps @ 1080P · CVI / CVBS / AHD / TVI switchable · Fixed lens (2.8 mm; 3.6 mm optional) · IP67, 12V ± 30% DC · Max 30fps@1080P</p>	IRR 10,420,000	IRR 9,500,000	IRR 9,630,000		
	DH-HAC-HDW1200TLMQP-0208B	<p>· Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 3.6mm fixed lens (2.8mm optional) · Built-in mic(-A) · Max. IR length 30m, Smart IR · IP67, DC12V</p>		IRR 10,150,000			
44	DH-HAC-HFW1200TLP-0360B-S5	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens</p> <p>HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V</p>	IRR 10,630,000				











45	DH-HAC-HFW1200TLP-A	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens</p> <p>HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V--a</p>	IRR 11,900,000			
46	DH-HAC-HFW1200TL-A	<p>2MP HDCVI IR Bullet Camera- Max 30fps@1080P</p> <ul style="list-style-type: none"> · CVI/CVBS/AHD/TVI switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Built-in mic · Max. IR length 80m, Smart IR · IP67, DC12V 	IRR 10,900,000			
47	DH-HAC-HFW1200TP(S)	<p>1/2.7" 2Megapixel CMOS .Max 30fps@1080P</p> <ul style="list-style-type: none"> · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V 	IRR 10,310,000	IRR 9,000,000		
48	DH-HAC-HFW1200TP-A-0360B-S5	<p>1/2.7" Progressive Scan 2Megapixel CMOS.Max 30fps@1080P</p> <p>HD and SD output switchable</p> <ul style="list-style-type: none"> · Built-in mic · 2.8mm fixed lens · Max. IR length 30m, Smart IR · IP67, DC12V 	IRR 10,550,000			
49	DH-HAC-HFW1200DP-S5-0360B	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V</p>	IRR 13,480,000	IRR 12,600,000		
50	DH-HAC-HFW1200RP(S)	<p>1/2.7" 2Megapixel CMOS25/30fps@1080P , 25/30/50/60fps@720P</p> <p>3.6mm fixed lensHD and SD output switchableDay/Night(ICR) , AWB, AGC, BLC, 2D-DNRSupport OSD MenuMax . IR length 20m, Smart IR IP67</p>				
51	DH-HAC-HDW1209TLQP-A-LED-0280B	<p>2MP Full-color HDCVI Quick-to-install Eyeball Camera</p> <p>1/2.8 inch 2MP Progressive CMOS</p> <ul style="list-style-type: none"> · Max. 30fps@1080P · 2.8mm fixed lens · Built-in Mic · CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 	IRR 11,220,000			
52	HAC-HDW1200EMP-A	<p>1/2.7" 2Megapixel CMOS , 25/30fps@1080P, Built-in MIC</p> <p>Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR</p> <p>3.6 & 2.8mm fixed lens</p> <p>Max. IR LEDs length 50m, Smart IR, IP67, DC12V</p>	IRR 11,370,000	IRR 10,900,000		
	DH-HAC-HDW1200TMQP-A-S5-0280B	<ul style="list-style-type: none"> · Max 30fps@1080P · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 2.7-12mm motorized lens · Built-in mic(-A) · Max. IR length 60m, Smart IR 		IRR 12,300,000		
53	DH-HAC-HDW1200TRQP-A-0360B-S5	<p>2MP HDCVI Quick-to-install IR Eyeball Camera</p> <p>1/2.7 inch Progressive CMOS</p> <ul style="list-style-type: none"> · Max 30fps@2MP · 2.8mm/3.6mm fixed lens · Built in Mic · CVI/TVI/AHD/CVBS Switchable, Support OSD Menu 	IRR 9,520,000			







54	DH-HAC-HDW1200TRQP-A-0280B-S5	<p>2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu</p>	IRR 10,420,000	IRR 9,200,000		
55	DH-HAC-HFW1200SP	<p>Max 30fps@1080P(1920x1080) · 2MP HDCVI IR Bullet Camera · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V</p>				
56	DH-HAC-HFW1200THP-I8	<p>2MP HDCVI IR Bullet Camera · Max 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 80m, Smart IR · IP67, DC12V</p>	IRR 11,990,000	IRR 11,300,000		
57	DH-HAC-HFW1200TP	<p>2MP HDCVI IR Bullet Camera · Max 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V</p>				
58	DH-HAC-HFW1200TP-A	<p>1/2.7" 2Megapixel CMOS · 25/30fps@1080P, 25/30/50/60fps@720P · 3.6mm fixed lens. Built-in mic · HD and SD output switchable · DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR ,OSD · Max. IR length 30m, Smart IR. IP67, DC12V</p>	IRR 10,270,000	IRR 11,300,000		
59	DH-HAC-HFW1230TLP	<p>2MP Starlight HDCVI IR Bullet Camera · Max. 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 40m, Smart IR · IP67, DC12V</p>				
60	DH-HAC-HFW1230TP	<p>2MP Starlight HDCVI IR Bullet Camera · Max. 30fps@1080P. Starlight · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V</p>				
61	DH-HAC-HFW1230THP-I8	<p>2MP Starlight HDCVI IR Bullet Camera · Max. 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (6mm, 8mm optional) · Max. IR length 80m, Smart IR · IP67, DC12V</p>				
62	DH-HAC-HFW1200THP-I8	<p>2MP HDCVI IR Bullet Camera · Max 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 80m, Smart IR · IP67, DC12V</p>	IRR 13,100,000	IRR 12,600,000		
63	DH-HAC-HFW1200THP-I4	<p>DH-HAC-HFW1200THP-I4 2MP HDCVI IR Bullet Camera * The parameters and datasheets below can only be applied to 1200-S5 series > Max 30fps@1080P > HD and SD output switchable> 3.6mm fixed lens (2.8mm, 6mm optional) > Max. IR length 40m, Smart IR> IP67, DC12V</p>	IRR 12,310,000	IRR 11,300,000		
64	DH-HAC-HFW1200TP	<p>2MP HDCVI IR Bullet Camera · Max 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V</p>				







65	DH-HAC-HFW1200TP-A	<p>17.7" 2Megapixel CMOS</p> <ul style="list-style-type: none"> · 25/30fps@1080P, 25/30/50/60fps@720P · 3.6mm fixed lens. Built-in mic · HD and SD output switchable · DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR ,OSD · Max. IR length 30m, Smart IR · IP67, DC12V 				
66	DH-HAC-HFW1200RP-Z-IRE6	<ul style="list-style-type: none"> · Max 30fps@1080P(1920x1080) · HD and SD output switchable · 2.7-12mm Motorized lens · Max. IR length 60m, Smart IR · IP67, DC12V 	IRR 23,010,000			
	DH-HAC-HFW1209CP-LED-0280B	<p>Full-color starlight</p> <ul style="list-style-type: none"> · 20 m illumination distance · Max. 30fps@1080P, · CVI/CVBS/AHD/TVI switchable · Fixed lens (2.8 mm,3.6 mm optional) · IP67, 12V±30% DC 	IRR 8,800,000			
67	DH-HAC-HFW1209CP-LED-0360B	<p>Full-color starlight</p> <ul style="list-style-type: none"> · 20 m illumination distance · Max. 30fps@1080P, · CVI/CVBS/AHD/TVI switchable · Fixed lens (2.8 mm,3.6 mm optional) · IP67, 12V±30% DC 	IRR 10,020,000			
68	DH-HAC-HFW1200CMP	<p>2 MP HDCVI Bullet Camera with IR Illumination</p> <ul style="list-style-type: none"> > Up to 30fps @ 1080P > Switchable CVI / CVBS / AHD / TVI outputs > Fixed lens 3.6mm (2.8mm optional), > Built-in microphone (-A) > Max. IR illumination range 30m, Intelligent IR illumination > IP67, DC 12V 	IRR 10,320,000			
69	DH-HAC-HFW1200CMP-A	<p>HAC-HFW1200CM-A-POC</p> <p>2MP HDCVI POC Fixed IR ullet Camera> Max 30 fps@1080P.</p> <ul style="list-style-type: none"> > 3.6mm fixed lens (2.8mm optional),> CVI/CVBS/AHD/TVI switchable. > Built-in mic.> Max. IR length 30m, Smart IR.> IP67, PoC (only CVI)/12V±30% DC. 	IRR 11,110,000			
70	DH-HAC-HFW1209CMP-LED-0360B	<p>2MP Full-color HDCVI Bullet Camera</p> <ul style="list-style-type: none"> > 24/7 color imaging > 20 m illumination distance > Max. 30 fps @ 1080p, > Built-in mic (-A) > CVI / CVBS / AHD / TVI switchable > Fixed lens (2.8 mm; 3.6 mm optional), > IP67, 12V ± 30% DC 	IRR 11,210,000			
71	DH-HAC-HFW1239TP-LED	<p>Full-color starlight</p> <ul style="list-style-type: none"> · 20m LED distance · Max. 30fps@1080P, · CVI/CVBS/AHD/TVI Switchable · 3.6mm fixed lens (2.8mm Optional) · IP67, DC12V±30% DC 	IRR 15,080,000			
72	DH-HAC-HFW1231RP-Z-A	<p>2MP Starlight HDCVI IR Bullet Camera</p> <ul style="list-style-type: none"> > Max. 30 fps@1080P > Starlight, 130dB true WDR, 3D NR > Auto focus, 2.7 mm-12 mm motorized lens > CVI/CVBS/AHD/TVI switchable Super Adapt > Built-in mic> Max. IR length 80 m, Smart IR > IP67, 12V D 	IRR 26,980,000			
73	DH-HAC-HFW1400TLP	<ul style="list-style-type: none"> · Max. 30fps@4MP · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 40m, Smart IR · IP67, DC12V 				
74	DH-HAC-HFW1400THP-I8	<p>4MP HDCVI IR Bullet Camera</p> <ul style="list-style-type: none"> · Max. 30fps@4MP · IP67, DC12V · HD and SD output switchable · 3.6mm fixed lens (6mm, 8mm optional) · Max. IR length 80m, Smart IR 				






75	HAC-HDW1200MP-S5-0280B	Dahua DH-HAC-HDW1200MP-0280B-S5 Dahua 4 in 1 fixed dome with... Dahua 4 in 1 fixed dome with Smart IR 30m for outdoor use. CMOS 1/2.7" 2MP. Output 4 in 1 by a BNC port. Fixed optics 2.8 mm (101°). 0.02 lux. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, Mirror, privacy masks. 3AXIS. 12V DC.	IRR 10,320,000	IRR 9,800,000		
76	HAC-HDW1200M-S5	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V	IRR 9,180,000			
77	COOPER					
78	DH-HAC-B2A51P-0360B-S2	2MP HDCVI Eyeball Camera, 1/2.7" 2Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium	IRR 13,680,000			
78	DH-HAC-B2A51P-0208B-S2	2MP HDCVI Eyeball Camera, 1/2.7" 2Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium	IRR 13,680,000	IRR 12,420,000		
	DH-HAC-B2A21P-0280B	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		IRR 8,070,000		
79	DH-HAC-B2A21P-0360B	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 8,000,000	IRR 7,250,000		
80	DH-HAC-T2A21P-0280B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 9,520,000	IRR 7,250,000		
81	DH-HAC-T2A21P-0360B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 8,430,000			
82	DH-HAC-T1A21P-0280B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm & 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V	IRR 6,960,000	IRR 6,200,000		
83	DH-HAC-T1A21P-0360B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm & 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V	IRR 7,060,000			
84	DH-HAC-T1A41P	. 4MP HDCVI IR Eyeball Camera . Max. 30fps@4MP (2560x1440) . HD and SD output switchable . 3.6mm fixed lens (2.8mm, 6mm optional) . Max. IR length 20m, Smart IR. DC12V				

	HAC-D1A51P			IRR 10,500,000		
	HAC-T1A51P			IRR 10,350,000		
85	DH-HAC-T2A41P	<ul style="list-style-type: none"> · Max. 30fps@4MP(2560×1440) · HD and SD output switchable · 3.6mm fixed lens (2.8mm,6mm optional) · Max. IR length 20m, Smart IR · IP67, DC12V 				
86	DH-HAC-T2A51P	<ul style="list-style-type: none"> · 5MP HDCVI IR Eyeball Camera · Max. 20fps@5MP (2592×1944) · HD and SD output switchable · 3.6mm fixed lens (2.8mm,6mm optional) · Max. IR length 20m, Smart IR · IP67, DC12V 	IRR 14,280,000		IRR 13,000,000	
87	DH-HAC-B1A21P	<ul style="list-style-type: none"> · 2MP HDCVI IR Bullet Camera · Max. 30fps@1080P (1920×1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 20m, Smart IR · IP67, DC12V 	IRR 6,850,000	IRR 6,200,000		
88	DH-HAC-B1A41P	<ul style="list-style-type: none"> · 4MP HDCVI IR Bullet Camera · Max. 30fps@4MP (2560×1440) · HD and SD output switchable · 3.6mm fixed lens (6mm optional) · Max. IR length 20m, Smart IR · IP67, DC12V 				
89	DH-HAC-B1A51P	<p>* The parameters and datasheets below can only be applied to A51-S2 series * In order to use the SMP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.> Max. 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 20 m, Smart IR> IP67, DC12V</p>	IRR 12,700,000	IRR 10,850,000		
90	DH-HAC-B2A41P	<ul style="list-style-type: none"> · Max. 30fps@4MP(2560×1440) · HD and SD output switchable · 3.6mm fixed lens (2.8mm,6mm optional) · Max. IR length 20m, Smart IR · IP67, DC12V 				
91	DH-HAC-B2A41P	<p>2MP 15x Starlight HDCVI PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 15x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IK10</p>	IRR 128,560,000			
92	PTZ					
93	DH-SD49225-HC-LA	<p>2MP 25x Starlight IR PTZ HDCVI Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IR distance up to 100 m > IP66</p>				

94	DH-SD59230I-HC	<ul style="list-style-type: none"> · 1/2.8" 2Megapixel STARVIS™ CMOS · Powerful 30x optical zoom · Starlight technology · 120dB true WDR, 3D DNR · Max. 25/30fps@1080P, 25/30/50/60fps@720P · IR distance up to 150m · IP66 						
95	DH-SD59232-HC-LA	<ul style="list-style-type: none"> · 2MP 32X Starlight IR PTZ HDCVI Camera · > 1/2.8" 2Megapixel STARVIS™ CMOS · > Powerful 32X optical zoom · > Starlight technology · > 120dB true WDR, 3D DNR · > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P · IP66 	IRR 238,950,000					
96	DH-SD59430I-HC	<ul style="list-style-type: none"> · 1/3" 4Megapixel CMOS · Powerful 30x optical zoom · 120dB true WDR, 3D DNR · Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P · IR distance up to 100m · IP66 						
97	XVR							
98	XVR1B04-I	<ul style="list-style-type: none"> · 4 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps), · 4CH: 1/4 PlaybackHDMI , VGA ,simultaneous video Output1 SATA port, up to 6 TB capacity2*USB 2.0, 10/100 Mbps LAN Interface, P2P SupportSMD Plus, Full channel AI-Coding, Human/Vehicle Classification15,900,00070 DH-XVR1A088CH Penta-brid 1080N/720P noneReal-Time Cooper · 8 Channel Penta-brid 1080N/720P Cooper 1U · H.264 video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 10 channels IP camera inputs, each channel up to 5MP; Max 40Mbps Incoming Bandwidth · Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB 	IRR 18,500,000	IRR 15,900,000	IRR 16,800,000			
99	DH-XVR1A08	<ul style="list-style-type: none"> · 8 Channel Penta-brid 1080N/720P Cooper 1U · H.264 video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 10 channels IP camera inputs, each channel up to 5MP; Max 40Mbps Incoming Bandwidth · Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB 	IRR 23,100,000					
100	DH-XVR1A04	<ul style="list-style-type: none"> · 4 Channel Penta-brid 1080N/720P Cooper 1U · H.264 video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 5channels IP camera inputs, each channel up to 2MP; Max 20Mbps Incoming Bandwidth · Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB 						
101	DH-XVR1B08-I	<ul style="list-style-type: none"> · 8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), · 4CH: 1/4/9 PlaybackHDMI , VGA ,simultaneous video Output · 1 SATA port, up to 6 TB capacity2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support · 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification · 16CH Penta-brid 1080N/720P noneReal-time Cooper Recorder · H.265+/H.265 dual-stream video compression1st channel 1080N/720P@25fps, others 1080N/720P@15fps16CH: 1/4/9/16 Playback · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(72 Mbps)]1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TBHDMI , VGA ,simultaneous video Output · 2 USB 2 , 10/100 Mbps LAN Interface, P2P Support 	IRR 22,730,000	IRR 20,700,000	IRR 21,200,000			
102	DH-XVR1B16-I	<ul style="list-style-type: none"> · 16 Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth, Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB, Smart Search and Intelligent Video System 	IRR 43,520,000					
103	DH-XVR1B16H	<ul style="list-style-type: none"> · 16 Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth, Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB, Smart Search and Intelligent Video System 						
104	DH-XVR4104HS-I	<ul style="list-style-type: none"> · 4 Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 5 channels IP camera inputs, each channel up to 2MP; Max 32 Mbps incoming bandwidth · Up to 4 channels video stream (analog channel) SMD Plus 		IRR 21,750,000				

105	DH-XVR4108HS-I	<ul style="list-style-type: none"> · 8 Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 10 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth · Up to 8 channels video stream (analog channel) SMD Plus 		IRR 27,600,000			
106	DH-XVR4116HS-I	<ul style="list-style-type: none"> · 16 Channel Penta-brid 720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth · Long transmission distance over coax cable · Up to 8 channels video stream (analog channel) SMD Plus 		IRR 51,270,000			
107	DH-XVR5104HS-I3	<ul style="list-style-type: none"> · 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4ch1 SATA Port up to 6 TB capacity2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 	IRR 30,000,000	IRR 28,200,000	IRR 28,200,000		
108	DH-XVR5108HS-I3	<ul style="list-style-type: none"> · 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity 	IRR 45,100,000	IRR 40,000,000			
109	DH-XVR5104HS-4KL-I3	<ul style="list-style-type: none"> · 4 Channel Penta-brid 4K WizSense Ai XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4ch1 SATA Port up to 10 TB capacity2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support · 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support 	IRR 43,570,000	IRR 40,900,000			
110	DH-XVR5108HS-4KL-I3	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 	IRR 76,900,000				
111	DH-XVR5108HS-4KL-I2	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 	IRR 68,730,000				
112	DH-XVR5108HS-4KL	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHDTV+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support 	IRR 65,910,000				
113	DH-XVR5116H-I2	<ul style="list-style-type: none"> · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth · Up to 2 channels video stream (analog channel) Perimeter Protection · Up to 16 channels video stream (analog channel) SMD Plus · Up to 2 channels video stream (analog channel) human face recognition · IoT & POS functionalities 	IRR 72,130,000				

114	DH-XVR5116HS-S2	<p>16 Channel Penta-brid 1080P Compact 1U Digital Video Recorder</p> <ul style="list-style-type: none"> > Embedded processor-Power Supply DC12V/2A > H.264+/H.264 video compression > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6/12/24 channels IP camera inputs, each channel up > Smart Search and Intelligent Video System-Internal HDD 1 SATA Port, up to 8TB capacity 	IRR 72,480,000			
115	DHI-XVR5216AN-S2	<p>Embedded processor</p> <ul style="list-style-type: none"> > H.264+/H.264 dual-stream video compression > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6/12/24 channels IP camera inputs, each channel up > Smart Search and Intelligent Video System 	IRR 94,500,000			
116	DH-XVR5216AN-I2	<p>16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR</p> <p>5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4/9/16ch</p> <p>2 SATA Port up to 10 TB capacity each port(20TB Total)</p> <p>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support</p> <p>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to</p>	IRR 74,810,000			
117	DH-XVR5216AN-4KL	<p>16 Channel Penta-brid 4K 1U Digital Video Recorder -Embedded processor – H.264+/H.264 dual-stream video compression – Support HDCVI/AHD/TVI/CVBS/IP video inputs – Max 12/24 channels IP camera inputs, each channel up to 8MP – Max 48/96Mbps Incoming Bandwidth – Smart Search and Intelligent Video System</p>	IRR 136,370,000			
118	DH-XVR5216AN-4KL-I2	<p>16 Channel Penta-brid 4KN/5MP WizSense Ai XVR</p> <p>4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4/9/16ch</p> <p>2 SATA Port up to 10 TB capacity each port(20TB Total)</p> <p>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support</p> <p>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	IRR 140,850,000			
119	DHI-XVR5232AN-S2	<p>Embedded processor</p> <ul style="list-style-type: none"> -H.264+/H.264 dual-stream video compression -Support HDCVI/AHD/TVI/CVBS/IP video inputs -Max 32 channels IP camera inputs; Max 128Mbps Incoming Bandwidth -Long transmission distance over coax cable -Support 2 SATA HDD, up to 16TB 	IRR 142,300,000			

120	DH-XVR5232AN-I2	<p>32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHDTVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	IRR 120,270,000			
121	DH-XVR5104HS-4KL-I2	<p>4 Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense Digital Video Recorder . H.265+/H.265 dual-stream video compression . Supports HDCVI/AHD/TVI/CVBS/IP video inputs . Max 8 channels IP camera inputs, each channel up to 8MP; Max 64 Mbps incoming bandwidth . Up to 2 channels video stream (analog channel) Perimeter Protection Up to 4 channels video stream (analog channel) SMD Plus</p>				
122	DH-XVR5216AN-4KL-X	<p>16 Channel Penta-brid 4K 1U Digital Video Recorder . H.265+/H.265 dual-stream video compression . Supports HDCVI/AHD/TVI/CVBS/IP video inputs . Max 12/24 channels IP camera inputs, each channel up to 8MP; Max 48/96Mbps Incoming Bandwidth . Smart Search and Intelligent Video System</p>				
123	DH-XVR5432L-I2	<p>32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHDTVI+CVBS)N+M 32ch IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 4/1ch Audio I/O, 16/6 Alarm I/O Playback 1/4/9/16ch</p>	IRR 181,870,000			
124	PINHOLE					
125	DH-HAC-HUM2301BP-B		IRR 19,360,000			

هایک ویژن تهران

نماینده رسمی هایک ویژن در ایران







09906500074












تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران























Hikvisiontehran










DAHUA - camera,nvr











Items	Description	User Price	USER Price (با گارانتی پارس ارتباط)	گارانتی ماد طلایی	گارانتی فراگستر		
DAHUA - camera,nvr		User Price (با گارانتی پارس ارتباط)	USER Price (با گارانتی پارس ارتباط)	گارانتی ماد طلایی	گارانتی فراگستر		
1	DH-IPC-HFW2439SP-SA-LED-S2-0360B 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illumination 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T	IRR 35,250,000	IRR 30,000,000				
2	DH-IPC-HFW2439MP-AS-LED-B-S2 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs 4MP (2560 x 1440) @ 25/30 fps, Max. supports 4MP (2688 x 1520) @ 20 fps > H.265 codec, high compression rate, ultra-low bit rate> Built-in warm lights, max. illumination distance: 40 m> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital	IRR 37,290,000					
3	DH-IPC-HFW2431SP-S-S2-0360B 4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI	IRR 32,850,000			IRR 30,800,000		
4	DH-IPC-HFW2431TP-ZS-27135-S2 4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.5, 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67, PoE	IRR 59,050,000	IRR 52,800,000				
5	DH-IPC-HFW1230T1P-ZS 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 x 1080p) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate: Built-in IR LED, max. IR distance: 50 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access. Supports max. 256 GB Micro SD card 12V DC/PoE power supply; IP67 protection						
6	DH-IPC-HDW1330-SP H.264+ & H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm 6mm optional) Max IR LEDs Length 30m IP67, PoE						





7	H-IPC-HFW3441TP-ZS	<p>4MP IR Vari-Focal Bullet Wi2Sense Network Camera</p> <ul style="list-style-type: none"> > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs max. 4MP (2688 × 1520)@30 fps > H.265 codec, high compression rate, low bit rate > Built-in IR LED, max. IR distance: 60 m <p>> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode: WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</p>	IRR 77,750,000				
8	DH-IPC-HFW1431S1P-S4	<ul style="list-style-type: none"> · Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP(2688 × 1520) @20 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max. IR distance: 30 m- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments- Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection- 12V DC/PoE power access, - IP67, protection 	IRR 24,430,000				
9	DH-IPC-HFW1831EP	<ul style="list-style-type: none"> · 1/1.8" 8Megapixel progressive scan CMOS · H.265&H.264 dual-stream encoding · 25/30fps@8MP(3840×2160) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8mm fixed lens (4mm, 6mm optional); Max. IR LEDs Length 50m -IP67, PoE 					
10	DH-IPC-HFW2231TP-ZS	<ul style="list-style-type: none"> · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920×1080) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens; Max IR LEDs Length 60m; - IP67, IK10(optional), PoE 	IRR 44,500,000				
11	DH-IPC-HFW2531SP-S-S2-0360B	<p>5MP Lite IR Fixed-focal Bullet Network Camera STARLIGHT</p> <ul style="list-style-type: none"> · 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments 	IRR 36,850,000				
	DH-IPC-HDB2231RP-ZS-27135-S2-QH			IRR 39,500,000			
12	DH-IPC-HDBW2431RP-ZS-S2	<ul style="list-style-type: none"> · 1/3" 4MP WDR IR Dome Network Camera · H.265 & H.264 dual-stream encoding · 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB 	IRR 57,740,000	IRR 48,500,000			
13	DH-IPC-HDBW2531RP-ZS	<ul style="list-style-type: none"> · 5MP WDR IR Dome Network Camera IP6730m · 1/2.7" 5Megapixel progressive CMOS, · H.265 & H.264 dual-stream encoding · 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB 					
	DH-IPC-HFW2831SP-S-0360B-S2		IRR 55,480,000				
14	DH-IPC-HDBW2831RP-ZS	<ul style="list-style-type: none"> · 1/1.8" 8Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@8MP(3840×2160) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB - IP67, IK10, PoE 					
15	DH-IPC-HDW2431TMP-AS-s2-0280B	<p>4MP WDR IR Eyeball Network Camera, Starlight</p> <ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire)Intrusion Micro SD memory:256 GB, Built-in Mic 	IRR 36,850,000				
	DH-IPC-HDBW3241FP-AS-M-0280B			IRR 37,000,000			







	DH-IPC-HFW3241EP-SA-0600B			IRR 37,400,000				
16	DH-IPC-HDW2431TP-AS-S2	<p>4MP Lite IR Fixed-focal Eyeball Network Camera</p> <ul style="list-style-type: none"> > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire> Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection> Max. 256 GB SD card and built-in Mic> 12V DC/POE power supply> IP67 protection 	IRR 35,700,000					
17	H-IPC-HDW2439TP-AS-LED-0280B	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera</p> <ul style="list-style-type: none"> 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ 	IRR 37,650,000					
17	H-IPC-HDW2439TP-AS-LED-0360B	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera</p> <ul style="list-style-type: none"> 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ 	IRR 32,700,000					
18	DH-IPC-HDBW2431EP-S-S2-0360B	<p>4MP IR Mini Dome Network Camera</p> <ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. illumination:0.008 Lux @ F1.6 2.8mm/3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 	IRR 31,210,000					
	DH-IPC-HDBW2431EP-S-S2-0280B	<p>4MP IR Mini Dome Network Camera</p> <ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. illumination:0.008 Lux @ F1.6 2.8mm/3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 	IRR 32,000,000					
19	DH-IPC-HDBW2531EP-S-S2	<p>5MP Lite IR Fixed-focal Dome Network Camera, STARLIGHT</p> <ul style="list-style-type: none"> 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max IR distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage 	IRR 36,850,000	IRR 40,390,000				
20	DH-IPC-HFW1431SP-S4-0360B	<p>4MP, 1/3" CMOS image sensor, low illuminance, high image definition</p> <ul style="list-style-type: none"> Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 30 m ROI, SMART H.264/H.265, flexible coding, 	IRR 30,000,000					
21	DH-IPC-HDBW1431EP-S4	<ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm optional) 	IRR 30,590,000					
	DH-IPC-HDPW1431R1P-0280B-S4			IRR 25,600,000				
22	DH-IPC-HDW1431T1P-S4-0280B	<p>4MP Entry IR Fixed-focal Eyeball Network Camera</p> <ul style="list-style-type: none"> 1/3" 4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI 	IRR 28,170,000					










23	DH-IPC-HFW2231SP-S-S2-0360B	2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Roi Micro SD memory 256GB	IRR 30,080,000				
24	DH-IPC-HFW2239SP-SA-LED-S2		IRR 31,790,000				
25	DH-IPC-HFW1239S1-LED-0360B-S5	2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+	IRR 21,480,000		IRR 20,550,000		
26	DH-IPC-HFW1239S1P-LED-0360B	· 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments	IRR 21,480,000	IRR 18,600,000			
27	DH-IPC-HFW1230S-S5	2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens	IRR 21,290,000				
28	DH-IPC-HFW1230S5-S5-0360B	· 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 2MP (1920 × 1080p) @25/30 fps- H.265 codec, high compression rate, ultra-low bit rate- Built-in IR LED, max. IR distance: 30 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes- Abnormality detection: Motion detection, video tampering, network	IRR 21,860,000	IRR 20,700,000			
29	DH-IPC-HDBW1230EP	· 1/2.7" 2Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8mm fixed lens (3.6mm optional)					
30	DH-IPC-HFW1230S1P-S5-0360B	2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition > Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate > Built-in efficient IR illuminator, and the max. illumination distance is 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments	IRR 20,710,000	IRR 16,850,000			
31	DH-IPC-HDW1239T1-LED	· 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments	IRR 21,480,000		IRR 24,230,000		
32	DH-IPC-HDW1239T1P-LED-0280B-S5-QH2	2MP Lite Full-Color Fixed-focal Eyeball Network Camera > 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition > Outputs max. 2MP (1920 × 1080) @25/30 fps > H.265 codec, high compression rate, ultra-low bit rate> Built-in LEDs, max LED distance: 30 meters > ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments	IRR 19,010,000				
33	DH-IPC-HDW2239TP-AS-LED-S2	2MP Lite Full-color Fixed-focal Eyeball Network Camera > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition > Outputs max. 2MP (1920 × 1080) @25/30 fps.265 codec, high compression rate, ultra-low bit rate> Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire> Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection> Supports max. 256 GB Micro SD card and built-in Mic> 12V DC/PoE power supply> IP67 protection	IRR 31,790,000				








34	DH-IPC-HDBW2231E-S-S2	<p>2MP Lite IR Fixed-focal Dome Network Camera</p> <ul style="list-style-type: none"> > 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition> Outputs 2MP (1920 × 1080) @ 25/30 fps> H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 30 m> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire> Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection> Max. 256 GB Micro SD card> 12V DC/PoE power supply> IP67, IK10 protectio 	IRR 28,550,000	IRR 29,200,000		
35	DH-IPC-HDW2231TP-AS-S2-0380B	<p>2MP Lite IR Fixed-focal Eyeball Network Starlight Camera</p> <p>2MP, 1/2.8" Progressive CMOS</p> <p>low illumination 0.002 Lux @F1.6high image definition 2MP@25/30fps2.8mm fixed lensSMART H.264+/H.265+IVS Intrusion/TripwireWDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto SwitchMicro SD 256GB, Built-in Mic2V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>	IRR 32,050,000			
36	DH-IPC-HDW1239T1-LED-S5	<ul style="list-style-type: none"> · 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition · Outputs max. 2MP (1920 × 1080) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in efficient LED illuminator, and the max. illumination distance is 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access 	IRR 20,030,000	IRR 18,600,000		
37	DH-IPC-HDW1239T1-LED	<p>2MP, 1/2.8" Progressive CMOS</p> <p>low illumination 0.005 Lux @F1.6</p> <p>high image definition 2MP@25/30fps</p> <p>2.8mm fixed lens</p> <p>Smart H.265+/Smart H.264+</p> <p>DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination</p> <p>12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>	IRR 20,050,000			
38	DH-IPC-HDW2231TM-AS-S2	<ul style="list-style-type: none"> > 2MP 1/2.8" CMOS image sensor, low luminance, and high definition image.> Outputs max. 2MP (1920 × 1080)@25/30 fps.> H.265 codec, high compression rate, ultra-low bit rate.> Built-in IR LED, and the max. illumination distance is 30 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, appli cable to various monitoring scenes. · Intelligent monitoring: intrusion, tripwire. > Abnormality detection: Motion detection, privacy masking, audio abnormality, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.> Max. 256 G micro SD card; built-in MIC. > 12 V DC/PoE power supply. 	IRR 32,600,000			
39	DH-IPC-HDW2230T-AS-S2	<ul style="list-style-type: none"> > 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition > Outputs 2MP (1920 × 1080)@25/30 fps > H.265 coding, high compression ration, low bit rate> Built-in IR LED, max IR distance: 30 m> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable tovarious monitoring scenes> Intelligent detection: Intrusion, tripwire 	IRR 29,360,000	IRR 25,500,000		
40	DH-IPC-HFW2230SP-S-S2	<ul style="list-style-type: none"> > 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition > Outputs 2MP (1920 × 1080)@25/30 fps > H.265 codec, high compression rate, ultra-low bit rate> Built-in IR LED, max IR distance: 30 m> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire> Abnormality detection: Motion 	IRR 26,880,000	IRR 24,000,000		
41	DH-IPC-T1B20P-L	<p>· 2MP IR Turret Network Camera · 1/2.7" 2Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 20fps@1080P(1920×1080) & 25/30fps@1.3MP(1280×960) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m · IP67, PoE</p>				
42	DH-IPC-T1B20P	<ul style="list-style-type: none"> · 1/2.7" 2Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 25/30fps@1080P(1920×1080) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m · IP67, PoE 				











43	DH-IPC-T1B40P	<ul style="list-style-type: none"> ·4MP IR Turret Network Camera ·1/3" 4Megapixel progressive CMOS ·H.265+ & H.265 dual-stream encoding ·20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·2.8 mm fixed lens (3.6mm optional), · Max IR LEDs Length 30m · IP67, PoE 					
44	DH-IPC-T2B20P-ZS	<ul style="list-style-type: none"> ·1/2.7" 2Megapixel progressive CMOS ·H.265+ & H.265 dual-stream encoding ·25/30fps@1080P(1920×1080) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·2.8"×12mm motorized ·Max IR LEDs Length 40m· Micro SD card memory, IP67, PoE 					
45	DH-IPC-B1B20P-L	<ul style="list-style-type: none"> ·2MP IR Mini-Bullet Network Camera ·1/2.7" 2Megapixel progressive CMOS ·H.265+ & H.265 dual-stream encoding ·25/30fps@1080P(1920×1080) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·2.8 mm fixed lens (3.6mm optional) ·Max IR LEDs Length 30m · IP67, PoE 					
46	DH-IPC-B1B20P	<ul style="list-style-type: none"> ·H.265+ & H.265 dual-stream encoding ·25/30fps@1080P(1920×1080) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & ·2.8 mm fixed lens (3.6mm optional) ·Max IR LEDs Length 30m · IP67, PoE 					
47	DH-IPC-B1B40P	<ul style="list-style-type: none"> ·H.265+ & H.265 dual-stream encoding ·20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·2.8 mm fixed lens (3.6mm optional) ·Max IR LEDs Length 30m· IP67, PoE 					
48	DH-IPC-B2B20P-ZS	<ul style="list-style-type: none"> ·H.265+ & H.265 dual-stream encoding ·25/30fps@1080P(1920×1080) · 2.8"×12mm motorized lens ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·Max IR LEDs Length 40m ·Micro SD card memory, IP67, PoE7 					
49	DH-IPC-B2B40P-ZS	<ul style="list-style-type: none"> ·1/3" 4Megapixel progressive CMOS ·H.265+ & H.265 dual-stream encoding: 2.8"×12mm motorized lens ·20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) ·DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DM 					
	DH-IPC-HDW1230T1-S5				IRR 16,850,000		
50	DH-IPC-HDW1230T1P-S5-0280B	<ul style="list-style-type: none"> 2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens 	IRR 20,710,000		IRR 18,500,000		
51	DH-IPC-HDBW3441EP-S	<ul style="list-style-type: none"> ·4MP IR Fixed focal Dome WizSense Network Camera ·4MP, 1/3" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 × 1520)@30 fps ·H.265 codec, high compression rate, low bit rate., Built-in IR LED, max. IR distance: 50 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) 					
52	DH-IPC-HDBW3441EP-AS	<ul style="list-style-type: none"> ·4MP IR Fixed focal Dome WizSense Network Camera, STARLIGHT ·4MP, 1/3" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 × 1520)@30 fps ·H.265 codec, high compression rate, low bit rate., Built-in IR LED, max. IR distance: 50 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) 					

53	DH-IPC-HDW3449TMP-AS-LED	<ul style="list-style-type: none"> Outputs max. 4MP (2688 x 1520) @ 30 fps H.265 codec, high compression rate, low bit rate- Built-in Warm LED, max. LEDs distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)- Abnormality detection: Motion detection, video tampering, scenechanging, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Supports max. 256 G Micro SD card, built-in Mic- 12V DC/PoE power support, IP67 protection- SMD Plus 	IRR 44,000,000				
54	DH-IPC-HDBW3441RP-ZAS	<ul style="list-style-type: none"> 4MP, 1/3" CMOS image sensor, low illuminance, high image definition Outputs max. 4MP (2688 x 1520)@30 fps, H.265 codec, high compression rate, low bit rate Built-in IR LED, max. IR distance: 40 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Supports max. 256 G Micro SD card 	IRR 69,000,000				
55	DH-IPC-HDW4831EMP-ASE	<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Smart detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (4mm optional)- Built-in Mic Max. IR LEDs Length 50m. Micro SD memory, IP67, PoE 					
56	DH-IPC-HDW4431EMP-AS	<ul style="list-style-type: none"> 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688x1520)- Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 50m Built-in Mic - Micro SD memory, IP67, PoE 					
57	DH-IPC-HDBW4431EP-S	<ul style="list-style-type: none"> 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688x1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 30m, Micro SD memory 256GB, IP67, IK10, PoE 					
58	DH-IPC-HDBW4831EP-ASE	<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Smart Detection supported, WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (4mm optional), 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 30m- Micro SD memory, IP67, IK10, PoE 					
59	DH-IPC-HDW5431RP-ZE	<ul style="list-style-type: none"> 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688x1520)- Built-in Mic WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens- Max. IR LEDs Length 50m Micro SD card memory, IP67, PoE 					
60	DH-IPC-HDBW5831RP-ZE	<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296)-> Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens-> Max. IR LEDs Length 50m Micro SD card memory, IP67,IK10, PoE 					
61	DH-IPC-HDBW5431RP-ZE	<ul style="list-style-type: none"> 4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m- Micro SD card memory, IP67,IK10, PoE 					













	DH-IPC-HFW5241EP-ZE-0560			IRR 111,700,000			
	DH-IPC-HFW5241EP-E			IRR 76,300,000			
	DH-IPC-HDBW5242E-ZE-MF			IRR 107,000,000			
62	DH-IPC-HDBW5442EP-ZE	<ul style="list-style-type: none"> 4MP IR Vari-Focal Dome Wi-Fi Mini Network Camera 1/1.8" 4Megapixel progressive scan CMOS ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments 25/30 fps@2688 × 1520, 50/60 fps@1080P (1920 × 1080) WDR (140 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS 	IRR 147,410,000	IRR 112,000,000			
63	DH-IPC-HDBW5631EP-ZE	<ul style="list-style-type: none"> 3IEP-ZE 1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 20fps@6M(3072×2048),25/30fps@4M(2688×1520) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m, Micro SD card memory, IP67,IK10, PoE+ 5MP 1/2.7" CMOS image sensor, low luminance, and high definition image. 					
	DH-IPC-HDW1530T-S6	<ul style="list-style-type: none"> Outputs max. 5MP (2880 × 1620) @20 fps and supports 2688 × 1520 (2688 × 1520) @25/30 fps. H.265 codec, high compression rate, and ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m. ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments. 			IRR 30,300,000		
	DH-IPC-HFW1530S-S6	<ul style="list-style-type: none"> 5MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 5MP (2880 × 1620) @20 fps and supports 2688 × 1520 (2688 × 1520) @25/30 fps. H.265 codec, high compression rate, and ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m. ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, Abnormally detection, 5MP Fixed focal Bullet Network Camera 			IRR 29,300,000		
	DH-IPC-HFW3541EP-AS (BLACK)	<ul style="list-style-type: none"> 5MP, 1/2.7" CMOS image sensor, low luminance, high image definition Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps H.265 codec, high compression rate, low bit rate Built-in IR LED, max. IR distance: 50 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes 			IRR 49,000,000		
64	DH-IPC-HFW2531TP-ZS	<ul style="list-style-type: none"> 1/2.7" 5Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB · IP67, PoE+ 2.7"~13.5mm motorized lens· Max IR LEDs Length 60m 					














65	DH-IPC-HFW2831TP-ZS	<ul style="list-style-type: none"> - 1/1.8" 8Megapixel progressive CMOS - H.265 & H.264 dual-stream encoding - 25/30fps@8MP(3840x2160) - WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & - Micro SD card slot, up to 128GB- 3.7"-11mm motorized lens - Max IR LEDs Length 60m- IP67, IK10(optional), PoE 				
66	DH-IPC-HFW3449EP-AS-LED	<ul style="list-style-type: none"> - 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 x 1520) @ 30 fps - H.265 codec, high compression rate, low bit rate - Built-in Warm LED, max. LED distance: 30 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) - Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection - Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic 	IRR 46,890,000			
67	DH-IPC-HFW3441EP-AS-0360B	<ul style="list-style-type: none"> - 4MP, 1/3" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 x 1520)@30 fps, H.265 codec, high compression rate, low bit rate - Built-in IR LED, max. IR distance: 50 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) 	IRR 56,650,000			
68	DH-IPC-HFW3441EP-SA	<ul style="list-style-type: none"> - 4MP, 1/3" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 x 1520)@30 fps, H.265 codec, high compression rate, low bit rate - Built-in IR LED, max. IR distance: 50 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) - Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection, Supports max. 256 G Micro SD card, built-in Mic - 12V DC/POE power supply, IP67 protection SMD Plus 				
69	DH-IPC-HFW4431EP-S-S4	<ul style="list-style-type: none"> - 1/3" 4 Megapixel progressive scan CMOS - H.265 & H.264 triple-stream encoding 25/30fps@4MP(2688 x 1520) - True Day/Night (ICR); WDR; BLC; 3DNR; AWB; AGC, Corridor Mode; Privacy Zones; Motion Detection - Smart Functions: Tripwire; Intrusion; Scene Change; Face Detect Integrated IR LEDs; maximum 40m illumination, Micro SD Card Support - Multiple network monitoring: Web viewer; CMS & Mobile 3.6mm Fixed Lens (81° Angle of View) - IP67 Weatherproof and metal construction with cable managed bracket PoE and 12Vdc power input 	IRR 38,420,000			
70	DH-IPC-HFW4431TP-S-S4	<ul style="list-style-type: none"> - 1/3" 4Megapixel progressive scan CMOS - H.265&H.264 triple-stream encoding - 25/30fps@4Mp(2688x1520), Smart Detection supported - WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - 3.6mm fixed lens (6mm, 8mm, 12mm optional) - Max. IR LEDs Length 80m - Micro SD memory 256GB, IP67, IK10, PoE 	IRR 43,270,000			
71	DH-IPC-HFW4831EP-SE	<ul style="list-style-type: none"> - 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS - H.265&H.264 triple-stream encoding - 15fps@4K(3840x2160), 25/30fps@3M(2304x1296) - Smart Detection supported, WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & - 2.8mm fixed lens (4mm optional)- Max. IR LEDs Length 40m - Micro SD Memory IP67, PoE 				
72	DH-IPC-HFW5442EP-Z4E-0832	<ul style="list-style-type: none"> - 1/1.8" 4Megapixel progressive scan CMOS (AI-SATRLIGHT) - H.265 & H.264 triple-stream encoding - 25/30 fps@2688 x 1520, 50/60 fps@1080P(1920 x 1080) - WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS - 2.7 mm-12.0 mm motorized lens, - 2/1 Alarm in/out, 1/1 audio in/out - Max. IR LEDs Length 50 m - Micro SD memory, IP67, IK10 	IRR 156,830,000			
73	DH-IPC-HFW5541TP-A5E	<ul style="list-style-type: none"> - 1/2.7" 5Megapixel progressive scan CMOS - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - 20 fps@2592 x 1944, 50/60 fps@1080P (1920 x 1080), WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC, Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS - 2.8 mm fixed lens (3.6 mm, 6.0 mm, 8.0 mm, 12.0 mm optional) - 1/1 Alarm in/out, 1/1 audio in/out, - Max. IR LEDs Length 80 m, - Micro SD memory, IP67, IK10 				












74	DH-IPC-HFW5631EP-ZE	<ul style="list-style-type: none"> 6MP WDR IR Bullet Network Camera 1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 20fps@6M(3072x2048),25/30fps@4M(2688x1520), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens- Max. IR LEDs Length 50m-- Micro SD memory, IP67, IK10, PoE 				
75	DH-IPC-HFW5842EP-ZE-2712-S2	<ul style="list-style-type: none"> MP IR Vari-focal Bullet WizMind Network Camera > 8MP 1/1.8" CMOS image sensor, low illumination, high image definition (high definition image). > Outputs max. 8MP (3840x 2160) @30 fps.> Max. IR distance: 60 m.> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.> 12V DC/PoE power supply.> ePoE, IP67, IK10 protection.> SMD 3.0 	IRR 153,510,000			
	DH-IPC-HFW5842E-ZE-2712-S2		IRR 149,520,000			
76	DH-IPC-HDBW5842EP-ZE-2712-S2	<ul style="list-style-type: none"> 8MP IR Vari-focal Dome WizMind Network Camera > 8MP 1/1.8" CMOS image sensor, low illumination, high image definition. > Outputs max. 8MP (3840x 2160) @30 fps.> Max. IR distance: 40 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.> Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.> 24V AC/PoE/12V DC power supply.> ePoE, IP67, IK10 protection.> SMD 3 	IRR 153,510,000			
77	DH-IPC-HFW5831EP-ZE	<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens- Max. IR LEDs Length 50m Micro SD memory, IP67, IK10, PoE 				
78	Cube IP Camera					
79	DH-IPC-K22P	<ul style="list-style-type: none"> 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 x 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Max. IR distance: 10 m Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes 				
80	DH-IPC-K100W	<ul style="list-style-type: none"> 1/3" 1.3Megapixel Aptina CMOS H.264 & MJPEG dual-stream encoding Max 15fps@1.3M (1280x960)/25/30fps@720P(1280x720) DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens • White LEDs length 10m PIR sensor range 6m • Micro SD memory, Wi-Fi 				
81	PTZ IP CAMERA					
82	DH-SD5A432XA-HNR	<ul style="list-style-type: none"> 4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm~156 mm Powerful 32x optical zoom, Max. Aperture F1.35~F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation 	IRR 359,430,000			
	DH-SD59232XA-HNR		IRR 337,000,000			
83	DH-SD59230U-HNI	<ul style="list-style-type: none"> 2MP 32x Starlight IR WizSense Network PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS 				







84	DH-SD49225-HC-LA1	<p>2MP 25x Starlight IR PTZ HDCVI Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom> Starlight technology> 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IR distance up to 100 m > IP66 	IRR 155,470,000					
85	DH-SD29204UE-GN	<ul style="list-style-type: none"> · 1/2.8" STARVIS™ CMOS · STARLIGHT · Powerful 4x optical zoom · Support Triple-streams encoding · WDR, Day/Night(ICR), Ultra DNR · Max. 25/30fps@1080P · IVS · Support PoE · IR distance up to 30m 						
87	DH-SD5A232XA-HNR	<ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P, > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS, > PoE+ > IP67, IK10, Face Detection 	IRR 352,600,000					
87	DH-SD5A232XB-HNR	<ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P, > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS, > PoE+ > IP67, IK10, Face Detection 	IRR 335,000,000					
	DH-SD6AL445XA-HNR			IRR 715,000,000				
88	SD42215-HC-LA	<p>2MP 15x Starlight HDCVI PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 15x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IK10 > IP66 	IRR 114,760,000					
	DH-PTZ-SD49425XB-HNR	<p>4MP 25x Starlight IR WisSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 4Megapixel CMOS > Powerful 25x optical zoom > Starlight technology > Max.25/30fps@4M > Perimeter protection > Support PoE+ > IR distance up to 100m > SMD PLUS > IP66 			IRR 190,200,000			
89	DH-SD49225XA-HNR	<p>2MP 25x Starlight IR PTZ AI Network Camera</p> <p>1/2.8" STARVIS™ CMOS</p> <p>H.265+/H.265/H.264+/H.264/MJPEG (sub stream)Max. 1~60fps@1080P,960P, 720P</p> <p>4.8mm~120mm 25x optical zoomMax 240°/s pan speed, 360° endless pan rotation</p> <p>WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus</p>						
90	NVR							
91	DHI-NVR1104HS-S3/H	<p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback</p> <p>Smart H.265+/Smart H.264+/H.265/H.264</p> <p>Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding.Up to 8MP Resolution for Preview & Playback</p> <p>Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)</p>	IRR 22,580,000					
92	DHI-NVR1108HS-S3/H	<p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback</p> <p>Smart H.265+/Smart H.264+/H.265/H.264</p> <p>Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback</p> <p>Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)</p>	IRR 26,140,000					
93	DHI-NVR2108HS-4KS2(S)	<ul style="list-style-type: none"> · H.265/H.264 codec decoding · Max 80Mbps incoming bandwidth · Up to 8Mp resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output 	IRR 35,300,000					

	DHI-NVR2108HS-i2	<p>8 Channel Compact 1U 1HDD WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format > Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding > 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR) <p>New 4.0 user interface</p>		IRR 43,200,000					
94	DHI-NVR2108HS-I	<ul style="list-style-type: none"> > Remote surveillance, live view and video play on mobile phone App> Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding> Supports mainstream cameras of ONVIF and RTSP protocols> H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch> 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P> 1-channel face 	IRR 51,260,000	IRR 43,150,000					
95	DHI-NVR2116HS-i2			IRR 54,800,000					
95	DHI-NVR2116HS-4KS2(S)	<ul style="list-style-type: none"> > Smart H.265+/H.265/Smart H.264+/H.264 > Max 80Mbps Incoming Bandwidth > Up to 8MP Resolution for Preview and Playback > Up to 2ch@4K/8ch@1080P decoding > HDMI/VGA simultaneous video output > Support IPC 		IRR 42,000,000					
96	DHI-NVR2216p-I			IRR 95,000,000					
96	DHI-NVR2216-I	<p>16 Channel 1U WizSense Network Video Recorder</p> <ul style="list-style-type: none"> > New 4.0 user interface> Remote surveillance, live view and video play on mobile phone App> Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch > 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P > 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images > Security baseline 2.1 	IRR 68,230,000						
97	DHI-NVR2216-4KS2	<p>16 Channel 4K Lite H.265 NVR 1/4 Live & Playback</p> <p>Dual-core embedded processor, H.265/H.264 codec decoding</p> <p>Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding</p> <p>HDMI/VGA simultaneous video output</p> <p>2 SATA III Ports, up to 6TB capacity for each, Total 12TB</p> <p>1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only</p> <p>1 RJ-45 port (1000Mbps), P2P Support</p> <p>40,000,000</p> <p>77 NVR2116HS-I</p> <p>16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback</p> <p>Smart H.265+/H.264+/MJPEG</p>	IRR 50,830,000						
98	DHI-NVR4216-4KS2/L	<p>New UI interface with more easier operation experience</p> <ul style="list-style-type: none"> · Smart H.265+/ Smart H.264+ · P2P remote surveillance, video play on mobile device · 16-ch@720P(30FPS), self-adaptive decoding capability · Supports mainstream cameras of ONVIF and RTSP protocol · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K- Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches- DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain 	IRR 77,670,000	IRR 68,670,000					
99	DHI-NVR4104HS-P-4KS2/L	<p>New 4.0 user interface, Security baseline 2.1</p> <ul style="list-style-type: none"> > H.264, H.265, Smart H.264+, and Smart H.265+ H.265 auto switch > Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > P2P remote surveillance, video play on mobile device > VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K 	IRR 58,940,000						

100	DHI-NVR4232-4KS2	32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0)	IRR 74,360,000				
101	DHI-NVR5232-4KS2(V2.	32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support	IRR 130,540,000		IRR 138,960,000		
102	DH-NVR1104HS-P-S3/H	- New 4.0 user interface - P2P remote surveillance, video play on mobile device - 4-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.265/H.264 - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P					
103	DH-NVR4108HS-8P-4KS2	16 Channel Compact 1U 8PoE 4K&H.265 Lite Network Video Recorder - Smart H.265+/H.265/Smart H.264+/H.264 - Max 80Mbps Incoming Bandwidth - Up to 8MP Resolution for Preview and Playback - Up to 2ch@4K/8ch@1080P decoding - HDMI/VGA simultaneous video output - Support IPC UPnP, 8PoE ports					
104	DH-NVR4108HS-8P-4KS2/L	- New 4.0 user interface, Security baseline 2.1 - H.264, H.265, Smart H.264+, and Smart H.265+, H.265 auto switch - Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding - Supports mainstream cameras of ONVIF and RTSP protocols - P2P remote surveillance, video play on mobile device - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K - AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD - Supports remote configuration and management of IPC, such as setting parameters, getting information, and					
105	DH-NVR1108HS-8P-S3/H	- New 4.0 user interface - P2P remote surveillance, video play on mobile device - 8-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.265/H.264- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P - Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the camera (via batched DHCP/Dynamic Host Configuration Protocol)					
106	NVR2104HS-I	- 4 channel IP camera input 1U Lite 4K - H.265/H.264 codec decoding . 100 Mbps Network Card . P2P support - Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output - Up to 8Mp resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - Support 1 SATA HDD up to 6TB, 2 USB2.0		IRR 32,600,000			
106	DH-NVR2104HS-4KS2	- 4 channel IP camera input 1U Lite 4K - H.265/H.264 codec decoding . 100 Mbps Network Card . P2P support - Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output - Up to 8Mp resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - Support 1 SATA HDD up to 6TB, 2 USB2.0					
107	DH-NVR2104HS-P-I2	4 Channel Compact 1U 4PoE Lite 4K, H.265/H.264 codec decoding - Max 80Mbps incoming bandwidth-Up to 8Mp resolution - preview&playback-Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output - Support 1 SATA HDD up to 6TB, 2 USB2.0 - 100 Mbps Network Card-4PoE Port. P2P support		IRR 45,700,000			
107	DH-NVR2104HS-P-4KS2	4 Channel Compact 1U 4PoE Lite 4K, H.265/H.264 codec decoding - Max 80Mbps incoming bandwidth-Up to 8Mp resolution - preview&playback-Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output - Support 1 SATA HDD up to 6TB, 2 USB2.0 - 100 Mbps Network Card-4PoE Port. P2P support					
108	DH-NVR2108-8P-4KS2	8 Channel Smart 1U 8PoE Lite 4K H.265 Network Video Recorder> Smart H.265+/Smart H.264+/H.265/H.264> Max 80Mbps incoming bandwidth> Up to 8Mp resolution preview&playback > Up to 1ch@8MP/4ch@1080P decoding> HDMI/VGA simultaneous video output > Support IPC UPnP, 8PoE ports	IRR 56,200,000				
109	DH-NVR2108HS-8P-i			IRR 72,500,000			

109	DH-NVR2108HS-8P-4KS2	<ul style="list-style-type: none"> · H.265/H.264 codec decoding, HDMI/VGA simultaneous video output · Max 80Mbps incoming bandwidth · Up to 8Mp resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · Support 1 SATA HDD up to 6TB, 2 USB2.0 · 100 Mbps Network Card-8Port PoE, P2P support 	IRR 58,540,000						
110	DH-NVR4104HS-4KS2/L	<ul style="list-style-type: none"> · Smart H.265+/H.265/Smart H.264+/H.264 · Max 80Mbps Incoming Bandwidth · Up to 8MP Resolution for Preview and Playback · Up to 2ch@4K/8ch@1080P decoding · HDMI/VGA simultaneous video output · 1 SATA III Port, Up to 6 TB capacity for each HDD 	IRR 39,750,000	IRR 36,200,000					
112	DH-NVR4108HS-4KS2	<ul style="list-style-type: none"> · 8 Channel Compact 1U 4K&H.265 Lite Network Video Recorder · Smart H.265+/H.265/Smart H.264+/H.264 · Max 80Mbps Incoming Bandwidth · Up to 8MP Resolution for Preview and Playback · Up to 2ch@4K/8ch@1080P decoding · HDMI/VGA simultaneous video output 	IRR 41,900,000						
113	DH-NVR4108HS-4KS2/L	<ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+, H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people 	IRR 60,600,000	IRR 41,400,000					
114	DH-NVR4116HS-4KS2/L	<ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+, H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people 	IRR 55,000,000		IRR 55,740,000				
115	NVR4208-8P-4KS2/L				IRR 86,000,000				
115	DH-NVR4216-16P-4KS2/L	<ul style="list-style-type: none"> · 16 Channel 1U 2HDDs 16PoE Network Video Recorder- New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+, H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · 32-channel IP video access · Smart H.265+/Smart H.264+/H.265/H.264, H.265 auto switch · Max 200 Mbps incoming bandwidth · Up to 8MP resolution for preview and playback · 8-channel decoding@1080p (30 fps) · AI by Camera: Perimeter protection; SMD Plus; people counting; heat map 	IRR 129,140,000						
116	DH-NVR4232-4KS2	<ul style="list-style-type: none"> · Smart H.265+/Smart H.264+/H.265/H.264, H.265 auto switch · Max 200 Mbps incoming bandwidth · Up to 8MP resolution for preview and playback · 8-channel decoding@1080p (30 fps) · AI by Camera: Perimeter protection; SMD Plus; people counting; heat map 							
117	DH-NVR4232-4KS2/L	<ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+, H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people 	IRR 91,110,000		IRR 84,020,000				
118	DH-NVR4432-4KS2-L	<ul style="list-style-type: none"> · 32 channel Live Preview-H.265/H.264 codec decoding · Max 200Mbps incoming bandwidth · Up to 8MP Resolution for Preview and Playback · HDMI/VGA simultaneous video output, · Support 4 SATA HDD up to 6TB · 2 USB Ports (1 USB2.0, 1 USB3.0) · 16 Alarm Input, 4 Relay Output, RS232, RS485 · > 8/16-channel IP video access 	IRR 154,680,000						
119	DHI-NVR5208-8P-4KS2	<ul style="list-style-type: none"> · > Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch · > Max 320 Mbps incoming bandwidth · > Up to 24MP resolution for live view and playback · > 1-channel fisheye dewarping (AI by NVR) · > AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map 	IRR 151,260,000						
120	DHI-NVR5208-4KS2	<ul style="list-style-type: none"> · Smart H.265+/H.265/Smart H.264+/H.264/MJPEG · Max 320Mbps Incoming Bandwidth · Up to 12MP Resolution for Preview and Playback · HDMI/VGA simultaneous video output 	IRR 109,250,000						
121	DH-NVR5216-4KS2	<ul style="list-style-type: none"> · 16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00) · Smart H.265+/H.265/Smart H.264+/H.264/MJPEG · Max 320Mbps Incoming Bandwidth · Up to 12MP Resolution for Preview and Playback · HDMI/VGA simultaneous video output · 2 SATA III Ports, Up to 10 TB capacity for each HDD 	IRR 148,020,000						

122	DH-NVR5216-16P-4KS2E	<ul style="list-style-type: none"> .32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder . 32-channel IP video access . Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch . Max 320 Mbps incoming bandwidth . Up to 24MP resolution for live view and playback . 1-channel fisheye dewarping (AI by NVR) . AI by Camera: Perimeter protection, Face detection and recognition, SMD Plus, video metadata 						
123	DH-NVR5216-16P-I	<ul style="list-style-type: none"> .16 Channel 1U 1PoE AI Network Video Recorder . 16 Channel IP video access . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Up to 16 Channel perimeter protection . Up to 4 Channel video stream face recognition . Up to 22 face pictures /sec processing . Up to 70 face databases with 100,000 face images in total 		IRR 31,000,000				
124	DH-NVR5432-4KS2	<ul style="list-style-type: none"> .32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . 2HDMI/2VGA simultaneous video output . 1-8 PoE Ports Support 800m ePoE & EoC 		IRR 180,070,000				
125	DH-NVR5432-16P-4KS2E	<ul style="list-style-type: none"> . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . 2HDMI/VGA simultaneous video output . 3D intelligent positioning with Dahua PTZ camera . 4 SATA III Ports, Up to 8 TB capacity for each HDD 						
126	DH-NVR5832-4KS2	<ul style="list-style-type: none"> .32 Channel IPC Input, 32 Channel Live Preview . H.265/H.264/MJPEG/MPEG4 codec decoding . Max 320Mbps incoming bandwidth . P2P Support-Raid 0/1/5/6/10 . Up to 12Mp resolution preview&playback . Max 16ch@1080P 4ch@4K H.265 H.264 Playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 4 USB2, USB3, 0, 2, 1 USB2, 0 . Intel dual-core Processor-32 channel IPC input 						
127	DH-NVR608-32-4KS2	<ul style="list-style-type: none"> . 32 Channel Live Preview: 16 Alarm In , 8 Relay Output . (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding, . Max 384Mbps incoming bandwidth . Up to 12Mp resolution preview&playback, . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 1 eSATA Port . Support Raid 0/1/5/6/10, 4 USB2, USB3, 0, 2, 1 USB2, 0 . Intel dual-core Processor 		IRR 269,930,000				
128	DH-NVR608-64-4KS2	<ul style="list-style-type: none"> . 64 channel IPC input-32 Channel Live Preview: . (1st Screen:1st Screen: 1/4/8/9/16/25/36, 2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth . 2HDMI/VGA simultaneous video output . Up to 12Mp resolution preview & playback . RS232 , RS485-16 Alarm In . Support 8 SATA HDDs up to 64TB, 1 eSATA Port . Support Raid 0/1/5/6/10 		IRR 525,890,000	IRR 447,000,000	IRR 509,010,000		
129	DH-NVR608-128-4KS2	<ul style="list-style-type: none"> 64/128 Channel 2U 8HDDs Ultra series Network Video Recorder > New 4.0 user interface> 16-channel decoding@1080p (30 fps); self-adaptive decoding capability> Access, storage or forwarding at 384 Mbps> Simultaneous video output for VGA and HDMI1; 4K heterogeneous output for the 2 HDMI ports > Supports RAID 0/1/5/10Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10 > Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches> AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis> N+M cluster. When the host fails, the standby device will continue to record; once the host recovers, video recorded on the standby device will be transmitted back 		IRR 604,550,000				
130	DH-NVR104-P	<ul style="list-style-type: none"> .4CH Smart Box 4PoE Network Video Recorder . Up to 4 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan) 						
131	DH-NVR108-P	<ul style="list-style-type: none"> .8CH Smart Box 4PoE Network Video Recorder . Up to 8 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 						
132	DH-NVR1B08	<ul style="list-style-type: none"> . H.265+/H.264+ codec decoding . Max 8 channel IP camera inputs . Max 80Mbps incoming bandwidth . Up to 8MP resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output 						

133	DH-NVR1B08HS-8P	<ul style="list-style-type: none"> - H.265+/H.264+ codec decoding - Max 80Mbps incoming bandwidth - Max 8 channel IP camera inputs - Up to 8MP resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output, Support IPC UPnP, 8PoE ports - 1 SATA III Port, up to 6TB capacity for each HDD 					
134	DH-NVR1B08HS	<ul style="list-style-type: none"> - H.265+/H.264+ codec decoding - Max 8 channel IP camera inputs - Max 80Mbps incoming bandwidth - Up to 8MP resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output - 1 SATA III Port, up to 6TB capacity for each HDD 					
135	DH-NVR1B04-4P	<ul style="list-style-type: none"> - H.265+/H.264+ codec decoding - Max 4 channel IP camera inputs, - Max 80Mbps incoming bandwidth - Up to 8MP resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output, - Support IPC UPnP, 4PoE ports - 1 SATA III Port, up to 6TB capacity for each HDD 					
136	DH-NVR1B04	<ul style="list-style-type: none"> - 4 Channel Smart 1U H.265 Network Video Recorder - H.265+/H.264+ codec decoding - Max 4 channel IP camera inputs - Max 80Mbps incoming bandwidth - Up to 8MP resolution preview&playback - Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output 					
137	DH-NVR2B16	<ul style="list-style-type: none"> - 16 Channel 1U H.265 Network Video Recorder - H.265+/H.264+ codec decoding - Max 16 channel IP camera inputs, - Max 80Mbps incoming bandwidth - Up to 8MP resolution preview&playback, - Up to 1ch@8MP/4ch@1080P decoding - HDMI/VGA simultaneous video output, 2 SATA III Ports, up to 6TB capacity for each HDD 					
138	DHI-NVR5432-4KS2(V2.	<ul style="list-style-type: none"> - 32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) - Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding - Max 320Mbps incoming bandwidth - Up to 12Mp resolution preview & playback - Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding - 2*HDMI/2*VGA simultaneous video output 	IRR 190,000,000				

هایک ویژن تهران



نماینده رسمی هایک ویژن در ایران









09906500074









تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران









Hikvisiontehran


















	Items	Description	User Price	
1	THC-B110-M	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	ناموجود	
	THC-B120-PC (2.8MM)	2 MP high-performance CMOS 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed focal lens Day/Night switch EXIR 2.0, smart IR, up to 20 m IR distance 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP66	IRR 6,220,000	








2	THC-B120-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 7,320,000	
3	THC-B120-MS	2 MP Audio Fixed Mini Bullet Camera Smart IR, up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 9,150,000	
	THC-B120-MC(2.8MM)	2 MP Fixed Mini Bullet Camera 1080p bullet camera Smart IR, up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 7,320,000	
	THC-B150-M (2.8MM)	5 MP Fixed Mini Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 2.8 mm and 3.6 mm fixed focal lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)	IRR 9,880,000	
	THC-B123-M	2 MP Ultra Low Light Fixed Mini Bullet Camera 1080p bullet camera Good night-time performance with ultra-low light 0.005 lux Clear imaging against strong back light due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance	IRR 9,510,000	
4	THC-B120-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 7,690,000	
5	THC-B120-MPIRL	2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66	ناموجود	
6	THC-B140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	ناموجود	







7	THC-B140-M	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	ناموجود	
8	THC-B220	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 8,780,000	
9	THC-B220C	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	ناموجود	
10	THC-B220-M	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	ناموجود	
11	THC-B240	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	ناموجود	
12	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR- DWDR, OSD Menu, IP66, 2.8/3.6/6mm Lens,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	ناموجود	
13	THC-T110-P	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	ناموجود	
	THC-T120-PS(2.8 MM)	2 MP Indoor Audio Fixed Turret Camera 1080P turret camera Up to 20 m IR distance for bright night imaging Water and dust resistant (IP66) One port for four switchable signals (TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 7,690,000	







	THC-T123-P(2.8MM)	<p>2 MP Ultra Low Light Indoor Fixed Turret Camera 1080p turret camera</p> <p>Good night-time performance with ultra-low light 0.005 lux Clear imaging against strong back light due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	IRR 7,690,000	
14	THC-T120-PC	<p>2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC</p>	ناموجود	
15	THC-T120	<p>2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC</p>	ناموجود	
16	THC-T123	<p>2 MP EXIR Turret Camera-performance CMOS- Ultra low light- 1920 × 1080 resolution- 2.8 mm, 3.6 mm, 6 mm fixed lens- Day/Night switch EXIR 2.0, smart IR, up to 30 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</p>	ناموجود	
17	THC-T1+B26:B2720-MS	<p>2 MP Audio Fixed Turret Camera Smart IR, up to 20 m IR distanceWater resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together</p>	ناموجود	
18	THC-T120-M	<p>2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL</p>	ناموجود	
19	THC-T140-P	<p>4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66</p>	IRR 9,510,000	
20	THC-T140	<p>4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66</p>	IRR 9,880,000	







21	THC-T140-M	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	IRR 10,250,000	
22	THC-T220-P	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	ناموجود	
23	THC-T220-PC	2 MP Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 6,860,000	
24	THC-T220-MC	HiLook 2MP EXIR Turret Cam with Fixed Lens 1080p turret camera Smart IR, up to 40 m IR distanceWater resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	ناموجود	
25	THC-T220-MS	2 MP Audio Fixed Turret Camera Smart IR, up to 40 m IR distanceWater resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	ناموجود	
26	THC-T220-M	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	ناموجود	
27	THC-T240-P	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 10,790,000	
28	THC-T240-M	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 11,710,000	
Vari-Focal Series				


29	THC-B320-VF	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,,DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 17,560,000	
30	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 19,390,000	
31	THC-D320-VF	2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output-,IK10-Full Metal	IRR 19,020,000	
32	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 20,120,000	
33	THC-T320 VF	2MP CMOS Sensor, 40m IR, EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 17,560,000	
34	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 19,390,000	
Turbo HD PTZ Camera				
35	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	IRR 95,100,000	

36	PTZ-T4215I-D	<p>1/2.8" HD progressive scan CMOS</p> <p>1920 × 1080 resolution 15× optical zoom, 16× digital zoom</p> <p>120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance</p> <p>3D intelligent positioning</p> <p>Switchable TVI/AHD/CVI/CVBS video outputs</p>	IRR 80,470,000	
37	PTZ-T5225I-A	<p>1/2.8" HD progressive scan CMOS 1920 × 1080 resolution</p> <p>25× optical zoom DWDR (Digital Wide Dynamic Range)</p> <p>Up to 150 m IR distance 3D intelligent positioning</p> <p>Switchable turbo HD and CVBS outputs</p>	ناموجود	
DVR 4 Channel				
38	DVR-104G-F1	<p>4-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/ AHD/ CVI/ CVBS/ IP), Long distance transmission over UTP and coaxial cable, H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, Encoding ability up to 1080p lite @ 12 fps, One HDD for continuous video recording, Smart search for efficient playback.</p>	ناموجود	
39	DVR-204G-F1	<p>Recording Capability HD1080p Lite</p> <p>4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, - 1-ch Up to 960P resolution), 1 SATA (6TB) interface, HD1080p Lite @ 25 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	ناموجود	
40	DVR-204Q-F1	<p>Recording Capability 3MP</p> <p>4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input (up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4: 1920×1080P: 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	ناموجود	
41	DVR-204Q-K1	<p>H265+ compression saving up to 50% on bandwidth and storage.</p> <p>Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1)</p> <p>Support self-adaptive HDTV/ HDCVI/ AHD/ CVBS signal input. Add up to 2 x 6MP IP cameras. HDMI output at 1920 x 1080 resolution</p> <p>Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.</p>	IRR 21,950,000	
42	DVR-204U-F1	<p>Recording Capability 5MP/3MP</p> <p>4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, - 2-ch IP video input (up to 6MP resolution), 1 SATA (6 TB)- interface, 5MP@12fps, 4MP@15fps, 3MP@18fps, 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case--HDMI output HD1080p-Metal</p>	IRR 30,000,000	

43	DVR-204U-K1	<p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 Defogging function enabled for the supported analog cameras Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal</p>	IRR 31,280,000	
DVR 8 Channel				
44	DVR-108G-F1	<p>8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP), Long distance transmission over UTP and coaxial cable, H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, Encoding ability up to 1080p lite @ 12 fps, One HDD for continuous video recording, Smart search for efficient playback.</p>	ناموجود	
45	DVR-208G-F1	<p>Recording Capability HD1080p Lite 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	IRR 18,660,000	
46	DVR-208Q-F1	<p>Recording Capability 3MP 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	ناموجود	
47	DVR-208Q-K1	<p>Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).</p>	IRR 41,700,000	
48	DVR-208Q-K2	<p>8-ch 1080p 1U H.265 DVR-5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP)-Long distance transmission over UTP and coaxial cable-H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs-Supports 4 MP lite, and when enabled the image effect is similar with 4 MP-Encoding ability up to 1080p lite @ 15 fps-Two HDDs for continuous video recording Smart search for efficient playback.</p>	ناموجود	

49	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output 4K-Metal	IRR 47,730,000	
50	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 47,730,000	
Digital Video Recorder				
51	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	ناموجود	
52	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 32,190,000	
53	DVR-216G-K1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 30,700,000	
54	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	ناموجود	

55	DVR-216Q-F2	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 2 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	ناموجود	
56	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 53,660,000	
57	DVR-216Q-K2	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	ناموجود	
58	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-	IRR 95,130,000	
59	DVR-216U-K2	DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD - CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording	IRR 95,130,000	
60	DVR-232G-K2	32-ch 1080p Lite 1U H.265 DVR, transmission over UTP and coaxial cable H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, and when enabled the image effect is similar with 1080pEncoding ability up to 1080p lite @ 12 fps, 2HDDs for continuous video recording	IRR 84,250,000	

61	DVR-232Q-K2	<p>32-ch 1080p 1U H.265 DVR 5 signals input adaptively (HDTV/AV/HD/SD/TV/NTSC/PAL) H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs, Supports 4 MP lite, and when enabled the image effect is similar with 4 MP,Encoding ability up to 1080p lite @ 15 fps 2 HDDs for continuous video recording</p>	ناموجود	
----	-------------	---	---------	---

هایک ویژن تهران









نماینده رسمی هایک ویژن در ایران
















09906500074












تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران















Hikvisiontehran





Hilook-NVR

Items	Description	User Price	
1	IPC-B120 1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	ناموجود	
2	IPC-B120-D/W 2 MP Outdoor Fixed Bullet Network Camera with Build-in Mic High quality imaging with 2 MP resolution Efficient H.264 compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology Built-in microphone for real-time audio security Wireless connection for convenient installation and use	ناموجود	
3	IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR- Support mobile monitoring via Hik-Connect *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 18,770,000	
4	IPC-B121H 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265	IRR 18,290,000	
5	IPC-B121H-M 2 MP Fixed Bullet Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology, (IP67) EXIR 2.0: advanced infrared technology with long IR range	ناموجود	
6	IPC-B140H 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Conne *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 22,680,000	
7	IPC-B140H-M 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Conne *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	ناموجود	
8	IPC-B150H High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 29,260,000	
9	IPC-B220 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 18,770,000	
10	IPC-B220-D 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application-D model only support 12VDC power supply	IRR 17,930,000	
11	IPC-T120 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR -H.264+&H.264-2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 18,290,000	

12	IPC-T120-D	1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 17,560,000	
13	IPC-T220-H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 20,080,000	
14	IPC-T221-H	2 MP Fixed Turret Network Camera High quality imaging with 2 MP resolution,Efficient H.265+ Clear imaging against ,strong back light by DWDR technology Water and dust resistant (IP67) (PoE) technology	IRR 20,800,000	
15	IPC-T220	1/2.8" progressive scan CMOS BLC/3D DNR,1920 x 1080@30fps,IP67 2.8, 4, 6 mm fixed lens,Digital WDR,H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON);	IRR 19,600,000	
16	IPC-T240H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,-Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 27,000,000	
17	IPC-D120	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 18,660,000	
18	IPC-D120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,-2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	ناموجود	
19	IPC-D121H	2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology	IRR 18,290,000	
20	IPC-D121H-M	2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology-METAL CASE	IRR 18,290,000	
21	IPC-D140H	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR.	IRR 27,000,000	
22	IPC-D150H	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	ناموجود	
Vari-Focal Series				
23	IPC-B620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 38,190,000	
24	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 42,800,000	
25	IPC-B621-V	2 MP Varifocal Bullet Network Camera Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology(IP66) -V: model with manual vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 36,940,000	
26	IPC-B621-Z	2 MP Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light due to DWDR technology(IP66) -Z: model with motorized vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 42,060,000	

27	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,800,000	
28	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 47,550,000	
29	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC, WDR- up to 30m IR-DC12V & PoE, Support mobile monitoring via Hik-Connect *power supply no included 2.8~12mm VF lens-Eyeball: Metal Cover: Plastic-IP67	IRR 43,160,000	
30	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, DWDR- 3D DNR, BLC, 2.8~12mm varifocal lens - DC12V & PoE, TF card slot, up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 38,190,000	
31	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR - 3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)-IP67, IK10	IRR 46,820,000	
32	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 41,480,000	
33	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	ناموجود	
PanoVu Mini Series IR Network PTZ Camera				
34	PTZ-P332ZI-DE3	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkage Up to 10 m IR radius Panoramic Camera Three 1/2.8" progressive scan CMOS I 3-ch 1920 x 1080@30fps resolution! Horizontal FOV: 128.5° x 3 PTZ Camera 1/2.8" progressive scan CMOS I Up to 1920 x 1080@30fps resolution! 4x optical zoom, 8x digital zoom	ناموجود	
IP PTZ Camera				
35	PTZ-N4215-DE3	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	ناموجود	
36	PTZ-N4215I-DE	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 79,500,000	
37	PTZ-N4225I-DE	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 25x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 99,400,000	

38		Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10)	ناموجود	
Network Video Recorder				
39	NVR-104-B	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch @ 4MP-4-ch@1080p	IRR 15,150,000	
40	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),,Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 18,440,000	
41	NVR-108-B/8p	4-ch Mini 1U 4 PoE 4K NVR,Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Supports decoding H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 30,490,000	
42	NVR-104H-D	4-ch Mini 1U 4 PoE NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs,Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 14,370,000	
43	NVR-108H-D	4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 8-ch network camera inputs,Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 18,290,000	
44	NVR-104MH-C	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 19,750,000	
45	NVR-104MH-D	Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.	IRR 15,150,000	
46	NVR-104MH-D/4P	Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 25,020,000	
47	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080p	ناموجود	
48	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 27,800,000	
49	NVR-108MH-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF / 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 18,440,000	
50	NVR-208MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 33,970,000	
51	NVR-108MH-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	ناموجود	

52	NVR-108MH-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 47,500,000	
53	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,630,000	
54	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4K-Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	ناموجود	
55	NVR-216MH-C/16P	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	ناموجود	

هایک ویژن تهران

نماینده رسمی هایک ویژن در ایران

09906500074

تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران

Hikvisiontehran

Hard Disk				
	Items	Description	User Price	
	Surveillance HDD	Western Digital	Purple	
1	WD10PURX-WD Purple 1TB	Capacity 1TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
2	WD20PURX-WD Purple 2TB	Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
3	WD30PURX-WD Purple 3TB	Capacity 3TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
4	WD40PURX-WD Purple 4TB	Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
5	WD60PURX-WD Purple 6TB	Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
6	WD82PURX-WD Purple 8TB	Capacity 8TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 256MB	CALL	
7	WD101PURX-WD Purple 10TB		CALL	
8	WD121PURX-WD Purple 12TB		CALL	
11	Surveillance HDD	SEAGATE	SKYHAWK SURVEILLANCE	
12	ST2000VX - Seagate Surveillance 2TB	Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB	CALL	

13	ST3000VX - Seagate Surveillance 3TB		CALL	
14	ST4000VX - Seagate Surveillance 4TB	Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB	CALL	
15	ST6000VX - Seagate Surveillance 6TB	Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 7200 - Cache 256MB	CALL	
16	ST8000VX - Seagate Surveillance 8TB		CALL	
17	ST10000VX - Seagate Surveillance 10TB		CALL	
18	ST12000VX - Seagate Surveillance 12TB		CALL	
19	ST14000VX - Seagate Surveillance 14TB		CALL	
20	NAS HDD	 SEAGATE	 IRONWOLF	
21	ST2000VN - Seagate Iron Wolf 2TB		CALL	
22	ST3000VN - Seagate Iron Wolf 3TB		CALL	
23	ST4000VN - Seagate Iron Wolf 4TB		CALL	
24	ST6000VN - Seagate Iron Wolf 6TB		CALL	
25	ST8000VN - Seagate Iron Wolf 8TB		CALL	
26	ST10000VN - Seagate Iron Wolf 10TB		CALL	
27	ST12000VN - Seagate Iron Wolf 12TB		CALL	

28	ST14000VN - Seagate Iron Wolf 14TB		CALL	
Enterprise HDD  				
30	ST2000NM - Seagate EXOS 2TB		CALL	
31	ST3000NM - Seagate EXOS 3TB		CALL	
32	ST4000NM - Seagate EXOS 4TB		CALL	
33	ST6000NM - Seagate EXOS 6TB		CALL	
34	ST8000NM - Seagate EXOS 8TB		CALL	
35	ST10000NM - Seagate EXOS 10TB		CALL	
36	ST12000NM - Seagate EXOS 12TB		CALL	
37	ST14000NM - Seagate EXOS 14TB		CALL	
38	ST16000NM - Seagate EXOS 16TB		CALL	

هایک ویژن تهران

نماینده رسمی هایک ویژن در ایران

09906500074

تهران خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28 فروشگاه کمیران

Hikvisiontehran

Equip Rack

	Items	Description	User Price
	ER Standing Rack IP42		
1	ERS - 4761	رک 47 یونیت عمق 100-عرض 60 - درب جلو و درب عقب مشبک	158,500,000
2	ERS - 4461	رک 44 یونیت عمق 100-عرض 60 - درب جلو و درب عقب مشبک	156,800,000
3	ERS - 4281	رک 42 یونیت عمق 100-عرض 80 - درب جلو مشبک، درب پشت 2 لنگه مشبک	182,000,000
4	ERS - 4261	رک 42 یونیت عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	133,900,000
5	ERS - 4268	رک 42 یونیت عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	119,500,000
6	ERS - 4266	رک 42 یونیت عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	111,900,000
7	ERS - 3761	رک 37 یونیت عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	109,900,000
8	ERS - 3768	رک 37 یونیت عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	103,900,000
9	ERS - 3766	رک 37 یونیت عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	96,980,000
10	ERS - 3261	رک 32 یونیت عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	103,900,000
11	ERS - 3268	رک 32 یونیت عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	96,800,000
12	ERS - 3266	رک 32 یونیت عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	89,950,000
13	ERS - 2761	رک 27 یونیت عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	98,500,000
14	ERS - 2768	رک 27 یونیت عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	87,980,000

15	ERS - 2766	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۸۲,۵۰۰,۰۰۰
16	ERS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۸۴,۹۰۰,۰۰۰
17	ERS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۷۸,۵۰۰,۰۰۰
18	ERS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۷۳,۸۰۰,۰۰۰
19	ERS - 1868	رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۷۳,۹۰۰,۰۰۰
20	ERS-1866	رک ۱۸ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۶۹,۸۵۰,۰۰۰
21	ERS-1468	رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۶۳,۹۵۰,۰۰۰
22	ERS-1466	رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۶,۹۰۰,۰۰۰
23	ER Wall Mount		
24	ERW - 1266	رک دیواری - ۱۲ یونیت-عمق ۶۰، عرض ۶۰	۲۱,۵۰۰,۰۰۰
25	ERW - 0966	رک دیواری - ۹ یونیت-عمق ۶۰، عرض ۶۰	۱۹,۹۰۰,۰۰۰
26	ERW - 0964	رک دیواری - ۹ یونیت-عمق ۴۵، عرض ۶۰	۱۸,۵۰۰,۰۰۰
27	ERW - 0666	رک دیواری - ۶ یونیت-عمق ۶۰، عرض ۶۰	۱۵,۹۵۰,۰۰۰
28	ERW - 0663	رک دیواری - ۶ یونیت-عمق ۳۳، عرض ۶۰	۱۳,۵۰۰,۰۰۰
29	ERW - 0764	رک دیواری - ۷ یونیت-عمق ۴۵، عرض ۶۰	۱۶,۹۸۰,۰۰۰
30	ERW - 0366	رک دیواری - ۳ یونیت-عمق ۶۰، عرض ۶۰ (تاشو)	۲۵,۵۰۰,۰۰۰
31	ER OUTDOOR RACK بدون تخفیف		
32	ERO - 0745	رک ۷ یونیت -عمق ۴۵ OUTDOOR	۶۳,۰۰۰,۰۰۰
33	ERO - 0966	رک ۹ یونیت -عمق ۶۰ OUTDOOR	۷۴,۵۰۰,۰۰۰
34	ERO - 1266	رک ۱۲ یونیت -عمق ۶۰ OUTDOOR	۱۰۰,۰۰۰,۰۰۰
35	ERO - 1866	رک ۱۸ یونیت -عمق ۸۰ OUTDOOR	۱۰۸,۰۰۰,۰۰۰
		پایه ثابت زیرک اوت دور	۴,۵۰۰,۰۰۰
		نگهدارنده رک به دکل	۵,۵۰۰,۰۰۰
36	ER MAIN FRAME		
37	ERM - 4202	رک ۴۲ یونیت - آزمایشگاهی - چهار ستون	CALL
38	ERM - 4201	رک ۴۲ یونیت - آزمایشگاهی - دو ستون	CALL
39	ERM - 3202	رک ۳۲ یونیت - آزمایشگاهی - چهار ستون	CALL
40	Shelf		
41	ERA - SSW	طبقه ثابت رک های دیواری عمق ۳۳	۱,۱۵۰,۰۰۰
42	ERA - SSW	طبقه ثابت رک های دیواری عمق ۴۵	۱,۷۰۰,۰۰۰
43	ERA - SSW	طبقه ثابت رک های دیواری عمق ۶۰	۲,۱۵۰,۰۰۰
44	ERA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۲,۶۰۰,۰۰۰

45	ERA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۳,۶۰۰,۰۰۰
46	ERA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۴,۶۰۰,۰۰۰
47	ERA - SM 60	سینی متحرک رک ۶۰ سانتیمتر	۴,۵۰۰,۰۰۰
48	ERA - SM 80	سینی متحرک رک ۸۰ سانتیمتر	۴,۵۰۰,۰۰۰
49	ERA - SM 10	سینی متحرک رک ۱۰۰ سانتیمتر	۴,۵۰۰,۰۰۰
50	Power Module		
51	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۲,۵۳۰,۰۰۰
52	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۱,۵۰۰,۰۰۰
53	Accessories		
54	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۳,۰۰۰,۰۰۰
55	ERA - SCR - 20	پیچ و کزنات مخصوص رک بسته ۵۰ تایی	۸۸۰,۰۰۰
56	ERA - TR - 20	سیستم کنترل حرارت ، رطوبت ، ولتاژ ، جریان، دود- دیجیتال	۲۸,۲۷۰,۰۰۰
57	ERA - FN - 20	فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۱,۵۸۰,۰۰۰
		کیت فن یک یونیت ۶ تایی	۳,۹۵۰,۰۰۰
58	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ ۶ حلقه	۱,۴۵۰,۰۰۰
59	ERA - CM - 20	حلقه نگهدارنده کابل	۲۰۰,۰۰۰
60	ERA - CM - 30	نگهدارنده کابل درپوش دار	۷۵۰,۰۰۰
61	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۴۰۰,۰۰۰
62	Blank Panel		
63	ERA - BLA - 10	پانل ۱۰ یونیت	۴۲۰,۰۰۰
64	ERA - BLA - 20	پانل ۲۰ یونیت	۵۲۰,۰۰۰
65	ERA - BLA - 30	پانل ۳۰ یونیت	۶۷۰,۰۰۰
66	ERA - BLA - 40	پانل ۴۰ یونیت	۸۷۰,۰۰۰
67	ERA - BLA - 50	پانل ۵۰ یونیت فرچه ای	۱,۳۵۰,۰۰۰
68	Doors بدون تخفیف		
69	EDM - 0000	درب مشبک (جلو) جهت رک های ۲۷-۳۲-۳۷-۴۲-۴۷	۲۰,۰۰۰,۰۰۰
70	EDM - 0001	درب مشبک (عقب) جهت رک های ۲۷-۳۲-۳۷-۴۲-۴۷	۱۰,۰۰۰,۰۰۰
71	EDM - 0002	درب مشبک دو لنگه با قفل ریتال جهت رک های ۴۲-۴۴-۴۷	۲۴,۰۰۰,۰۰۰
	لازم به ذکر است درب مشبک شامل تخفیف نمی گردد		