

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



09906500074-66765968-66765923

ایمیل
Info@Hikvisiontehran.com




آدرس فروشگاه








تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28








شماره تماس








CONTACT US
HIKVISIONTEHRAN.COM







Turbo HD Camera - DVR








| Items | Description | User Price | |
|-----------------------|--|---------------|---|
| Turbo HD - 1MP | | | |
| 1 DS-2CE56C0T-IRP | 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR | IRR 5,410,000 |  |
| 2 DS-2CE56C0T-IRPF | 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS | IRR 5,820,000 |  |
| Turbo HD - 2MP | | | |
| 3 DS-2CE16D0T-ITF | 2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR | IRR 8,610,000 |  |







| | | | | |
|--|------------------------|--|----------------|---|
| 4 | DS-2CE16D0T-ITFS | <p>2 MP coaxial audio camera</p> <p>Enhancing safety with discreet and economical built-in microphone</p> <p>Transmits audio over the coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> | IRR 12,050,000 |  |
| 5 | DS-2CE16D0T-VFIR3F | <p>2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4</p> | IRR 19,780,000 |  |
| 6 | DS-2CE76D0T-ITPF | <p>2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p> | IRR 8,600,000 |  |
| 7 | DS-2CE76D0T-ITFS | <p>2 MP Audio Fixed Turret Camera</p> <p>2 MP coaxial audio camera, Enhancing safety with discreet and economical built-in microphone, Transmits audio over the coaxial cable. EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> | IRR 8,890,000 |  |
| 8 | DS-2CE76D0T-ITMFS | <p>2 MP coaxial audio camera</p> <p>Enhancing safety with discreet and economical built-in microphone</p> <p>Transmits audio over the coaxial cable</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> | IRR 12,100,000 |  |
| 9 | DS-2CE56D0T-VFIR3F | <p>2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4</p> | IRR 19,610,000 |  |
| Turbo HD - 2MP - Ultra Low Light Series | | | | |
| | DS-2CE76D3T-ITPF (NEW) | <p>2 MP Ultra Low Light Indoor Fixed Turret Camera, 2 MP turret camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.005 lux</p> <p>Clear imaging even against strong back lighting due to 120 dB true WDR technology, 3D DNR technology delivers clean and sharp images, EXIR 2.0: advanced infrared technology with 30 m IR distance, 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p> | IRR 10,590,000 |  |

| | | | | |
|----------------------------------|-------------------|---|----------------|---|
| 10 | DS-2CE16D3T-I3F | 2 MP high-performance CMOS .Ultra low light . 1920 × 1080 resolution . 2.8 mm, 3.6 mm, 6 mm fixed lens .Smart IR, up to 30 m IR distance . OSD menu, 3D DNR, 120 dB true WDR , day/night switch .4 in 1 video output (switchable TVI/AHD/CVI/CVBS) .IP67.Up the coax (HIKVISION-C) | IRR 11,750,000 |  |
| Turbo HD - 3MP- motorized | | | | |
| 11 | DS-2CE56F7T-IT3Z | 3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized vari-focal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof | IRR 33,260,000 |  |
| Turbo HD - 5MP | | | | |
| 12 | DS-2CE16H0T-ITFS | 5 MP Audio Fixed Mini Bullet Camera, 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone,Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) | IRR 13,610,000 |  |
| 13 | DS-2CE16H0T-IT1F | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | IRR 14,130,000 |  |
| 14 | DS-2CE16H0T-IT3F | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | IRR 14,480,000 |  |
| 15 | DS-2CE16H0T-IT5F | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | call |  |
| 16 | DS-2CE16H0T-IT3ZF | 5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | call |  |

| | | | | |
|---|-------------------|--|----------------|---|
| 17 | DS-2CE76H0T-ITMF | 5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) | IRR 13,720,000 |  |
| 18 | DS-2CE76H0T-ITMFS | 5 MP coaxial audio camera , Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) | IRR 13,770,000 |  |
| 19 | DS-2CE56H0T-ITMF | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | call |  |
| 20 | DS-2CE56H0T-IT1F | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | IRR 13,290,000 |  |
| 21 | DS-2CE56H0T-IT3F | 5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | IRR 16,250,000 |  |
| 22 | DS-2CE56H0T-IT3ZF | 5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67 | IRR 24,000,000 |  |
| TURBO HD 5MP (TURBO HD 5.0) PIR Series | | | | |
| 23 | DS-2CE71H0T-PIRL | 5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR | IRR 14,550,000 |  |
| Turbo HD - 8MP | | | | |

| | | | | |
|--|-----------------------|---|-----------------|---|
| 24 | DS-2CE78U8T-IT3 | 4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67 | IRR 38,840,000 |  |
| 25 | DS-2CE18U8T-IT3 | 4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67 | IRR 41,230,000 |  |
| Turbo HD PTZ Camera | | | | |
| 26 | DS-2AE4225TI-D | High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology -Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 × optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66) | IRR 107,860,000 |  |
| 27 | DS-2AE5223TI-A(24VAC) | 1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR | call |  |
| 28 | DS-2AE7230TI-A(24VAC) | High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30× optical zoom, focal length 4-120mm - 16× digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output | call |  |
| Turbo HD DVR 720P / 1080p lite | | | | |
| 30 | DS-7216HGHI-K1 | <u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 1080p lite/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u> : 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 37,480,000 |  |
| Turbo HD DVR 1080p / 3MP / 4MP lite | | | | |

| | | | | |
|--|-----------------|---|------------------------|---|
| 31 | DS-7204HQHI-K1 | <u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 29,690,000 |  |
| 33 | DS-7208HQHI-K1 | <u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 38,640,000 |  |
| 34 | DS-7116HQHI-K1 | <u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity | IRR 57,140,000 |  |
| 35 | 7216HQHI-K1-Eco | <u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - ECO CASE | IRR 65,460,000 |  |
| 36 | DS-7216HQHI-K1 | <u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 72,260,000 |  |
| 37 | DS-7216HQHI-K2 | <u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk | IRR 84,130,000 |  |
| 38 | DS-7232HQHI-K2 | <u>Analog video input</u> 32-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk | IRR 168,250,000 |  |
| Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite | | | | |

| | | | | |
|--|------------------|---|-----------------|---|
| 39 | DS-7204HUHI-K1 | Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 32,380,000 |  |
| 40 | DS-7208HUHI-K1 | Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> :8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | IRR 71,430,000 |  |
| 41 | DS-7216HUHI-K2 | Analog video input 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk | IRR 133,020,000 |  |
| Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series) | | | | |
| 42 | DS-7204HUHI-K1/P | Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 × 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable | IRR 39,080,000 |  |
| 43 | DS-7208HUHI-K2/P | Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable | IRR 74,090,000 |  |
| Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP | | | | |
| 44 | DS-7204HTHI-K1 | Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 8 MP resolution - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity | call |  |

45

DS-7208HTHI-K2

Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk

call



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویزن



آدرس فروشگاه
تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923





ایمیل









Info@Hikvisiontehran.com









CONTACT US









HIKVISIONTEHRAN.COM








Network Camera - NVR









| Items | Description | User Price | |
|--------------------------------|---|----------------|---|
| Lite Mini Bullet Series | | | |
| 1 DS-2CV1021G0-IDW1 | 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in WIFI | call |  |
| 2 DS-2CD1023G0E-I | 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE | IRR 20,310,000 |  |
| 3 DS-2CD1023G0-I | 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) | call |  |
| 4 DS-2CD1023G0-IU | 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in microphone | IRR 23,620,000 |  |








| | | | | |
|-------------------------|------------------------------------|---|----------------|---|
| 5 | DS-2CD1043G0E-I | 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range) - ECO CASE | IRR 27,230,000 |  |
| | DS-2CD1047G0-L ColorVu Lite | 4 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging | IRR 39,190,000 |  |
| 6 | DS-2CD1043G0-I | 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range) | IRR 27,230,000 |  |
| Lite Dome Series | | | | |
| 7 | DS-2CD1323G0E-I | 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 | call |  |
| 8 | DS-2CD1323G0-IU | 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone | IRR 22,280,000 |  |
| | DS-2CD1327G0-L ColorVu Lite | 2 MP ColorVu Lite Fixed Turret Network Camera, High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging | IRR 32,390,000 |  |
| 9 | DS-2CD1123G0E-I | 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE | IRR 21,770,000 |  |
| 10 | DS-2CD1123G0-I | 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) | call |  |








| | | | | |
|---------------------------|------------------------|---|----------------|---|
| 11 | DS-2CD1143G0-I | 4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range) | IRR 32,020,000 |  |
| Mini Bullet Series | | | | |
| 12 | DS-2CD2025FWD-I | 2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP67), Robust structure design with full metal material. | IRR 38,000,000 |  |
| 13 | DS-2CD2023G0-I | 2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | IRR 37,740,000 |  |
| 15 | DS-2CD2043G0-I | 4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | IRR 42,960,000 |  |
| 16 | DS-2CD2043G0-I (Black) | 4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | call |  |
| 18 | DS-2CD2063G0-I | 6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | IRR 44,180,000 |  |
| 19 | DS-2CD2083G0-I | 8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | IRR 47,890,000 |  |
| Dome Series | | | | |
| 20 | DS-2CD2123G0-IS | 2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors | call |  |








| | | | | |
|----|-------------------------|---|----------------|---|
| 21 | DS-2CD2143G2-IU | 4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning | IRR 43,140,000 |  |
| 23 | DS-2CD2143G0-IS (Black) | 4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x 1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors | call |  |
| 24 | DS-2CD2143G0-IU | 4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x 1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP66- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone | IRR 43,140,000 |  |
| 26 | DS-2CD2163G0-IS | 6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors | call |  |
| 27 | DS-2CD2163G0-IS (Black) | 6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors | IRR 46,370,000 |  |
| 28 | DS-2CD2163G0-IU | 6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone | IRR 45,140,000 |  |
| 29 | DS-2CD2183G0-IS | 8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors | IRR 51,800,000 |  |
| 30 | DS-2CD2183G0-IU | 8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP66, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone | call |  |

| | | | | |
|----------------------|-------------------------|--|----------------|---|
| 31 | DS-2CD2183G0-IS (Black) | 8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors | IRR 50,780,000 |  |
| Bullet Series | | | | |
| 33 | DS-2CD2T43G0-I5 | 1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range | IRR 49,260,000 |  |
| 34 | DS-2CD2T43G0-I8 | 1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range | IRR 51,210,000 |  |
| 35 | DS-2CD2T63G0-I5 | 6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR | call |  |
| 36 | DS-2CD2T63G0-I8 | 6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range | IRR 53,350,000 |  |
| 37 | DS-2CD2T83G0-I5 | 8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G | ناموجود |  |
| 38 | DS-2CD2T83G0-I8 | 8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range | IRR 56,380,000 |  |
| 39 | Exir Dome Series | | | |








| | | | | |
|--|------------------|---|----------------|---|
| 40 | DS-2CD2327WD-I | Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect | IRR 33,900,000 |  |
| Mini Dome Series | | | | |
| 42 | DS-2CD2523G0-IS | 1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO | call |  |
| 43 | DS-2CD2542FWD-IS | 1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO | call |  |
| 44 | DS-2CD2543G0-IS | 1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 × 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO | call |  |
| 45 | DS-2CD2563G0-IS | 1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 × 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO | call |  |
| Lite Bullet Vari-Facal Motorized Series | | | | |
| 46 | DS-2CD1623G0-I | 2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | IRR 43,660,000 |  |
| 47 | DS-2CD1623G0-IZ | 2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens | call |  |
| 48 | DS-2CD1643G0-I | 4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB | call |  |

| | | | | |
|---|-------------------|---|----------------|---|
| 49 | DS-2CD1643G0-IZ | 4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot,up to 128 GB - Z:Motorized VF lens | IRR 52,960,000 |  |
| Lite Dome Vari-Facal Series | | | | |
| 50 | DS-2CD1723G0-I | 2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR | call |  |
| 51 | DS-2CD1743G0-I | 4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR | call |  |
| 52 | DS-2CD1743G0-IZ | 4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens | IRR 56,670,000 |  |
| 53 | DS-2CD1753G0-I | 5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR , Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range | IRR 52,000,000 |  |
| Bullet Vari-Facal Motorized Series | | | | |
| 54 | DS-2CD2625FWD-IZS | 2MP Powered by DarkFighter Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials. | IRR 81,000,000 |  |
| 55 | DS-2CD2632F-I | 3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048×1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P | IRR 57,670,000 |  |










| | | | | |
|--|-------------------|--|-----------------|---|
| 56 | DS-2CD2643G2-IZS | 4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology,(IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning | IRR 77,630,000 |  |
| 57 | DS-2CD2663FG0-IZS | 6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps -2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens | call |  |
| 58 | DS-2CD2683G0-IZS | 8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens | call |  |
| Dome Vari-Facal Motorized Series | | | | |
| 60 | DS-2CD2743G1-IZS | 4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolutionEfficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology-S: audio and alarm interface available-Water and dust resistant (IP67) and vandal proof (IK10)-Motorized varifocal lens for easy installation and monitoring-Robust structure design with full metal materials | IRR 80,040,000 |  |
| 61 | DS-2CD2763G0-IZS | 6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens | call |  |
| 62 | DS-2CD2783G0-IZS | 8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens | call |  |
| Fish Eye Series | | | | |
| 63 | DS-2CD2955FWD-I | 5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 x 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range | IRR 103,350,000 |  |











| | | | | |
|--------------------------|------------------|--|-----------------|---|
| 63 | DS-2CD2955FWD-IS | 5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO | IRR 106,660,000 |  |
| Cube Smart Series | | | | |
| 64 | DS-2CD2420F-I(W) | Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB - IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker - Support Wi-Fi, support WPS configuration with one touch - Support PIR (Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter | IRR 26,000,000 |  |
| 65 | DS-2CD2421G0-IW | 1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS | IRR 28,800,000 |  |
| 66 | DS-2CD2423G0-IW | 1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS | call |  |
| 67 | DS-2CD2443G0-IW | 1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR - Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS | IRR 39,810,000 |  |
| Pin Hole Series | | | | |
| 68 | DS-2CD2D14WD | 1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P | call |  |
| 2Q Smart Series | | | | |
| 69 | DS-2CD2Q10FD-IW | 1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90 | IRR 29,840,000 |  |








2U Smart Series

| | | | | |
|----------------------|------------------|---|-----------------|---|
| 70 | DS-2CV2U21FD-IW | 2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card. | IRR 20,760,000 |  |
| IP PTZ Camera | | | | |
| 71 | DS-2DE4A225IW-DE | 4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome High quality imaging with 2 MP resolution,Excellent low-light performance via powered-by, DarkFighter technology, Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to monitor zones of interest,25x optical zoom allows for closer viewing of subjects in expansive areas,Up to 50m IR range ensures safety at night (IP66) | IRR 119,000,000 |  |
| 72 | DS-2DE4220IW-DE | 2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC | call |  |
| 73 | DS-2DE4225IW-DE | 2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 x 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology | call |  |
| 74 | DS-2DE4425IW-DE | 4MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 x 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology | IRR 156,140,000 |  |
| 75 | DS-2DE5230W-AE | 2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° - 150°/s | call |  |
| 77 | DS-2DE7232IW-AE | 2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression | call |  |

NVR-Monitor

| | | | | |
|----------------------|-------------------|--|-----------------|---|
| 78 | DS-7600NI-E1/A | Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed | IRR 156,500,000 |  |
| NVR 4 Channel | | | | |
| 79 | DS-7104NI-Q1/M | IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity | IRR 20,670,000 |  |
| 80 | DS-7104NI-Q1/4P/M | IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity | call |  |
| 81 | DS-7604NI-Q1 | IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | call |  |
| 82 | DS-7604NI-Q1/4P | IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | call |  |
| 83 | DS-7604NI-K1 | IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | IRR 37,270,000 |  |
| 84 | DS-7604NI-K1/4P | IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | call |  |
| NVR 8 Channel | | | | |
| 89 | DS-7108NI-Q1/M | IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity | IRR 27,180,000 |  |
| 90 | DS-7108NI-Q1/8P/M | IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity | call |  |

| | | | | |
|-----------------------|------------------|---|-----------------|---|
| 94 | DS-7608NI-Q2/8P | IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | call |  |
| 95 | DS-7608NI-K1 | IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | IRR 43,030,000 |  |
| 96 | DS-7608NI-K2/8P | IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | call |  |
| NVR 16 Channel | | | | |
| 98 | DS-7616NI-Q1 | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity | IRR 48,540,000 |  |
| 99 | DS-7616NI-Q2 | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | IRR 52,580,000 |  |
| 100 | DS-7616NI-Q2/16P | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | IRR 93,470,000 |  |
| 101 | DS-7616NI-K2 | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | call |  |
| 102 | DS-7616NI-K2/16P | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk | call |  |
| 103 | DS-7716NI-Q4 | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 108,510,000 |  |
| 104 | DS-7716NI-Q4/16P | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 136,220,000 |  |

| | | | | |
|--|------------------|--|-----------------|---|
| 105 | DS-7716NI-K4 | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | call |  |
| 106 | DS-7716NI-K4/16P | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | call |  |
| Network Video Recorders- Ultra Series | | | | |
| 107 | DS-8616NI-K8 | 16-ch 2U 4K NVR, Up to 16 channel IP cameras can be connected, Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces, 8 HDD can be used for continuous video recording, Supports some specialist cameras, including people counting camera/ANPR | IRR 140,000,000 |  |
| NVR 32 Channel | | | | |
| 108 | DS-7732NI-Q4 | IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 120,890,000 |  |
| 109 | DS-7732NI-Q4/16P | IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 172,640,000 |  |
| 110 | DS-7732NI-K4 | IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 139,060,000 |  |
| 111 | DS-7732NI-K4/16P | IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk | IRR 204,680,000 |  |

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM

Accessories

Items

Description

User Price

Switches

1

DS-3E0105P-E/M

L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af PoE power budget 35W

Call



2

DS-3E0105P-E

L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W

Call



3

DS-3E0109P-E/M

L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af, PoE power budget 60W

Call



4

DS-3E0109P-E

L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W

Call



5

DS-3E0318P-E

L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W

Call



6

DS-3E0326P-E

L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W

Call




7








DS-3E1310P-E









L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W



Call



| | | | | |
|----|-----------------|--|----------------|---|
| 8 | DS-3E1318P-E | <p>802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission,VLAN configurable Port trunk, multicast and port mirroring,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation</p> | Call |  |
| 9 | Cables | | | |
| 10 | DS-1LN6-UE-W | UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE | IRR 46,940,000 |  |
| 11 | DS-1LN6-UU | <p>UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange</p> | IRR 51,660,000 |  |
| 12 | Brackets | | | |
| 13 | DS-1602ZJ | <p>Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx DS-2DF7xxx-DS-2DF5xxx</p> | IRR 6,840,000 |  |
| 14 | DS-1602ZJ-pole | <p>Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p> | Call |  |
| 15 | DS-1605ZJ | <p>Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm</p> | Call |  |
| 16 | DS-1661ZJ | <p>Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: - 116.5×200mm-Weight: -600g</p> | IRR 7,490,000 |  |

| | | | | |
|----|-----------------|---|---------------|---|
| 17 | DS-1662ZJ | Pendant mount , Hik white , Aluminum alloy , Φ 116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx | IRR 8,600,000 |  |
| 18 | DS-1663ZJ | Ceiling mount , Hik white , Aluminum alloy , Φ 116.5×57mm-Suitable for:-DS-2DE/AE4xxx DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx | ناموجود |  |
| 19 | DS-1693ZJ | Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner | Call |  |
| 20 | DS-1681ZJ | Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx | IRR 1,860,000 |  |
| 21 | DS-1273ZJ-135B | Wall mount , White , Aluminum alloy , with junction box , Φ 135×182×120mm Suitable for: DS-2CD27xx | Call |  |
| 22 | Keyboard | | | |
| 23 | DS-1100KI | Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup | Call |  |
| 24 | DS-1005KI | network Keyboard, USB interface, support Hikvision VMS, NVR, DVR | Call |  |
| 25 | Tester | | | |

| | | | | |
|----|-------------------|---|-----------------|---|
| 26 | IPC-4300H | IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI | Call |  |
| 27 | DS-TT-X41T-tester | TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps | IRR 138,420,000 |  |
| 28 | Adapters | | | |
| 29 | AD-121/P | 12V-1A | IRR 420,000 |  |
| 30 | AD-122/P | 12V -2A | IRR 450,000 |  |
| 31 | AD-122/PL | 12V-2A | IRR 480,000 |  |
| 32 | AD-125/PL | 12V -5A | IRR 800,000 |  |
| 33 | AD-12A/M | 12V -10A-METAL | IRR 1,180,000 |  |
| 34 | AD-12F/M | 12V -15A-METAL | IRR 1,600,000 |  |

| | | | | |
|----|-----------|-------------------------|---------------|---|
| 35 | AD-12K/MF | 12V -20A-METAL WITH FAN | IRR 1,840,000 |  |
| 36 | AD-12U/MF | 12V -30A-METAL WITH FAN | IRR 2,550,000 |  |

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه
تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923







ایمیل

Info@Hikvisiontehran.com










CONTACT US

HIKVISIONTEHRAN.COM









Hilook-DVR



| Items | Description | User Price | |
|---------------------|--|---------------|---|
| 1 THC-B110-M | 1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66 | IRR 4,810,000 |  |
| 2 THC-B120-P | 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66 | IRR 6,500,000 |  |
| 3 THC-B120-MS | 2 MP Audio Fixed Mini Bullet Camera Smart IR, up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together | IRR 7,350,000 |  |
| 4 THC-B120-M | 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL | IRR 7,090,000 |  |
| 5 THC-B120-MPIRL | 2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66 | IRR 7,630,000 |  |
| 6 THC-B140-P | 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66 | IRR 7,240,000 |  |








| | | | | |
|----|-------------|---|----------------------|---|
| 7 | THC-B140-M | 4MP high-performance CMOS - 2560 ×1440 resolution- 2.8 mm - fixed focal lens- Day/Night switch - EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal | IRR 7,990,000 |  |
| 8 | THC-B220 | 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66 | IRR 7,590,000 |  |
| 9 | THC-B220C | 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66 | IRR 7,100,000 |  |
| 10 | THC-B220-M | 2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66 , 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal | IRR 8,440,000 |  |
| 11 | THC-B240 | 4MP high-performance CMOS - 2560 ×1440 resolution- 2.8 mm - fixed focal lens- Day/Night switch - EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66 | IRR 9,110,000 |  |
| 12 | THC-B240-M | 4MP CMOS Sensor, EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66 , 2.8/3.6/6mm Lens,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal | IRR 9,940,000 |  |
| 13 | THC-T110-P | 1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case | IRR 3,460,000 |  |
| 14 | THC-T120-PC | 2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC | IRR 4,900,000 |  |
| 15 | THC-T120 | 2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC | IRR 7,400,000 |  |
| 16 | THC-T123 | 2 MP EXIR Turret Camera-performance CMOS- Ultra low light- 1920 × 1080 resolution- 2.8 mm, 3.6 mm, 6 mm fixed lens- Day/Night switch EXIR 2.0, smart IR, up to 30 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) | IRR 6,000,000 |  |






| | | | | |
|----|-------------|--|----------------------|---|
| 17 | THC-T120-MS | <p>2 MP Audio Fixed Turret Camera Smart IR, up to 20 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together</p> | IRR 7,350,000 |  |
| 18 | THC-T120-M | <p>2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL</p> | IRR 6,270,000 |  |
| 19 | THC-T140-P | <p>4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66</p> | IRR 7,340,000 |  |
| 20 | THC-T140 | <p>4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66</p> | IRR 7,400,000 |  |
| 21 | THC-T140-M | <p>4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL</p> | IRR 8,400,000 |  |
| 22 | THC-T220-P | <p>2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm,fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC</p> | IRR 6,580,000 |  |
| 23 | THC-T220-PC | <p>2 MP Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> | IRR 6,380,000 |  |
| 24 | THC-T220-MC | <p>HiLook 2MP EXIR Turret Cam with Fixed Lens 1080p turret camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> | IRR 7,400,000 |  |
| 25 | THC-T220-MS | <p>2 MP Audio Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together</p> | IRR 8,760,000 |  |
| 26 | THC-T220-M | <p>2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm,fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL</p> | IRR 7,710,000 |  |

| | | | | |
|----------------------------|-------------|---|-----------------------|---|
| 27 | THC-T240-P | 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66 | IRR 8,740,000 |  |
| 28 | THC-T240-M | 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL | IRR 9,900,000 |  |
| Vari-Focal Series | | | | |
| 29 | THC-B320-VF | 2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,, DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal | IRR 15,200,000 |  |
| 30 | THC-B340-VF | 4MP CMOS Sensor - 2.8-12mm Vari Focal Lens , EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66 , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal | IRR 16,780,000 |  |
| 31 | THC-D320-VF | 2MP CMOS Sensor, 40m IR , EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens --support HD-TVI/AHD/CVI/CVBS video output-,IK10-Full Metal | IRR 14,900,000 |  |
| 32 | THC-D340-VF | 4MP CMOS Sensor, EXIR Dome, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens ,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal | IRR 16,110,000 |  |
| 33 | THC-T320 VF | 2MP CMOS Sensor, 40m IR , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal | IRR 13,780,000 |  |
| 34 | THC-T340-VF | 4MP CMOS Sensor, EXIR Eyeball, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal | IRR 15,070,000 |  |
| Turbo HD PTZ Camera | | | | |

| | | | | |
|----------------------|--------------|---|----------------|---|
| 35 | PTZ-T4225I-D | 1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 5× optical zoom, 16× digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs | IRR 71,040,000 |  |
| 36 | PTZ-T4215I-D | 1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 5× optical zoom, 16× digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs | call |  |
| 37 | PTZ-T5225I-A | 1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs | call |  |
| DVR 4 Channel | | | | |
| 38 | DVR-104G-F1 | 4-ch 1080p Mini 1U Lite H.264 DVR,5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback. | IRR 8,830,000 |  |
| 39 | DVR-204G-F1 | Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 1-ch Up to 960P resolution), 1 SATA (6TB) interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- HDMI output HD1080p-Metal | IRR 11,120,000 |  |
| 40 | DVR-204Q-F1 | Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920×1080P: 12 fps/ch, 260 1U case-- HDMI outputHD1080p-Metal | IRR 12,370,000 |  |
| 41 | DVR-204Q-K1 | H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed. | IRR 15,490,000 |  |
| 42 | DVR-204U-F1 | Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch IP video input(up to 6MP resolution) , 1 SATA (6 TB) - interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-- HDMI output HD1080p-Metal | IRR 19,020,000 |  |

| | | | | |
|----------------------|-------------|---|----------------|---|
| 43 | DVR-204U-K1 | <p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input</p> <p>I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1</p> <p>I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1</p> <p>I Defogging function enabled for the supported analog cameras</p> <p>I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal</p> | IRR 22,170,000 |  |
| DVR 8 Channel | | | | |
| 44 | DVR-108G-F1 | <p>8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP), Long distance transmission over UTP and coaxial cable, H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, Encoding ability up to 1080p lite @ 12 fps, One HDD for continuous video recording, Smart search for efficient playback.</p> | IRR 15,050,000 |  |
| 45 | DVR-208G-F1 | <p>Recording Capability HD1080p Lite</p> <p>8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p> | IRR 18,380,000 |  |
| 46 | DVR-208Q-F1 | <p>Recording Capability 3MP</p> <p>8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal</p> | IRR 30,700,000 |  |
| 47 | DVR-208Q-K1 | <p>Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable</p> <p>One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite.</p> <p>Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).</p> | IRR 27,070,000 |  |
| 48 | DVR-208Q-K2 | <p>8-ch 1080p 1U H.265 DVR-5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP)-Long distance transmission over UTP and coaxial cable-H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs-Supports 4 MP lite, and when enabled the image effect is similar with 4 MP-Encoding ability up to 1080p lite @ 15 fps-Two HDDs for continuous video recording Smart search for efficient playback.</p> | IRR 32,000,000 |  |
| 49 | DVR-208U-F1 | <p>Recording Capability 5MP/3MP</p> <p>8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB) interface, 5MP@12fps, 4MP@15fps, 3MP@18fps, 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output 4K-Metal</p> | IRR 38,140,000 |  |

| | | | | |
|-------------------------------|-------------|--|----------------|---|
| 50 | DVR-208U-K1 | 8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible | IRR 41,080,000 |  |
| Digital Video Recorder | | | | |
| 51 | DVR-116G-F1 | 16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback. | IRR 21,000,000 |  |
| 52 | DVR-216G-F1 | Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal | IRR 26,570,000 |  |
| 53 | DVR-216G-K1 | Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal | IRR 26,570,000 |  |
| 54 | DVR-216Q-F1 | Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal | IRR 37,620,000 |  |
| 55 | DVR-216Q-F2 | Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 2 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal | call |  |
| 56 | DVR-216Q-K1 | One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite | IRR 46,440,000 |  |

| | | | | |
|----|-------------|--|-----------------------|---|
| 57 | DVR-216Q-K2 | <p>One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite</p> | IRR 48,820,000 |  |
| 58 | DVR-216U-F2 | <p>Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-</p> | IRR 72,210,000 |  |
| 59 | DVR-216U-K2 | <p>DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD – CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording</p> | IRR 81,300,000 |  |
| 60 | DVR-232G-K2 | <p>32-ch 1080p Lite 1U H.265 DVR, transmission over UTP and coaxial cable H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, and when enabled the image effect is similar with 1080pEncoding ability up to 1080p lite @ 12 fps, 2HDDs for continuous video recording</p> | IRR 72,920,000 |  |
| 61 | DVR-232Q-K2 | <p>32-ch 1080p 1U H.265 DVR 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs, Supports 4 MP lite, and when enabled the image effect is similar with 4 MP,Encoding ability up to 1080p lite @ 15 fps 2 HDDs for continuous video recording</p> | IRR 91,580,000 |  |

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویزن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923







ایمیل











Info@Hikvisiontehran.com










CONTACT US









HIKVISIONTEHRAN.COM








**Hilook-NVR**











| Items | Description | User Price | |
|-------|--|----------------|---|
| 1 | IPC-B120 1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR | IRR 14,280,000 |  |
| 2 | IPC-B120-D/W 2 MP Outdoor Fixed Bullet Network Camera with Build-in Mic High quality imaging with 2 MP resolution Efficient H.264 compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology Built-in microphone for real-time audio security Wireless connection for convenient installation and use | IRR 13,570,000 |  |
| 3 | IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens BLC, DC12V & PoE, up to 30m IR-Support mobile monitoring via Hik-Connc *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67 | IRR 15,050,000 |  |
| 4 | IPC-B121H 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265 | IRR 15,050,000 |  |
| 5 | IPC-B121H-M 2 MP Fixed Bullet Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology, (IP67) EXIR 2.0: advanced infrared technology with long IR range | IRR 15,850,000 |  |
| 6 | IPC-B140H 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connc *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67 | IRR 18,610,000 |  |





| | | | | |
|----|-------------|--|----------------|---|
| 7 | IPC-B140H-M | 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens , Support mobile monitoring via Hik-up to 30m IR , Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67 | IRR 20,360,000 |  |
| 8 | IPC-B150H-M | High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology | IRR 22,620,000 |  |
| 9 | IPC-B220 | 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application | IRR 16,240,000 |  |
| 10 | IPC-B220-D | 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply | IRR 15,520,000 |  |
| 11 | IPC-T120 | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), DWDR -H.264+&H.264- ,2.8/4/6mm fixed lens- BLC, - DC12V & PoE, -up to 10m IR - Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67 | IRR 14,900,000 |  |
| 12 | IPC-T120-D | 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream- DWDR -3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application- IP 67 - D model only support 12VDC power supply | IRR 14,170,000 |  |
| 13 | IPC-T220-H | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE, -up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67 | IRR 17,190,000 |  |
| 14 | IPC-T221-H | 2 MP Fixed Turret Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against ,strong back light by DWDR technology Water and dust resistant (IP67) (PoE) technology | IRR 17,210,000 |  |
| 15 | IPC-T220 | 1/2.8" progressive scan CMOS BLC/3D DNR, 1920 x 1080@30fps, IP67 2.8, 4, 6 mm fixed lens, Digital WDR, H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON); | IRR 16,980,000 |  |
| 16 | IPC-T240H | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR - 3D DNR-DWDR, BLC, DC12V & PoE- 2.8/4/6mm fixed lens ,--Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67 | IRR 21,360,000 |  |
| 17 | IPC-D120 | 1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67- Digital WDR -IK 10 | IRR 15,600,000 |  |

| | | | | |
|--------------------------|-------------|--|----------------|---|
| 18 | IPC-D120H | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, --2.8/4/6mm fixed lens- BLC, DC12V & PoE, DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10 | IRR 16,040,000 |  |
| 19 | IPC-D121H | 2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology | IRR 15,930,000 |  |
| 20 | IPC-D121H-M | 2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology-METAL CASE | IRR 17,540,000 |  |
| 21 | IPC-D140H | 4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR. | IRR 19,780,000 |  |
| 22 | IPC-D150H | High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology | IRR 19,940,000 |  |
| Vari-Focal Series | | | | |
| 23 | IPC-B620H-V | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 33,050,000 |  |
| 24 | IPC-B620H-Z | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 37,550,000 |  |
| 25 | IPC-B621-V | 2 MP Varifocal Bullet Network Camera Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology(IP66) -V: model with manual vari-focal lens Built-in microphone enhances safety with video/audio in tandem | IRR 31,980,000 |  |
| 26 | IPC-B621-Z | 2 MP Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light due to DWDR technology(IP66) -Z: model with motorized vari-focal lens Built-in microphone enhances safety with video/audio in tandem | IRR 36,410,000 |  |

| | | | | |
|---|----------------|--|-----------------|---|
| 27 | IPC-B640H-V | 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic--IP67 | IRR 36,560,000 |  |
| 28 | IPC-B640H-Z | 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot,-WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67 | IRR 39,160,000 |  |
| 29 | IPC-T620-Z | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67 | IRR 33,620,000 |  |
| 30 | IPC-D620H-V | 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10 | IRR 32,090,000 |  |
| 31 | IPC-D620H-Z | 1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10 | IRR 35,900,000 |  |
| 32 | IPC-D640H-V | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10 | IRR 35,380,000 |  |
| 33 | IPC-D640H-Z | 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10 | IRR 38,060,000 |  |
| PanoVu Mini Series IR Network PTZ Camera | | | | |
| 34 | PTZ-P332ZI-DE3 | System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkagel Up to 10 m IR radius Panoramic Cameral Three 1/2.8" progressive scan CMOSI 3-ch 1920 × 1080@30fps resolutionI Horizontal FOV: 128.5° × 3 PTZ Cameral 1/2.8" progressive scan CMOSI Up to 1920 × 1080@30fps resolutionI 4× optical zoom, 8× digital zoom | IRR 159,000,000 |  |
| IP PTZ Camera | | | | |

| | | | | |
|-------------------------------|----------------|--|----------------|---|
| 35 | PTZ-N4215-DE3 | <p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p> | IRR 72,810,000 |  |
| 36 | PTZ-N4215I-DE | <p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p> | IRR 77,880,000 |  |
| 37 | PTZ-N4225I-DE | <p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 25× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p> | IRR 94,590,000 |  |
| 38 | PTZ-N2404I-DE3 | <p>Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10)</p> | IRR 50,020,000 |  |
| Network Video Recorder | | | | |
| 39 | NVR-104-B | <p>Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p</p> | IRR 9,810,000 |  |
| 40 | NVR-108-B | <p>Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p</p> | IRR 12,030,000 |  |
| 41 | NVR-108-B/8p | <p>4-ch Mini 1U 4 PoE 4K NVR, Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Supports decoding H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording</p> | IRR 30,490,000 |  |

| | | | | |
|----|-----------------------|---|-----------------------|---|
| 42 | NVR-104H-D | 4-ch Mini 1U 4 PoE NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output | IRR 10,400,000 |  |
| 43 | NVR-108H-D | 4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 8-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output | IRR 13,610,000 |  |
| 44 | NVR-104MH-C | Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB) interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p | IRR 15,590,000 |  |
| 45 | NVR-104MH-D | Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording. | IRR 12,510,000 |  |
| 46 | NVR-104MH-D/4P | Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording | IRR 21,660,000 |  |
| 47 | NVR-104MH-C/4P | Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P | IRR 22,860,000 |  |
| 48 | NVR-108MH-C | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K, Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p | IRR 20,970,000 |  |
| 49 | NVR-108MH-D | IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing, bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface, Capacity Up to 6TB capacity for each disk, | IRR 16,800,000 |  |
| 50 | NVR-208MH-C | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K, Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p | IRR 22,820,000 |  |
| 51 | NVR-108MH-C/8P | Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB), 8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p | IRR 53,500,000 |  |

| | | | | |
|----|-----------------|---|-----------------------|---|
| 52 | NVR-108MH-D/8P | IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk, | IRR 47,520,000 |  |
| 53 | NVR-116MH-C | Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p | IRR 24,530,000 |  |
| 54 | NVR-216MH-C | Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p | IRR 29,190,000 |  |
| 55 | NVR-216MH-C/16P | Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, -Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p | IRR 62,680,000 |  |

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM

Hard Disk

Items

Description

User Price

Surveillance HDD



Purple

1

WD10PURX-WD Purple 1TB

Capacity 1TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB

CALL



2

WD20PURX-WD Purple 2TB

Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB

CALL



3







WD30PURX-WD Purple 3TB









Capacity 3TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB









CALL









| | | | | |
|----|-------------------------------------|--|--|---|
| 4 | WD40PURX-WD Purple 4TB | Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB | CALL |  |
| 5 | WD60PURX-WD Purple 6TB | Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB | CALL |  |
| 6 | WD82PURX-WD Purple 8TB | Capacity 8TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 256MB | CALL |  |
| 7 | WD101PURX-WD Purple 10TB | | CALL |  |
| 8 | WD121PURX-WD Purple 12TB | | CALL |  |
| 11 | Surveillance HDD |  SEAGATE |  SKYHAWK SURVEILLANCE | |
| 12 | ST2000VX - Seagate Surveillance 2TB | Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB | CALL |  |

| | | | | |
|----|---------------------------------------|--|------|---|
| 13 | ST3000VX - Seagate Surveillance 3TB | | CALL |  |
| 14 | ST4000VX - Seagate Surveillance 4TB | Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB | CALL |  |
| 15 | ST6000VX - Seagate Surveillance 6TB | Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 7200 - Cache 256MB | CALL |  |
| 16 | ST8000VX - Seagate Surveillance 8TB | | CALL |  |
| 17 | ST10000VX - Seagate Surveillance 10TB | | CALL |  |
| 18 | ST12000VX - Seagate Surveillance 12TB | | CALL |  |

| | | | | |
|----|---------------------------------------|--|---|---|
| 19 | ST14000VX - Seagate Surveillance 14TB | | CALL |  |
| 20 | NAS HDD |  SEAGATE |  IRONWOLF NAS | |
| 21 | ST2000VN - Seagate Iron Wolf 2TB | | CALL |  |
| 22 | ST3000VN - Seagate Iron Wolf 3TB | | CALL |  |
| 23 | ST4000VN - Seagate Iron Wolf 4TB | | CALL |  |
| 24 | ST6000VN - Seagate Iron Wolf 6TB | | CALL |  |
| 25 | ST8000VN - Seagate Iron Wolf 8TB | | CALL |  |

| | | | | |
|----|-----------------------------------|--|---|---|
| 26 | ST1000VN - Seagate Iron Wolf 10TB | | CALL |  |
| 27 | ST1200VN - Seagate Iron Wolf 12TB | | CALL |  |
| 28 | ST1400VN - Seagate Iron Wolf 14TB | | CALL |  |
| 29 | Enterprise HDD |  |  | |
| 30 | ST2000NM - Seagate EXOS 2TB | | CALL |  |
| 31 | ST3000NM - Seagate EXOS 3TB | | CALL |  |
| 32 | ST4000NM - Seagate EXOS 4TB | | CALL |  |

| | | | | |
|----|-------------------------------|--|------|---|
| 33 | ST6000NM - Seagate EXOS 6TB | | CALL |  |
| 34 | ST8000NM - Seagate EXOS 8TB | | CALL |  |
| 35 | ST10000NM - Seagate EXOS 10TB | | CALL |  |
| 36 | ST12000NM - Seagate EXOS 12TB | | CALL |  |
| 37 | ST14000NM - Seagate EXOS 14TB | | CALL |  |
| 38 | ST16000NM - Seagate EXOS 16TB | | CALL |  |



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه
تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM

Equip Rack

| Items | Description | User Price |
|------------------------------|---|-------------|
| ER Standing Rack IP42 | | |
| 1 | ERS - 4761 رک ۴۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو و درب عقب مشبک | ۱۲۸,۸۰۰,۰۰۰ |
| 2 | ERS - 4461 رک ۴۴ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو و درب عقب مشبک | ۱۲۶,۲۰۰,۰۰۰ |
| 3 | ERS - 4281 رک ۴۲ یونیت-عمق ۱۰۰-عرض ۸۰ - درب جلو مشبک، درب پشت ۲ لنگه مشبک | ۱۴۹,۸۰۰,۰۰۰ |
| 4 | ERS - 4261 رک ۴۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۹۹,۶۰۰,۰۰۰ |
| 5 | ERS - 4268 رک ۴۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۸۸,۹۰۰,۰۰۰ |
| 6 | ERS - 4266 رک ۴۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۹,۹۵۰,۰۰۰ |
| 7 | ERS - 3761 رک ۳۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۸۹,۰۰۰,۰۰۰ |
| 8 | ERS - 3768 رک ۳۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۸,۹۵۰,۰۰۰ |

| | | | |
|----|------------|---|------------|
| 9 | ERS - 3766 | رک ۳۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۲,۸۰۰,۰۰۰ |
| 10 | ERS - 3261 | رک ۳۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۹,۵۰۰,۰۰۰ |
| 11 | ERS - 3268 | رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۲,۵۰۰,۰۰۰ |
| 12 | ERS - 3266 | رک ۳۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۶۵,۹۵۰,۰۰۰ |
| 13 | ERS - 2761 | رک ۲۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۷۴,۵۰۰,۰۰۰ |
| 14 | ERS - 2768 | رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۶۵,۳۰۰,۰۰۰ |
| 15 | ERS - 2766 | رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۵۹,۸۰۰,۰۰۰ |
| 16 | ERS - 2261 | رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۶۴,۳۰۰,۰۰۰ |
| 17 | ERS - 2168 | رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۵۷,۹۵۰,۰۰۰ |
| 18 | ERS - 2266 | رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۵۳,۵۰۰,۰۰۰ |
| 19 | ERS - 1868 | رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۵۲,۸۰۰,۰۰۰ |
| 20 | ERS-1866 | رک ۱۸ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۴۸,۸۰۰,۰۰۰ |
| 21 | ERS-1468 | رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۴۶,۵۰۰,۰۰۰ |

| | | | |
|----|-----------------|--|------------|
| 22 | ERS-1466 | رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی | ۴۱,۰۰۰,۰۰۰ |
| 23 | ER Wall Mount | | |
| 24 | ERW - 1266 | رک دیواری - ۱۲ یونیت-عمق ۶۰، عرض ۶۰ | ۱۷,۹۹۰,۰۰۰ |
| 25 | ERW - 0966 | رک دیواری - ۹ یونیت-عمق ۶۰، عرض ۶۰ | ۱۶,۵۰۰,۰۰۰ |
| 26 | ERW - 0964 | رک دیواری - ۹ یونیت-عمق ۴۵، عرض ۶۰ | ۱۲,۸۰۰,۰۰۰ |
| 27 | ERW - 0666 | رک دیواری - ۶ یونیت-عمق ۶۰، عرض ۶۰ | ۱۱,۵۰۰,۰۰۰ |
| 28 | ERW - 0663 | رک دیواری - ۶ یونیت-عمق ۳۳، عرض ۶۰ | ۸,۹۸۰,۰۰۰ |
| 29 | ERW - 0764 | رک دیواری - ۷ یونیت-عمق ۴۵، عرض ۶۰ | ۱۱,۹۸۰,۰۰۰ |
| 30 | ERW - 0366 | رک دیواری - ۳ یونیت-عمق ۶۰، عرض ۶۰ (تاشو) | ۱۶,۵۰۰,۰۰۰ |
| 31 | ER OUTDOOR RACK | | |
| 32 | ERO - 0745 | OUTDOOR رک ۷ یونیت -عمق ۴۵ | ۵۱,۵۰۰,۰۰۰ |
| 33 | ERO - 0966 | OUTDOOR رک ۹ یونیت -عمق ۶۰ | ۵۹,۸۵۰,۰۰۰ |
| 34 | ERO - 1266 | OUTDOOR رک ۱۲ یونیت -عمق ۶۰ | ۷۹,۹۰۰,۰۰۰ |
| 35 | ERO - 1866 | OUTDOOR رک ۱۸ یونیت -عمق ۸۰ | ۸۹,۹۰۰,۰۰۰ |
| 36 | ER MAIN FRAME | | |
| 37 | ERM - 4202 | رک ۴۲ یونیت - آزمایشگاهی - چهار ستون | C ALL |
| 38 | ERM - 4201 | رک ۴۲ یونیت - آزمایشگاهی - دو ستون | C ALL |
| 39 | ERM - 3202 | رک ۳۲ یونیت - آزمایشگاهی - چهار ستون | C ALL |
| 40 | Shelf | | |
| 41 | ERA - SSW | طبقه ثابت رک های دیواری عمق ۳۳ | ۹۶۰,۰۰۰ |

| | | | |
|----|----------------|--|------------|
| 42 | ERA - SSW | طبقه ثابت رک های دیواری عمق ۴۵ | ۱,۴۸۰,۰۰۰ |
| 43 | ERA - SSW | طبقه ثابت رک های دیواری عمق ۶۰ | ۱,۹۰۰,۰۰۰ |
| 44 | ERA - SS 60 | طبقه ثابت رک ، ۶۰ سانتیمتر | ۲,۲۲۰,۰۰۰ |
| 45 | ERA - SS 80 | طبقه ثابت رک ، ۸۰ سانتیمتر | ۳,۱۰۰,۰۰۰ |
| 46 | ERA - SS 10 | طبقه ثابت رک ، ۱۰۰ سانتیمتر | ۳,۹۷۰,۰۰۰ |
| 47 | ERA - SM 60 | سینی متحرک رک ۶۰ سانتیمتر | ۶,۹۰۰,۰۰۰ |
| 48 | ERA - SM 80 | سینی متحرک رک ۸۰ سانتیمتر | ۶,۹۰۰,۰۰۰ |
| 49 | ERA - SM 10 | سینی متحرک رک ۱۰۰ سانتیمتر | ۶,۹۰۰,۰۰۰ |
| 50 | Power Module | | |
| 51 | PMM - 08 | پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت | ۱,۷۲۰,۰۰۰ |
| 52 | PMM - 03 | پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت | ۸۷۰,۰۰۰ |
| 53 | Accessories | | |
| 54 | ERA - LI - 10 | لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات | ۲,۶۰۰,۰۰۰ |
| 55 | ERA - SCR - 20 | پیچ و کژنات مخصوص رک بسته ۵۰ تایی | ۷۸۰,۰۰۰ |
| 56 | ERA - TR - 20 | حرارت سنج یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان | ۱۵,۰۰۰,۰۰۰ |
| 57 | ERA - FN - 20 | فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر | ۱,۴۵۰,۰۰۰ |
| 58 | ERA - CM - 10 | نگهدارنده افقی کابل ۱۹ اینچ | ۱,۲۰۰,۰۰۰ |
| 59 | ERA - CM - 20 | نگهدارنده عمودی کابل | ۱۶۵,۰۰۰ |
| 60 | ERA - CM - 30 | نگهدارنده کابل درپوش دار | ۶۷۰,۰۰۰ |
| 61 | ERA - SL - 10 | قفل سوئیچی درب رک های دیواری و پنل های جانبی | ۷۰۰,۰۰۰ |
| 62 | Blank Panel | | |

| | | | |
|--|----------------|---|------------|
| 63 | ERA - BLA - 10 | بلانک پنل ، ۱ یونیت | ۴۲۰,۰۰۰ |
| 64 | ERA - BLA - 20 | بلانک پنل ، ۲ یونیت | ۵۲۰,۰۰۰ |
| 65 | ERA - BLA - 30 | بلانک پنل ، ۳ یونیت | ۶۷۰,۰۰۰ |
| 66 | ERA - BLA - 40 | بلانک پنل ، ۴ یونیت | ۸۷۰,۰۰۰ |
| 67 | ERA - BLA - 50 | بلانک پنل ، ۱ یونیت فرچه ای | ۸۷۰,۰۰۰ |
| 68 | Doors | | |
| 69 | EDM - 0000 | درب مشبک (جلو) جهت رک های ۲۷-۲۲-۳۷-۴۴-۴۲-۴۷ | ۱۸,۰۰۰,۰۰۰ |
| 70 | EDM - 0001 | درب مشبک (عقب) جهت رک های ۲۷-۲۲-۳۷-۴۴-۴۲-۴۷ | ۱۰,۵۰۰,۰۰۰ |
| 71 | EDM - 0002 | درب مشبک دو لنگه با قفل ریتال جهت رک های ۴۲-۴۴-۴۷ | ۲۰,۵۰۰,۰۰۰ |
| لازم به ذکر است درب مشبک شامل تخفیف نمی گردد | | | |

| Rack | | |
|-----------------------|---|------------|
| Items | Description | User Price |
| ER Standing Rack IP42 | | |
| NRS-4261 | رک ۴۲ یونیت-عمق ۱۰۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۶۴,۹۰۰,۰۰۰ |
| NRS-4268 | رک ۴۲ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۵۹,۳۰۰,۰۰۰ |
| NRS-3261 | رک ۳۲ یونیت-عمق ۱۰۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۵۶,۴۵۰,۰۰۰ |
| 1 NRS - 3268 | رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۵۲,۵۰۰,۰۰۰ |
| 2 NRS - 2768 | رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۵۱,۰۰۰,۰۰۰ |
| 3 NRS - 2766 | رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۴۶,۹۰۰,۰۰۰ |
| 4 NRS - 2261 | رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۴۴,۰۰۰,۰۰۰ |
| 5 NRS - 2168 | رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۴۰,۵۰۰,۰۰۰ |
| 6 NRS - 2266 | رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۲۲,۰۰۰,۰۰۰ |
| 7 NRS-1866 | رک ۱۸ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ | ۱۹,۶۰۰,۰۰۰ |
| ER Wall Mount | | |
| 9 NRW - 1266 | رک دیواری - ۱۲ یونیت - عمق ۶۰ ، عرض ۶۰ | ۱۳,۰۰۰,۰۰۰ |
| 10 NRW - 0966 | رک دیواری - ۹ یونیت - عمق ۶۰ ، عرض ۶۰ | ۹,۵۰۰,۰۰۰ |
| 11 NRW - 0964 | رک دیواری - ۹ یونیت - عمق ۴۵ ، عرض ۶۰ | ۹,۰۰۰,۰۰۰ |
| 12 NRW - 0766 | رک دیواری - ۷ یونیت - عمق ۶۰ ، عرض ۶۰ | ۸,۴۰۰,۰۰۰ |
| 13 NRW - 0764 | رک دیواری - ۷ یونیت - عمق ۴۵ ، عرض ۶۰ | ۶,۹۰۰,۰۰۰ |
| 14 NRW - 0664 | رک دیواری - ۶ یونیت - عمق ۴۵ ، عرض ۶۰ | ۵,۳۰۰,۰۰۰ |
| 15 NRW - 0445 | رک دیواری - ۴ یونیت - عمق ۴۵ ، عرض ۶۰ | ۴,۹۵۰,۰۰۰ |
| 16 NRW - 0446 | رک دیواری - ۴ یونیت - عمق ۴۰ | ۳,۲۰۰,۰۰۰ |
| 17 | Shelf | |

| | | | |
|----|----------------|--|------------|
| 18 | NRA - SSW | طبقه ثابت رک های دیواری عمق ۴۵ | ۷۵۰,۰۰۰ |
| 19 | NRA - SSW | طبقه ثابت رک های دیواری عمق ۶۰ | ۸۷۰,۰۰۰ |
| 20 | NRA - SS 60 | طبقه ثابت رک ، ۶۰ سانتیمتر | ۱,۶۰۰,۰۰۰ |
| 21 | NRA - SS 80 | طبقه ثابت رک ، ۸۰ سانتیمتر | ۱,۹۰۰,۰۰۰ |
| 22 | NRA - SS 10 | طبقه ثابت رک ، ۱۰۰ سانتیمتر | ۲,۴۰۰,۰۰۰ |
| 23 | NRA - SSU | سینی ثابت دو یونیت | ۲,۲۰۰,۰۰۰ |
| 24 | Power Module | | |
| 25 | PMM - 08 | پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت | ۱,۷۲۰,۰۰۰ |
| 26 | PMM - 03 | پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت | ۸۷۰,۰۰۰ |
| 27 | Accessories | | |
| 28 | ERA - LI - 10 | لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات | ۲,۶۰۰,۰۰۰ |
| 29 | ERA - SCR - 20 | پیچ و کزنات مخصوص رک بسته ۵۰ تایی | ۷۸۰,۰۰۰ |
| 30 | ERA - TR - 20 | حرارت سنچ یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان | ۱۵,۰۰۰,۰۰۰ |
| 31 | ERA - FN - 20 | فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر | ۱,۴۵۰,۰۰۰ |
| 32 | ERA - CM - 10 | نگهدارنده افقی کابل ۱۹ اینچ | ۱,۲۰۰,۰۰۰ |
| 33 | ERA - CM - 20 | نگهدارنده عمودی کابل | ۱۶۵,۰۰۰ |
| 34 | ERA - CM - 30 | نگهدارنده کابل درپوش دار | ۶۷۰,۰۰۰ |
| 35 | ERA - SL - 10 | قفل سوئیچی درب رک های دیواری و پنل های جانبی | ۷۰۰,۰۰۰ |
| 36 | Blank Panel | | |
| 37 | ERA - BLA - 10 | بلانک پنل ، ۱ یونیت | ۴۲۰,۰۰۰ |
| 38 | ERA - BLA - 20 | بلانک پنل ، ۲ یونیت | ۵۲۰,۰۰۰ |
| 39 | ERA - BLA - 30 | بلانک پنل ، ۳ یونیت | ۶۷۰,۰۰۰ |
| 40 | ERA - BLA - 40 | بلانک پنل ، ۴ یونیت | ۸۷۰,۰۰۰ |
| 41 | ERA - BLA - 50 | بلانک پنل ، ۱ یونیت فرچه ای | ۸۷۰,۰۰۰ |

