

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس




09906500074-66765968-66765923









ایمیل








Info@Hikvisiontehran.com








CONTACT US
HIKVISIONTEHRAN.COM








Turbo HD Camera - DVR








Items	Description	User Price	
Turbo HD - 1MP			
1	DS-2CE16C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 6,160,000	
2	DS-2CE56C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 5,410,000	
3	DS-2CE56C0T-IRPF 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS	IRR 5,820,000	
Turbo HD - 2MP			







5	DS-2CE16D0T-IF	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	ناموجود	
6	DS-2CE16D0T-IRF	2 MP Fixed Mini Bullet Camera 2 MP bullet camera Smart IR: up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);	IRR 9,500,000	
7	DS-2CE16D0T-ITFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 10,180,000	
8	DS-2CE16D0T-IT3	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens - IP66 weatherproof	IRR 12,310,000	
9	DS-2CE16D0T-VFIR3F	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 20,210,000	
10	DS-2CE56D0T-IPF	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - True Day/Night, Smart IR	ناموجود	
11	DS-2CE76D0T-ITPF	2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 7,870,000	
12	DS-2CE76D0T-ITMF	2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 9,600,000	







13	DS-2CE76D0T-ITMFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 10,180,000	
14	DS-2CE56D0T-VFIR3F	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 15,600,000	
15	Turbo HD - 2MP built-in PoC			
16	DS-2CE16D0T-IRE	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 10,810,000	
17	DS-2CE16D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu. IP66, 2.8/3.6/6mm Lens	ناموجود	
18	DS-2CE56D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 9,950,000	
19	DS-2CE56D0T-IT3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 13,720,000	
20	Turbo HD - 2MP - Starlight Value Series			
21	DS-2CE16D3T-I3F	2 MP high-performance CMOS .Ultra low light . 1920 × 1080 resolution . 2.8 mm, 3.6 mm, 6 mm fixed lens .Smart IR, up to 30 m IR distance . OSD menu, 3D DNR, 120 dB true WDR , day/night switch .4 in 1 video output (switchable TVI/AHD/CVI/CVBS) .IP67.Up the coax (HIKVISION-C)	IRR 11,180,000	








22	DS-2CE56D8T-ITME	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 16,630,000	
23	DS-2CE56D8T-IT1E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ built-in PoC , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	IRR 17,460,000	
24	Turbo HD - 3MP			
25	DS-2CE56F1T-IT3	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 12,940,000	
26	DS-2CE56F7T-IT3Z	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized varifocal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 33,260,000	
27	Turbo HD - 5MP			
28	DS-2CE16H0T-ITF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 11,600,000	
29	DS-2CE16H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,120,000	
30	DS-2CE16H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,580,000	







31	DS-2CE16H0T-IT5F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 17,880,000	
32	DS-2CE16H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 28,690,000	
33	DS-2CE76H0T-ITMF	5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 11,380,000	
34	DS-2CE76H0T-ITMFS	5 MP coaxial audio camera , Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 12,500,000	
35	DS-2CE56H0T-ITMF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 12,890,000	
36	DS-2CE56H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 11,690,000	
37	DS-2CE56H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 16,250,000	

38	DS-2CE56H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 21,490,000	
39	Turbo HD - 5MP - built-in PoC			
40	DS-2CE56H1T-ITME	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 14,200,000	
41	DS-2CE56H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 19,960,000	
42	DS-2CE56H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 21,620,000	
43	DS-2CE56H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	ناموجود	
44	DS-2CC52H1T-FITS	5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, Built-in microphone, 1-ch audio output	ناموجود	
45	TURBO HD 5MP (TURBO HD 5.0) PIR Series			
46	DS-2CE11H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 14,550,000	

47	DS-2CE12H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 15,800,000	
48	DS-2CE71H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 14,550,000	
49	Turbo HD - 8MP			
50	DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 24,840,000	
51	DS-2CE18U8T-IT3	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 26,360,000	
52	Turbo HD PTZ Camera			
53	DS-2AE4225TI-D	High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology -Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 × optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66)	IRR 105,330,000	
54	DS-2AE5223TI-A (24VAC)	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	ناموجود	

55	DS-2AE7230TI-A (24VAC)	High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30× optical zoom, focal length 4-120mm - 16× digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	IRR 212,830,000	
56	Turbo HD DVR 720p / 1080p lite			
57	DS-7208HGHI-F1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u> : 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> 2-ch (up to 10-ch) Up to 2 MP resolution - Support H.264+/H.264 IP cameras - <u>Audio input</u> 1-ch - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	IRR 26,300,000	
58	DS-7216HGHI-K1	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 1080p lite/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u> : 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 29,490,000	
59	Turbo HD DVR 1080p / 3MP / 4MP lite			
60	DS-7204HQHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 26,620,000	
61	DS-7208HQHI-K1/Eco	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - ECO CASE	IRR 38,020,000	
62	DS-7208HQHI-K1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 40,140,000	

63	DS-7116HQHI-K1	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	IRR 46,070,000	
64	7216HQHI-K1-Eco	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - ECO CASE	IRR 65,460,000	
65	DS-7216HQHI-K1	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 61,800,000	
66	DS-7216HQHI-K2	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 67,610,000	
67	DS-7224HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 32-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	ناموجود	
68	DS-7232HQHI-K2	<u>Analog video input</u> 32-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 118,210,000	
69	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite			
70	DS-7204HUHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 42,840,000	

71	DS-7208HUHI-K1	Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> :8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 61,260,000	
72	DS-7216HUHI-K2	Analog video input 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 116,500,000	
73	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)			
74	DS-7204HUHI-K1/P	Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 × 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable	IRR 47,050,000	
75	DS-7208HUHI-K2/P	Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	IRR 87,770,000	
76	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			
77	DS-7204HTHI-K1	Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 8 MP resolution - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 49,890,000	
78	DS-7208HTHI-K2	Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 96,990,000	



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM





Network Camera - NVR









Items

Description









User Price








Lite Mini Bullet Series









	Items	Description	User Price	
1	DS-2CV1021G0-IDW1	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in WIFI	IRR 19,280,000	
2	DS-2CD1023G0E-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 18,180,000	
3	DS-2CD1023G0-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 22,170,000	
4	DS-2CD1023G0-IU	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in microphone	IRR 19,700,000	









5	DS-2CD1043G0E-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 23,840,000	
6	DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 24,330,000	
7	Lite Dome Series			
8	DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	ناموجود	
9	DS-2CD1323G0E-IU	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone	IRR 19,950,000	
10	DS-2CD1123G0E-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 19,480,000	
11	DS-2CD1123G0-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	IRR 25,870,000	
12	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 26,770,000	
13	Mini Bullet Series			
14	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m	ناموجود	









15	DS-2CD2023G0-I	2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 37,740,000	
16	DS-2CD2043G0-ICKV	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 33,330,000	
17	DS-2CD2043G0-I	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 35,490,000	
18	DS-2CD2043G0-I (Black)	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 40,710,000	
19	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m	IRR 41,420,000	
20	DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 48,340,000	
21	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 56,820,000	
22	Dome Series			
23	DS-2CD2123G0-IS	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	IRR 40,710,000	







24	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 44,100,000	
25	DS-2CD2143G0-ISCKV	4 MP Outdoor WDR Fixed Dome Network Camera-1/3" Progressive Scan CMOS 2560 × 1440@25fps- 2.8/4 mm fixed lens-Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @(F2.0, AGC ON);- H.265+, H.265, H.264+, H.264-120 dB WDR - 2 Behavior analyses-BLC/3D DNR/ROIBuilt-in micro SD/micro SDHC/micro SDXC-card slot, up to 128 GB	IRR 33,330,000	
26	DS-2CD2143G0-IS (Black)	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 44,720,000	
27	DS-2CD2143G0-IU	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP66- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone	IRR 43,940,000	
28	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof -housing, HIK-Connect cloud service - S: Audio/Alarm IO connectors	IRR 43,600,000	
29	DS-2CD2163G0-IS	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 52,580,000	
30	DS-2CD2163G0-IS (Black)	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 41,510,000	
31	DS-2CD2163G0-IU	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone	IRR 47,030,000	








32	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 61,910,000	
33	DS-2CD2183G0-IU	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP66, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone	IRR 55,510,000	
34	DS-2CD2183G0-IS (Black)	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 48,860,000	
35	Bullet Series			
36	DS-2CD2T35FWD-IS/I8	3 MP Ultra-Low Light Network Bullet Camera Up to 3 megapixel high resolution <ul style="list-style-type: none"> Max. 2048 × 1536 @30fps 2.8 mm/4mm/6mm/8 mm/12mm fixed lens, optional Ultra-low light H.265, H.265+, H.264+, H.264 120dB Wide Dynamic Range 3D Digital Noise Reduction-12 VDC & PoE (802.3af) IR range: 50m, 80m, optional Support on-board storage, up to 128 GB IP67 	ناموجود	
37	DS-2CD2T43G0-IS	1/3" Progressive Scan CMOS, 2688 × 1520 @30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 39,800,000	
38	DS-2CD2T43G0-I8	1/3" Progressive Scan CMOS, 2688 × 1520 @30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range	IRR 40,990,000	
39	DS-2CD2T63G0-IS	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048 @20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	IRR 45,120,000	








40	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 45,480,000	
41	DS-2CD2T83G0-IS	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	ناموجود	
42	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 69,540,000	
43	Exir Dome Series			
44	DS-2CD2322WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 37,740,000	
45	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 46,560,000	
46	Mini Dome Series			
47	DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	ناموجود	
48	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO	IRR 58,730,000	
49	DS-2CD2543G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 × 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	IRR 57,650,000	

50	DS-2CD2563G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 lux with IR - 3072 × 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	ناموجود	
51	Lite Bullet Vari-Facal Motorized Series			
52	DS-2CD1623G0-I	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 49,190,000	
53	DS-2CD1623G0-IZ	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 55,120,000	
54	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 59,360,000	
55	DS-2CD1643G0-IZ	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 65,300,000	
56	Lite Dome Vari-Facal Series			
57	DS-2CD1723G0-I	2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	IRR 49,190,000	
58	DS-2CD1743G0-I	4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	IRR 53,430,000	
59	DS-2CD1743G0-IZ	4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens	IRR 48,900,000	
60	Bullet Vari-Facal Motorized Series			








61	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+ , dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 57,670,000	
62	DS-2CD2643G0-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS - 2688 x1520@30fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I - H.265+, H.265, H.264+, H.264 - Three streams - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens - Z:Motorized VF lens	ناموجود	
63	DS-2CD2643G1-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS - 2688 x1520@30fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I - H.265+, H.265, H.264+, H.264 - Three streams - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 82,490,000	
64	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps -2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens	ناموجود	
65	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens	ناموجود	
66	Dome Vari-Facal Motorized Series			
67	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 42,800,000	
68	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - Z: Motorized VF lens	ناموجود	
69	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8" 2MP progressive scan CMOS Up to 1920 x 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA, Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - Z: Motorized VF lens	ناموجود	

70	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Max IR distance: 30 meters - 3-Axis adjustment - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8 to 12 mm Varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 behavior analyses, and face detection - Digital Noise Reduction 3D DNR - Z: Motorized VF lens	ناموجود	
71	DS-2CD2743G1-IZS	4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology-S: audio and alarm interface available-Water and dust resistant (IP67) and vandal proof (IK10)-Motorized varifocal lens for easy installation and monitoring-Robust structure design with full metal materials	IRR 71,650,000	
72	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	
73	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	
74	Fish Eye Series			
75	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 105,780,000	
76	Cube Smart Series			
77	DS-2CD2420F-I(W)	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB- IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker -Support Wi-Fi, support WPS configuration with one touch - Support PIR(Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	IRR 31,380,000	










78	DS-2CD2421G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 23,470,000	
79	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 30,920,000	
80	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 34,920,000	
81	Pin Hole Series			
82	DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
83	Hologen Series			
84	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optionaln - (Black, Silver, Golden) -W: Built-in Wi-Fi	ناموجود	
85	2Q Smart Series			
86	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 29,840,000	
87	DS-2CV2Q21FD-IW	2 MP CMOS PT Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - Default: No SD card included. - 32GB-T: Include 16GB sd card.	ناموجود	

88	2U Smart Series			
89	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 20,760,000	
90	Mini PTZ Series			
91	DS-2CD2F52F-IS	5MP CMOS ICR Infrared Network Dome Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 48,860,000	
92	IP PTZ Camera			
93	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	ناموجود	
94	DS-2DE4220IW-DE	2MP 20× Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	ناموجود	
95	DS-2DE4225IW-DE	2MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 × 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 148,810,000	
96	DS-2DE4425IW-DE	4MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 × 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 157,960,000	
97	DS-2DE5220IW-AE	2MP 20X Network IR PTZ Dome Camera - 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s - 150m IR Distance - Hi-PoE&24VAC	IRR 237,770,000	








98	DS-2DE5230W-AE	2MP 30× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	ناموجود	
99	DS-2DE7184-AE	2MP 20× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 100m IR Distance, Hi-PoE&24VAC	IRR 155,130,000	
100	DS-2DE7220IW-AE	22MP 20× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
101	DS-2DE7230IW-AE	2MP 30× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
102	DS-2DE7232IW-AE	2MP 32× Network IR Speed Dome, Up to 1920 × 1080@60fps resolution, Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR, 32× optical zoom, 16× digital zoom, WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus, Up to 150 m IR distance, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	IRR 273,510,000	
103	DS-2DE7320IW-AE	3MP 20× Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 × 1536@30fps Resolution - 20× optical zoom, 16× digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	IRR 284,320,000	
104	DS-2DE7330IW-AE	3MP 30× Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 × 1536@30fps Resolution - 30× optical zoom, 16× digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	

105	DS-2DE7420IW-AE	4MP 20× Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,20× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
106	DS-2DE7430IW-AE	4MP 30× Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,30× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
107	DS-2DE7530IW-AE	5MP 30× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
108	PanoVu Mini Series IR Network PTZ Camera			
109	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 × 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° × 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 × 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4× optical zoom, 8× digital zoom	IRR 152,920,000	
110	NVR-Monitor			
111	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 156,500,000	
112	NVR 4 Channel			
113	DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 18,520,000	
114	DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 32,750,000	

115	DS-7604NI-E1	IP video input : 4-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
116	DS-7604NI-E1/4P	IP video input : 4-ch / 4-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
117	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 30,510,000	
118	DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 43,610,000	
119	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 30,500,000	
120	DS-7604NI-K1/4P	IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
121	NVR 8 Channel			
122	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 19,240,000	
123	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 47,620,000	
124	DS-7608NI-E2	IP video input :8-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 38,010,000	

125	DS-7608NI-E2/8P	IP video input :8-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 63,600,000	
126	DS-7608NI-Q1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 36,870,000	
127	DS-7608NI-Q1/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
128	DS-7608NI-Q2	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
129	DS-7608NI-Q2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 69,810,000	
130	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 32,590,000	
131	DS-7608NI-K2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
132	NVR 16 Channel			
133	DS-7616NI-E2	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 41,890,000	
134	DS-7616NI-E2/8P	IP video input :16-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 66,700,000	
135	DS-7616NI-E2/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 88,960,000	

136	DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 32,900,000	
137	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 41,600,000	
138	DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 83,750,000	
139	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 50,420,000	
140	DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
141	DS-7716NI-E4	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
142	DS-7716NI-E4/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
143	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 84,170,000	
144	DS-7716NI-Q4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 124,070,000	
145	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 116,610,000	

146	DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 160,290,000	
147	NVR 32 Channel			
148	DS-7732NI-E4	IP video input :32-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 124,500,000	
149	DS-7732NI-E4/16P	IP video input :32-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
150	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 96,400,000	
151	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 139,520,000	
152	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 110,390,000	
153	DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 163,590,000	

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM

Accessories

Items

Description

User Price

Switches

1

DS-3E0105P-E/M

L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af PoE power budget 35W

IRR 9,800,000



2

DS-3E0105P-E

L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W

ناموجود



3

DS-3E0109P-E/M

L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af, PoE power budget 60W

IRR 25,000,000



4

DS-3E0109P-E

L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W

IRR 36,240,000



5

DS-3E0318P-E

L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W

IRR 59,500,000







6









DS-3E0326P-E








L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W





IRR 79,000,000



7	DS-3E1310P-E	L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	ناموجود	
8	DS-3E1318P-E	802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss, Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission, VLAN configurable Port trunk, multicast and port mirroring, WEB management, Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation	ناموجود	
9	Cables			
10	DS-1LN6-UE-W	UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 46,940,000	
11	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 51,660,000	
12	Brackets			
13	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 6,840,000	
14	DS-1602ZJ-pole	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
15	DS-1605ZJ	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	ناموجود	

16	DS-1661ZJ	Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: -116.5×200mm-Weight: -600g	IRR 7,490,000	
17	DS-1662ZJ	Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 8,600,000	
18	DS-1663ZJ	Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
19	DS-1693ZJ	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	ناموجود	
20	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 1,860,000	
21	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	Call	 
22	Keyboard			
23	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	IRR 346,900,000	

24	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	IRR 83,140,000	
25	Tester			
26	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	ناموجود	
27	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 138,420,000	
28	Adapters			
29	AD-121/P	12V-1A	IRR 420,000	
30	AD-122/P	12V -2A	IRR 450,000	
31	AD-122/PL	12V-2A	IRR 480,000	
32	AD-125/PL	12V -5A	IRR 800,000	

33	AD-12A/M	12V -10A-METAL	IRR 1,180,000	
34	AD-12F/M	12V -15A-METAL	IRR 1,600,000	
35	AD-12K/MF	12V -20A-METAL WITH FAN	IRR 1,840,000	
36	AD-12U/MF	12V -30A-METAL WITH FAN	IRR 2,550,000	

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com



CONTACT US

HIKVISIONTEHRAN.COM

Hard Disk

Items

Description

User Price

Surveillance HDD



Purple

1

WD10PURX-WD Purple 1TB

Capacity 1TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB

CALL



2

WD20PURX-WD Purple 2TB

Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB

CALL











3








WD30PURX-WD Purple 3TB

Capacity 3TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB

CALL



4	WD40PURX-WD Purple 4TB	Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
5	WD60PURX-WD Purple 6TB	Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 64MB	CALL	
6	WD82PURX-WD Purple 8TB	Capacity 8TB - interface SATA - Transfer Rate 6Gb/s - RPM 5400 - Cache 256MB	CALL	
7	WD101PURX-WD Purple 10TB		CALL	
8	WD121PURX-WD Purple 12TB		CALL	
11	Surveillance HDD  			
12	ST2000VX - Seagate Surveillance 2TB	Capacity 2TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB	CALL	

13	ST3000VX - Seagate Surveillance 3TB		CALL	
14	ST4000VX - Seagate Surveillance 4TB	Capacity 4TB - interface SATA - Transfer Rate 6Gb/s - RPM 5900 - Cache 64MB	CALL	
15	ST6000VX - Seagate Surveillance 6TB	Capacity 6TB - interface SATA - Transfer Rate 6Gb/s - RPM 7200 - Cache 256MB	CALL	
16	ST8000VX - Seagate Surveillance 8TB		CALL	
17	ST10000VX - Seagate Surveillance 10TB		CALL	
18	ST12000VX - Seagate Surveillance 12TB		CALL	
19	ST14000VX - Seagate Surveillance 14TB		CALL	

20

NAS HDD



21

ST2000VN - Seagate Iron Wolf 2TB

CALL



22

ST3000VN - Seagate Iron Wolf 3TB

CALL



23

ST4000VN - Seagate Iron Wolf 4TB


CALL



24

ST6000VN - Seagate Iron Wolf 6TB


CALL



25

ST8000VN - Seagate Iron Wolf 8TB

CALL
















26

ST10000VN - Seagate Iron Wolf 10TB

CALL



27	ST12000VN - Seagate Iron Wolf 12TB		CALL	
28	ST14000VN - Seagate Iron Wolf 14TB		CALL	
29	Enterprise HDD  			
30	ST2000NM - Seagate EXOS 2TB		CALL	
31	ST3000NM - Seagate EXOS 3TB		CALL	
32	ST4000NM - Seagate EXOS 4TB		CALL	
33	ST6000NM - Seagate EXOS 6TB		CALL	

34	ST8000NM - Seagate EXOS 8TB		CALL	
35	ST10000NM - Seagate EXOS 10TB		CALL	
36	ST12000NM - Seagate EXOS 12TB		CALL	
37	ST14000NM - Seagate EXOS 14TB		CALL	
38	ST16000NM - Seagate EXOS 16TB		CALL	

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه
تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923







ایمیل

Info@Hikvisiontehran.com

CONTACT US









HIKVISIONTEHRAN.COM







Hilook-DVR








Items	Description	User Price	
1 THC-B110-M	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	IRR 4,810,000	
2 THC-B120-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 6,500,000	
3 THC-B120-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 7,090,000	
4 THC-B120-MPIRL	2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66	IRR 7,630,000	
5 THC-B140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 7,240,000	
6 THC-B140-M	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 7,990,000	




7	THC-B220	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 7,590,000	
8	THC-B220-M	2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66 , 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 8,440,000	
9	THC-B240	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm - fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 9,110,000	
10	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66 , 2.8/3.6/6mm Lens ,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 9,940,000	
11	THC-T110-P	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	IRR 3,460,000	
12	THC-T120-PC	2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 4,900,000	
13	THC-T120	2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 7,400,000	
14	THC-T120-M	2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 6,270,000	
15	THC-T140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 7,340,000	
16	THC-T140	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 7,400,000	

17	THC-T140-M	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 8,400,000	
18	THC-T220-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 6,580,000	
19	THC-T220-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 7,710,000	
20	THC-T240-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 8,740,000	
21	THC-T240-M	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 9,900,000	
22	Vari-Focal Series			
23	THC-B320-VF	2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,, DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 15,200,000	
24	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens , EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66 , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 16,780,000	
25	THC-D320-VF	2MP CMOS Sensor, 40m IR , EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens --support HD-TVI/AHD/CVI/CVBS video output--IK10-Full Metal	IRR 14,900,000	
26	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens ,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 16,110,000	

27	THC-T320 VF	2MP CMOS Sensor, 40m IR , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu , IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 13,780,000	
28	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 15,070,000	
29	Turbo HD PTZ Camera			
30	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom, 16× digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	IRR 71,040,000	
31	PTZ-T4215I-D	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 15× optical zoom, 16× digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	ناموجود	
32	PTZ-T5225I-A	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs	ناموجود	
33	DVR 4 Channel			
34	DVR-104G-F1	4-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP), Long distance transmission over UTP and coaxial cable, H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, Encoding ability up to 1080p lite @ 12 fps, One HDD for continuous video recording, Smart search for efficient playback.	IRR 8,830,000	
35	DVR-204G-F1	Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, - 1-ch Up to 960P resolution), 1 SATA (6TB) interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 11,120,000	
36	DVR-204Q-F1	Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input (up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4: 1920×1080P: 12 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 12,370,000	

37	DVR-204Q-K1	<p>H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.</p>	IRR 15,490,000	
38	DVR-204U-F1	<p>Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch IP video input(up to 6MP resolution), 1 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output HD1080p-Metal</p>	IRR 19,020,000	
39	DVR-204U-K1	<p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal</p>	IRR 22,170,000	
40	DVR 8 Channel			
41	DVR-108G-F1	<p>8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.</p>	IRR 15,050,000	
42	DVR-208G-F1	<p>Recording Capability HD1080p Lite 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,-2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	IRR 18,380,000	
43	DVR-208Q-F1	<p>Recording Capability 3MP 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal</p>	IRR 30,700,000	
44	DVR-208Q-K1	<p>Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).</p>	IRR 27,070,000	

45	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- HDMI output 4K-Metal	IRR 38,140,000	
46	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 41,080,000	
47	Digital Video Recorder			
48	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 21,000,000	
49	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 26,570,000	
50	DVR-216G-K1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 26,570,000	
51	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) - interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case- HDMI output 1ch 4k-Metal	IRR 37,620,000	
52	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 46,440,000	

53	DVR-216Q-K2	<p>One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite</p>	IRR 48,820,000	
54	DVR-216U-F2	<p>Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-</p>	IRR 72,210,000	
55	DVR-216U-K2	<p>DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD – CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording</p>	IRR 81,300,000	

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923







ایمیل


Info@Hikvisiontehran.com









CONTACT US







HIKVISIONTEHRAN.COM









Hilook-NVR

Items	Description	User Price	
1 IPC-B120	1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 14,280,000	
2 IPC-B120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 15,050,000	
3 IPC-B121H	1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265	IRR 15,050,000	
4 IPC-B140H	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 18,610,000	
5 IPC-B140H-M	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 20,360,000	
6 IPC-B150H-M	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 22,620,000	

7	IPC-B220	1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 16,240,000	
8	IPC-B220-D	1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 15,520,000	
9	IPC-T120	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR -H.264+&H.264- ,2.8/4/6mm fixed lens- BLC, - DC12V & PoE , -up to 10m IR - Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 14,900,000	
10	IPC-T120-D	1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 14,170,000	
11	IPC-T220-H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE , -up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens- Eyeball: MetalCover: Plastic-IP67	IRR 17,190,000	
12	IPC-T220	1/2.8" progressive scan CMOS BLC/3D DNR,1920 × 1080@30fps,IP67 2.8, 4, 6 mm fixed lens,Digital WDR,H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON);	IRR 16,980,000	
13	IPC-T240H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR - 3D DNR-DWDR, BLC, DC12V & PoE- 2.8/4/6mm fixed lens ,--Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 21,360,000	
14	IPC-D120	1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps- 2.8mm fixed lens-H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 15,600,000	
15	IPC-D120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,-- 2.8/4/6mm fixed lens - BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR - Base: Metal-Cover: Plastic- IP67 , IK10	IRR 16,040,000	
16	IPC-D140H	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR.	IRR 19,780,000	

17	IPC-D150H	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 19,940,000	
18	Vari-Focal Series			
19	IPC-B620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic- IP67	IRR 33,050,000	
20	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR- DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 37,550,000	
21	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 36,560,000	
22	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens- Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,160,000	
23	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included 2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 33,620,000	
24	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, DWDR- 3D DNR, BLC, 2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 32,090,000	
25	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 35,900,000	

26	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 35,380,000	
27	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 38,060,000	
28	PanoVu Mini Series IR Network PTZ Camera			
29	PTZ-P332ZI-DE3	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkageI Up to 10 m IR radius Panoramic Cameral Three 1/2.8" progressive scan CMOSI 3-ch 1920 × 1080@30fps resolutionI Horizontal FOV: 128.5° × 3 PTZ Cameral 1/2.8" progressive scan CMOSI Up to 1920 × 1080@30fps resolutionI 4× optical zoom, 8× digital zoom	IRR 159,000,000	
30	IP PTZ Camera			
31	PTZ-N4215-DE3	1/2.8" progressive scan CMOS Up to 1920 × 1080 resolutionMin. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 72,810,000	
32	PTZ-N4215I-DE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance15× optical zoom, 16× digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compressionUp to 24 programmable privacy masks Support ROI	IRR 77,880,000	
33	PTZ-N4225I-DE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IRUp to 100 m IR distance 25× optical zoom, 16× digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI	IRR 94,590,000	

34	PTZ-N2404I-DE3	<p>Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10)</p>	IRR 50,020,000	
35	Network Video Recorder			
36	NVR-104-B	<p>Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p</p>	IRR 9,810,000	
37	NVR-108-B	<p>Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),,Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p</p>	IRR 12,030,000	
38	NVR-108-B/8p	<p>4-ch Mini 1U 4 PoE 4K NVR,Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Supports decoding H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording</p>	IRR 30,490,000	
39	NVR-104MH-C	<p>Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p</p>	IRR 15,590,000	
40	NVR-104MH-D	<p>Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.</p>	IRR 12,510,000	
41	NVR-104MH-D/4P	<p>Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording</p>	IRR 21,660,000	
42	NVR-104MH-C/4P	<p>Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) ,Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P</p>	IRR 22,860,000	

43	NVR-108MH-C	Recording at up to 8 MP resolution- 80Mbps Bit Rate Input - Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps - H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 20,970,000	
44	NVR-108MH-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 16,800,000	
45	NVR-208MH-C	Recording at up to 8 MP resolution- 80Mbps Bit Rate Input - Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps - H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 22,820,000	
46	NVR-108MH-C/8P	Recording at up to 8 MP resolution- 80Mbps Bit Rate Input - Max (up to 8-ch IP video UP tp 8mp), Output Bandwidth 80Mbps ,- H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)--HDMI Output 1ch 4k, - Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 53,500,000	
47	NVR-108M-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 47,520,000	
48	NVR-116MH-C	Recording at up to 8 MP resolution- 160Mbps Bit Rate Input - Max (up to 16-ch IP video UP to 8MP), Output Bandwidth 80Mbps ,- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 24,530,000	
49	NVR-216MH-C	Recording at up to 8 MP resolution- 160Mbps Bit Rate Input Max (up to 16-ch IP video), Output Bandwidth 80Mbps , - H.265- 2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,190,000	
50	NVR-216MH-C/16P	Recording at up to 8 MP resolution- 160Mbps Bit Rate Input Max (up to 16-ch IP video) Output Bandwidth 80Mbps , H.265, 2 SATA (up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k,- Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 62,680,000	



Rack			
Items	Description	User Price	
ER Standing Rack IP42			
1	NRS - 3268	رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ	۴۸,۵۰۰,۰۰۰
2	NRS - 2768	رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ	۴۶,۰۰۰,۰۰۰
3	NRS - 2766	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ	۴۳,۰۰۰,۰۰۰
4	NRS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - به همراه فن و چهار چرخ	۴۱,۰۰۰,۰۰۰
5	NRS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - به همراه فن و چهار چرخ	۳۶,۸۰۰,۰۰۰
6	NRS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ	۱۹,۸۰۰,۰۰۰
7	NRS-1866	رک ۱۸ یونیت-عمق ۶۰-عرض ۶۰ - به همراه فن و چهار چرخ	۱۸,۴۰۰,۰۰۰
ER Wall Mount			
9	NRW - 1266	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۱۲,۰۰۰,۰۰۰
10	NRW - 0966	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۸,۷۰۰,۰۰۰
11	NRW - 0964	رک دیواری - ۹ یونیت- عمق ۴۵ ، عرض ۶۰	۸,۲۰۰,۰۰۰
12	NRW - 0766	رک دیواری - ۷ یونیت- عمق ۶۰ ، عرض ۶۰	۷,۵۰۰,۰۰۰
13	NRW - 0764	رک دیواری - ۷ یونیت- عمق ۴۵ ، عرض ۶۰	۶,۰۵۰,۰۰۰
14	NRW - 0664	رک دیواری - ۶ یونیت- عمق ۴۵ ، عرض ۶۰	۴,۶۰۰,۰۰۰
15	NRW - 0445	رک دیواری - ۴ یونیت- عمق ۴۵ ، عرض ۶۰	۴,۳۰۰,۰۰۰
16	NRW - 0446	رک دیواری - ۴ یونیت- عمق ۴۰	۲,۶۰۰,۰۰۰
Shelf			
18	NRA - SSW	طبقه ثابت رک های دیواری عمق ۴۵	۷۰۰,۰۰۰
19	NRA - SSW	طبقه ثابت رک های دیواری عمق ۶۰	۸۱۰,۰۰۰
20	NRA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۱,۴۸۰,۰۰۰

21	NRA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۱,۸۴۰,۰۰۰
22	NRA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۲,۰۰۰,۰۰۰
23	NRA - SSU	سینی ثابت دو یونیت	۲,۱۰۰,۰۰۰
24	Power Module		
25	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۲,۰۰۰,۰۰۰
26	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۱,۰۳۰,۰۰۰
27	Accessories		
28	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۲,۶۰۰,۰۰۰
29	ERA - SCR - 20	پیچ و کژنات مخصوص رک بسته ۵۰ تایی	۷۸۰,۰۰۰
30	ERA - TR - 20	حرارت سنچ یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان	۱۴,۰۰۰,۰۰۰
31	ERA - FN - 20	فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۱,۵۰۰,۰۰۰
32	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ	۷۲۰,۰۰۰
33	ERA - CM - 20	نگهدارنده عمودی کابل	۱۳۵,۰۰۰
34	ERA - CM - 30	نگهدارنده کابل درپوش دار	۶۵۰,۰۰۰
35	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۴۰۰,۰۰۰
36	Blank Panel		
37	ERA - BLA - 10	بلانک پنل ، ۱ یونیت	۳۱۰,۰۰۰
38	ERA - BLA - 20	بلانک پنل ، ۲ یونیت	۴۱۰,۰۰۰
39	ERA - BLA - 30	بلانک پنل ، ۳ یونیت	۵۷۰,۰۰۰
40	ERA - BLA - 40	بلانک پنل ، ۴ یونیت	۶۷۰,۰۰۰
41	ERA - BLA - 50	بلانک پنل ، ۱۰ یونیت فرچه ای	۷۲۰,۰۰۰

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه
تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل

Info@Hikvisiontehran.com

CONTACT US

HIKVISIONTEHRAN.COM

Equip Rack

Items	Description	User Price
ER Standing Rack IP42		
1	ERS - 4761 رک 47 یونیت-عمق-100-عرض 60 - درب جلو و درب عقب مشبک	98,500,000
2	ERS - 4461 رک 44 یونیت-عمق-100-عرض 60 - درب جلو و درب عقب مشبک	96,500,000
3	ERS - 4281 رک 42 یونیت-عمق 100-عرض 80 - درب جلو مشبک، درب پشت 2 لنگه مشبک	124,000,000
4	ERS - 4261 رک 42 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	77,000,000
5	ERS - 4268 رک 42 یونیت-عمق 80-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	66,500,000
6	ERS - 4266 رک 42 یونیت-عمق 60-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	60,000,000
7	ERS - 3761 رک 37 یونیت-عمق 100-عرض 60 - درب جلو شیشه ای فریم دار، درب پشت فلزی	68,000,000

8	ERS - 3768	رک ۳۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۶۰,۰۰۰,۰۰۰
9	ERS - 3766	رک ۳۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۴,۵۰۰,۰۰۰
10	ERS - 3261	رک ۳۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۶۴,۵۰۰,۰۰۰
11	ERS - 3268	رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۸,۲۰۰,۰۰۰
12	ERS - 3266	رک ۳۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۳,۰۰۰,۰۰۰
13	ERS - 2761	رک ۲۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۸,۲۰۰,۰۰۰
14	ERS - 2768	رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۱,۰۰۰,۰۰۰
15	ERS - 2766	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۶,۰۰۰,۰۰۰
16	ERS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۵۲,۰۰۰,۰۰۰
17	ERS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۴,۰۰۰,۰۰۰
18	ERS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۱,۰۰۰,۰۰۰
19	ERS - 1868	رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۲,۳۰۰,۰۰۰
20	ERS-1866	رک ۱۸ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۷,۶۰۰,۰۰۰

21	ERS-1468	رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۸,۰۰۰,۰۰۰
22	ERS-1466	رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۵,۰۰۰,۰۰۰
ER Wall Mount			
23	ERW - 1266	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۱۴,۷۰۰,۰۰۰
24	ERW - 0966	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۱۱,۵۰۰,۰۰۰
25	ERW - 0964	رک دیواری - ۹ یونیت- عمق ۴۵ ، عرض ۶۰	۹,۳۵۰,۰۰۰
26	ERW - 0666	رک دیواری - ۶ یونیت- عمق ۶۰ ، عرض ۶۰	۸,۰۰۰,۰۰۰
27	ERW - 0663	رک دیواری - ۶ یونیت- عمق ۳۳ ، عرض ۶۰	۷,۰۰۰,۰۰۰
28	ERW - 0764	رک دیواری - ۷ یونیت- عمق ۴۵ ، عرض ۶۰	۸,۷۰۰,۰۰۰
29	ERW - 0366	رک دیواری - ۳ یونیت- عمق ۶۰ ، عرض ۶۰ (تاشو)	۱۱,۰۰۰,۰۰۰
ER OUTDOOR RACK			
30	ERO - 0745	OUTDOOR رک ۷ یونیت - عمق ۴۵	۴۷,۵۰۰,۰۰۰
31	ERO - 0966	OUTDOOR رک ۹ یونیت - عمق ۶۰	۵۹,۰۰۰,۰۰۰
32	ERO - 1266	OUTDOOR رک ۱۲ یونیت - عمق ۶۰	Call
33	ERO - 1866	OUTDOOR رک ۱۸ یونیت - عمق ۸۰	۸۸,۵۰۰,۰۰۰
شامل تخفیف نمی گردد OUTDOOR لازم به ذکر است رک های			
ER MAIN FRAME			
34	ERM - 4202	رک ۴۲ یونیت - آزمایشگاهی - چهار ستون	CALL
35	ERM - 4201	رک ۴۲ یونیت - آزمایشگاهی - دو ستون	CALL

36	ERM - 3202	رک ۳۲ یونیت - آزمایشگاهی - چهار ستون	CALL
Shelf			
37	ERA - SSW	طبقه ثابت رک های دیواری عمق ۳۳	۷۰۰,۰۰۰
38	ERA - SSW	طبقه ثابت رک های دیواری عمق ۴۵	۱,۳۰۰,۰۰۰
39	ERA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۱,۶۵۰,۰۰۰
40	ERA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۲,۴۰۰,۰۰۰
41	ERA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۲,۹۰۰,۰۰۰
42	ERA - SM 60	سینی متحرک رک ۶۰ سانتیمتر	۴,۰۰۰,۰۰۰
43	ERA - SM 80	سینی متحرک رک ۸۰ سانتیمتر	۴,۰۰۰,۰۰۰
44	ERA - SM 10	سینی متحرک رک ۱۰۰ سانتیمتر	۴,۰۰۰,۰۰۰
Power Module			
45	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۲,۰۰۰,۰۰۰
46	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۱,۰۳۰,۰۰۰
Accessories			
47	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۲,۶۰۰,۰۰۰
48	ERA - SCR - 20	پیچ و کژنات مخصوص رک بسته ۵۰ تایی	۷۸۰,۰۰۰
49	ERA - TR - 20	حرارت سنج یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان	۱۴,۰۰۰,۰۰۰
50	ERA - FN - 20	فن بوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۱,۵۰۰,۰۰۰
51	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ	۷۲۰,۰۰۰
52	ERA - CM - 20	نگهدارنده عمودی کابل	۱۳۵,۰۰۰
53	ERA - CM - 30	نگهدارنده کابل درپوش دار	۶۵۰,۰۰۰

54	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۴۰۰,۰۰۰
Blank Panel			
55	ERA - BLA - 10	بلانک پنل ، ۱ یونیت	۳۱۰,۰۰۰
56	ERA - BLA - 20	بلانک پنل ، ۲ یونیت	۴۱۰,۰۰۰
57	ERA - BLA - 30	بلانک پنل ، ۳ یونیت	۵۷۰,۰۰۰
58	ERA - BLA - 40	بلانک پنل ، ۴ یونیت	۶۷۰,۰۰۰
59	ERA - BLA - 50	بلانک پنل ، ۱ یونیت فرجه ای	۷۲۰,۰۰۰
Doors			
60	EDM - 0000	درب مشبک (جلو) جهت رک های ۲۷-۳۲-۳۷-۴۴-۴۲-۴۷	۱۳,۰۰۰,۰۰۰
61	EDM - 0001	درب مشبک (عقب) جهت رک های ۲۷-۳۲-۳۷-۴۴-۴۲-۴۷	۷,۰۰۰,۰۰۰
62	EDM - 0002	درب مشبک دو لنگه با قفل ریتال جهت رک های ۴۲-۴۴-۴۷	۱۷,۰۰۰,۰۰۰
لازم به ذکر است درب مشبک شامل تخفیف نمی گردد			