

# HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس






09906500074-66765968-66765923











ایمیل










Info@Hikvisiontehran.com





















CONTACT US  
HIKVISIONTEHRAN.COM



Turbo HD Camera - DVR			
Items	Description	User Price	
<b>Turbo HD - 1MP</b>			
1	<b>DS-2CE16C0T-IRP</b> 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	<b>IRR 3,730,000</b>	
2	<b>DS-2CE56C0T-IRP</b> 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	<b>IRR 3,800,000</b>	
3	<b>DS-2CE56C0T-IRPF</b> 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - <b>Switchable TVI/AHD/CVI/CVBS</b>	<b>IRR 4,070,000</b>	
<b>Turbo HD - 2MP</b>			
5	<b>DS-2CE16D0T-IF</b> 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output ( <b>switchable TVI/AHD/CVI/CVBS</b> ) - IP66 weatherproof - True Day/Night, Smart IR	<b>IRR 4,540,000</b>	
6	<b>DS-2CE56D0T-IPF</b> 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output ( <b>switchable TVI/AHD/CVI/CVBS</b> ) - True Day/Night, Smart IR	<b>IRR 3,680,000</b>	

7	<b>DS-2CE16D0T-IR</b>	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	<b>IRR 5,440,000</b>	
8	<b>DS-2CE56D0T-IR</b>	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR	<b>IRR 5,280,000</b>	
9	<b>DS-2CE56D0T-IRM</b>	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	<b>IRR 5,445,000</b>	
10	<b>DS-2CE16D0T-IT1</b>	,2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	ناموجود	
11	<b>DS-2CE16D0T-IT3</b>	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens - IP66 weatherproof	<b>IRR 7,640,000</b>	
12	<b>DS-2CE56D0T-IT1</b>	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	ناموجود	
13	<b>DS-2CE16D0T-VFIR3F</b>	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens <b>2.8 - 12 mm @ F1.4</b>	<b>IRR 12,250,000</b>	
14	<b>DS-2CE56D0T-VFIR3F</b>	2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens <b>2.8 - 12 mm @ F1.4</b>	<b>IRR 12,250,000</b>	
15	<b>Turbo HD - 2MP built-in PoC</b>			
16	<b>DS-2CE16D0T-IRE</b>	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	<b>IRR 6,650,000</b>	
17	<b>DS-2CE16D0T-IT1E</b>	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu. IP66, 2.8/3.6/6mm Lens	ناموجود	









18	<b>DS-2CE56D0T-IT1E</b>	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	<b>IRR 7,990,000</b>	
19	<b>DS-2CE56D0T-IT3E</b>	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	ناموجود	
20	<b>DS-2CE16D0T-VFIR3E</b>	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu , IP66 - Lens 2.8 - 12 mm @ F1.4	ناموجود	
21	<b>DS-2CE56D0T-VFIR3E</b>	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & <b>built-in PoC</b> , Smart IR DNR, OSD Menu IP66 - Lens 2.8 - 12 mm @ F1.4	ناموجود	
22	<b>Turbo HD - 2MP built-in PoC - Starlight Value Series</b>			
23	<b>DS-2CE16D8T-ITE</b>	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ <b>built-in PoC</b> , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	<b>IRR 10,300,000</b>	
24	<b>DS-2CE56D8T-ITME</b>	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ <b>built-in PoC</b> , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	<b>IRR 10,080,000</b>	
25	<b>DS-2CE16D8T-IT3E</b>	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ <b>built-in PoC</b> , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67 , 2.8/3.6/6mm Lens	ناموجود	
26	<b>DS-2CE16D8T-IT3ZE</b>	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ <b>built-in PoC</b> , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, 2.8 mm to 12 mm motorized vari-focal lens - IP67	<b>IRR 17,600,000</b>	
27	<b>DS-2CE56D8T-IT1E</b>	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ <b>built-in PoC</b> , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	<b>IRR 10,590,000</b>	

28	<b>DS-2CE38D8T-PIR</b>	2.0 megapixel progressive scan CMOS - <b>Ultra-Low Light PIR</b> Cube Camera - Color: <b>0.005 Lux</b> @ (F1.2, AGC ON), 0 Lux with IR - 2.8 mm, 3.6 mm fixed focal lens - Backlight Compensation: WDR/BLC/OFF - Motion Detection: 4 programmable motion areas	ناموجود	
29	<b>Turbo HD - 3MP</b>			
30	<b>DS-2CE16F1T-IT</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 6,800,000	
31	<b>DS-2CE56F1T-ITM</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 6,800,000	
32	<b>DS-2CE16F1T-IT1</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	ناموجود	
33	<b>DS-2CE16F1T-IT3</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	ناموجود	
34	<b>DS-2CE16F1T-IT5</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 80m IR distance - IP66 weatherproof	ناموجود	
35	<b>DS-2CE56F1T-IT1</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 7,150,000	
36	<b>DS-2CE56F1T-IT3</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 8,030,000	
37	<b>DS-2CE16F7T-IT3Z</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - <b>2.8-12mm motorized varifocal lens</b> - True Day/Night - OSD menu, DNR, Smart IR - <b>True WDR</b> , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	ناموجود	










38	<b>DS-2CE56F7T-IT3Z</b>	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - <b>2.8-12mm motorized vari-focal lens</b> - True Day/Night - OSD menu, DNR, Smart IR - <b>True WDR</b> , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	<b>IRR 20,160,000</b>	
39	<b>Turbo HD - 5MP</b>			
40	<b>DS-2CE16H0T-ITF</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 8,560,000</b>	
41	<b>DS-2CE16H0T-IT1F</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 9,340,000</b>	
42	<b>DS-2CE16H0T-IT3F</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 10,080,000</b>	
43	<b>DS-2CE16H0T-IT5F</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	ناموجود	
44	<b>DS-2CE16H0T-IT3ZF</b>	5 MP high performance COMS - 2560 × 1944 resolution - <b>2.7 mm to 13.5 mm motorized vari-focal lens</b> - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 17,390,000</b>	
45	<b>DS-2CE56H0T-ITMF</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	ناموجود	
46	<b>DS-2CE56H0T-IT1F</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 9,580,000</b>	
47	<b>DS-2CE56H0T-IT3F</b>	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 9,850,000</b>	









48	<b>DS-2CE56H0T-IT3ZF</b>	5 MP high performance COMS - 2560 x 1944 resolution - <b>2.7 mm to 13.5 mm motorized vari-focal lens</b> - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - <b>4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</b> - IP67	<b>IRR 17,140,000</b>	
<b>49 Turbo HD - 5MP - built-in PoC</b>				
50	<b>DS-2CE16H1T-ITE</b>	5 MP high-performance CMOS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b> - <b>Up the coax</b>	<b>IRR 9,150,000</b>	

51	<b>DS-2CE16H1T-IT1E</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b> - <b>Up the coax</b>	<b>IRR 9,980,000</b>	
52	<b>DS-2CE16H1T-IT3E</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b> - <b>Up the coax</b>	<b>IRR 10,780,000</b>	
53	<b>DS-2CE16H1T-IT5E</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b>	ناموجود	
54	<b>DS-2CE16H1T-IT3ZE</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - <b>2.8 mm to 12 mm motorized vari-focal lens</b> - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - <b>PoC.at</b>	<b>IRR 18,600,000</b>	
55	<b>DS-2CE56H1T-ITME</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b>	<b>IRR 9,150,000</b>	
56	<b>DS-2CE56H1T-IT1E</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b>	<b>IRR 12,100,000</b>	
57	<b>DS-2CE56H1T-IT3E</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- <b>PoC.af</b>	<b>IRR 10,500,000</b>	
58	<b>DS-2CE56H1T-IT3ZE</b>	5 MP high-performance CMOS - 2560 × 1944 resolution - <b>2.8 mm to 12 mm motorized vari-focal lens</b> - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - <b>PoC.at</b>	ناموجود	
59	<b>DS-2CC52H1T-FITS</b>	5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, <b>Built-in microphone, 1-ch audio output</b>	ناموجود	
60	<b>TURBO HD 5MP (TURBO HD 5.0) PIR Series</b>			

61	<b>DS-2CE11H0T-PIRL</b>	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - <b>PIR detection, visual alarm</b> - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	ناموجود	
62	<b>DS-2CE12H0T-PIRL</b>	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - <b>PIR detection, visual alarm</b> - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	ناموجود	
63	<b>DS-2CE71H0T-PIRL</b>	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - <b>PIR detection, visual alarm</b> - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 8,700,000	
64	<b>Turbo HD - 8MP</b>			
65	<b>DS-2CE78U8T-IT3</b>	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 28,720,000	
66	<b>DS-2CE18U8T-IT3</b>	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 30,240,000	
67	<b>Turbo HD PTZ Camera</b>			
68	<b>DS-2AE5223TI-A (24VAC)</b>	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	ناموجود	
69	<b>DS-2AE7230TI-A (24VAC)</b>	High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30x optical zoom, focal length 4-120mm - 16x digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	ناموجود	
70	<b>Turbo HD DVR 720P / 1080p lite</b>			
71	<b>DS-7208HGHI-F1</b>	Analog video input 8-ch - <u>Encoding resolution</u> 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.264+/H.264 - <b>Full channel recording at up to 1080p lite resolution</b> - <u>Frame rate</u> : 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> 2-ch (up to 10-ch) Up to 2 MP resolution - Support H.264+/H.264 IP cameras - <u>Audio input</u> 1-ch - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	IRR 19,050,000	



72	DS-7216HGHI-K1	Analog video input 16-ch - Encoding resolution 1080p lite/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - Frame rate: 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 23,540,000	
73	<b>Turbo HD DVR 1080p / 3MP / 4MP lite</b>			
74	DS-7204HQHI-K1	Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 16,130,000	
75	DS-7108HQHI-K1	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity	IRR 22,726,000	
76	DS-7208HQHI-K1/Eco	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - <b>ECO CASE</b>	IRR 22,800,000	
77	DS-7208HQHI-K1	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 24,330,000	
78	DS-7116HQHI-K1	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity	IRR 35,590,000	
79	7216HQHI-K1-Eco	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - <b>ECO CASE</b>	ناموجود	
80	DS-7216HQHI-K1	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 41,740,000	
81	DS-7216HQHI-K2	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 46,200,000	

82	DS-7224HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <b>Full channel recording at up to 4 MP lite resolution</b> - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 32-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	ناموجود	
83	DS-7232HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <b>Full channel recording at up to 4 MP lite resolution</b> - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 80,390,000	
84	<b>Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite</b>			
85	DS-7204HUHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <b>8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1</b> - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 26,550,000	
86	DS-7208HUHI-K1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	ناموجود	
87	DS-7216HUHI-K2	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 73,990,000	
88	<b>Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)</b>			
89	DS-7204HUHI-K1/P	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <b>8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1</b> - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 x 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - <b>Provide power supply to PoC cameras over coaxial cable</b>	IRR 28,510,000	
90	DS-7208HUHI-K2/P	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - <b>Provide power supply to PoC cameras over coaxial cable</b>	IRR 53,190,000	
91	<b>Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP</b>			
92	DS-7204HTHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <b>Full channel recording at up to 8 MP resolution</b> - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 30,240,000	







93











**DS-7208HTHI-K2**











Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 x 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk











**IRR 58,790,000**













Network Camera - NVR			
Items	Description	User Price	
<b>Lite Mini Bullet Series</b>			
1	<b>DS-2CD1023G0E-I</b> 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - <b>ECO CASE</b>	IRR 14,100,000	
2	<b>DS-2CD1023G0-I</b> 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 14,650,000	
3	<b>DS-2CD1031-I</b> 1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8mm/4mm/6mm fixed focal lens Up to 30 m IR range- Dual stream- Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) - PoE (Power over Ethernet) - IP67	ناموجود	
4	<b>DS-2CD1043G0-I</b> 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 20,500,000	
5	<b>DS-2CD1053G0-I</b> 5.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1920@12.5fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, <b>True 120db WDR</b>	IRR 21,800,000	
<b>Lite Dome Series</b>			
7	<b>DS-2CD1123G0E-I</b> 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - <b>ECO CASE</b>	IRR 15,400,000	










8	<b>DS-2CD1123G0-I</b>	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	<b>IRR 15,680,000</b>	
9	<b>DS-2CD1323G0E-I</b>	1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - <b>ECO CASE</b>	ناموجود	
10	<b>DS-2CD1323G0-I</b>	1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	<b>IRR 14,850,000</b>	
11	<b>DS-2CD1131-I</b>	1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8 mm/4 mm/6 mm fixed focal lens Up to 30 m IR rang-Dual stream- Digital WDR (Wide Dynamic Range)- 3D DNR (Digital Noise Reduction) - PoE (Power over Ethernet) - IP67, Ik10	ناموجود	
12	<b>DS-2CD1143G0-I</b>	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	<b>IRR 21,080,000</b>	
13	<b>Mini Bullet Series</b>			
14	<b>DS-2CD2020F-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m	ناموجود	
15	<b>DS-2CD2023G0-I</b>	2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 22,870,000</b>	
16	<b>DS-2CD2043G0-I</b>	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 26,120,000</b>	
17	<b>DS-2CD2052-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams,IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m	<b>IRR 25,680,000</b>	
18	<b>DS-2CD2063G0-I</b>	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ناموجود	










19	<b>DS-2CD2083G0-I</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ناموجود	
20	<b>Dome Series</b>			
21	<b>DS-2CD2120F-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	ناموجود	
22	<b>DS-2CD2120F-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 22,000,000	
23	<b>DS-2CD2123G0-IS</b>	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	IRR 24,670,000	
24	<b>DS-2CD2143G0-IS</b>	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 26,730,000	
25	<b>DS-2CD2152F-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof -housing, HIK-Connect cloud service - S: Audio/Alarm IO connectors	IRR 27,000,000	
26	<b>DS-2CD2163G0-IS</b>	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 31,870,000	
27	<b>DS-2CD2183G0-IS</b>	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 37,520,000	
28	<b>Bullet Series</b>			
29	<b>DS-2CD2T35FWD-I8</b>	Up to 3 megapixel high resolution-Max. 2048 x 1536 @30fps - 2.8 mm/4mm/6mm/8 mm/12mm fixed lens,- optional - Ultra-low light-265, H.265+, H.264+, H.264- 120dB Wide Dynamic Range - 3D Digital Noise Reduction 12 VDC & PoE (802.3af) - IR range: 50m, 80m, optional- Support on board storage, up to 128 GB - IP67	ناموجود	
30	<b>DS-2CD2T43G0-IS</b>	1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 29,140,000	











31	<b>DS-2CD2T52-I5</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	ناموجود	
32	<b>DS-2CD2T63G0-I5</b>	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	ناموجود	
33	<b>DS-2CD2T63G0-I8</b>	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 35,470,000	
34	<b>DS-2CD2T83G0-I5</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	ناموجود	
35	<b>DS-2CD2T83G0-I8</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 42,150,000	
36	<b>Exir Dome Series</b>			
37	<b>DS-2CD2322WD-I</b>	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 22,930,000	
38	<b>DS-2CD2342FWD-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	ناموجود	
39	<b>DS-2CD2352-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	ناموجود	
40	<b>Mini Dome Series</b>			
41	<b>DS-2CD2523G0-IS</b>	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	ناموجود	
42	<b>DS-2CD2542FWD-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO	IRR 35,100,000	











43	<b>DS-2CD2543G0-IS</b>	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	ناموجود	
44	<b>DS-2CD2563G0-IS</b>	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	ناموجود	
45	<b>Lite Bullet Vari-Facal Motorized Series</b>			
46	<b>DS-2CD1623G0-I</b>	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 30,000,000</b>	
47	<b>DS-2CD1623G0-IZ</b>	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z:Motorized VF lens</b>	<b>IRR 33,410,000</b>	
48	<b>DS-2CD1643G0-I</b>	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 35,980,000</b>	
49	<b>Lite Dome Vari-Facal Series</b>			
50	<b>DS-2CD1723G0-I</b>	2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	<b>IRR 29,400,000</b>	
51	<b>DS-2CD1743G0-I</b>	4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	<b>IRR 32,380,000</b>	
52	<b>Bullet Vari-Facal Motorized Series</b>			
53	<b>DS-2CD2620F-I</b>	2 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	ناموجود	
54	<b>DS-2CD2632F-I</b>	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+ , dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	<b>IRR 34,950,000</b>	
55	<b>DS-2CD2643G0-IZS</b>	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS - 2688 x1520@30fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I - H.265+, H.265, H.264+, H.264 - Three streams - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z:Motorized VF lens</b>	<b>IRR 53,970,000</b>	




























56	<b>DS-2CD2663FG0-IZS</b>	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps -2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - <b>Z: Motorized VF lens</b>	ناموجود	
57	<b>DS-2CD2683G0-IZS</b>	<b>8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - <b>Z: Motorized VF lens</b></b>	ناموجود	
58	<b>Dome Vari-Facal <b>Motorized</b> Series</b>			
59	<b>DS-2CD2720F-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	<b>IRR 26,500,000</b>	
60	<b>DS-2CD2720F-IZ</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - <b>Z: Motorized VF lens</b>	<b>IRR 33,000,000</b>	
61	<b>DS-2CD2723G0-IZS</b>	2MP IR Motorized NETWORK DOME CAMERA 1/2.8 " 2MP progressive scan CMOS Up to 1920 × 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA,Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - <b>Z: Motorized VF lens</b>	ناموجود	
62	<b>DS-2CD2743G0-IZS</b>	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Max IR distance: 30 meters - 3-Axis adjustment - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8 to 12 mm Varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 behavior analyses, and face detection - Digital Noise Reduction 3D DNR - <b>Z: Motorized VF lens</b>	<b>IRR 53,970,000</b>	
63	<b>DS-2CD2763G0-IZS</b>	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 ×2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z: Motorized VF lens</b>	ناموجود	
64	<b>DS-2CD2783G0-IZS</b>	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z: Motorized VF lens</b>	ناموجود	
65	<b>Fish Eye Series</b>			
66	<b>DS-2CD2942F-IS</b>	Color: 0.01lux @(F1.2, AGC ON), 0.018lux @(F1.6, AGC ON), 0 lux with IR - 2560 × 1440 -1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical) -H.264/MJPEG - 50Hz: 12.5fps(2560 × 1440), 25fps(1920 × 1080, 1280 × 720) 60Hz: 15fps(2560 × 1440) - 30fps(1920 × 1080, 1280 × 720)  -8 meters - 12 VDC ± 10%, PoE (802.3af)	ناموجود	










67	<b>DS-2CD2955FWD-IS</b>	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	<b>IRR 64,710,000</b>	
68	<b>Cube Smart Series</b>			
69	<b>DS-2CD2420F-IW</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	ناموجود	
70	<b>DS-2CD2423G0-IW</b>	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - <b>PIR: 10m</b> - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	<b>IRR 20,560,000</b>	
71	<b>DS-2CD2442FWD-IW</b>	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB (SD card not included), -W: Built-in Wi-Fi with WPS	ناموجود	
72	<b>DS-2CD2443G0-IW</b>	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - <b>PIR: 10m</b> - 120dB WDR - Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	<b>IRR 25,440,000</b>	
73	<b>Pin Hole Series</b>			
74	<b>DS-2CD2D14WD</b>	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
75	<b>Hologen Series</b>			
76	<b>DS-2CD2E20F-W</b>	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional - (Black, Silver, Golden) -W: Built-in Wi-Fi	ناموجود	
77	<b>2Q Smart Series</b>			
78	<b>DS-2CD2Q10FD-IW</b>	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	<b>IRR 18,090,000</b>	
79	<b>DS-2CV2Q21FD-IW</b>	2 MP CMOS PT Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° - 355°; Tilt: -10° - 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - Default: No SD card included. - 32GB-T: Include 16GB sd card.	ناموجود	
80	<b>2U Smart Series</b>			








81	<b>DS-2CV2U21FD-IW</b>	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	<b>IRR 12,420,000</b>	
82	<b>Mini PTZ Series</b>			
83	<b>DS-2CD2F52F-IS</b>	5MP CMOS ICR Infrared Network Dome Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	<b>IRR 32,450,000</b>	
84	<b>IP PTZ Camera</b>			
85	<b>DS-2DE4A220IW-DE</b>	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	ناموجود	
86	<b>DS-2DE4220IW-DE</b>	2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	ناموجود	
87	<b>DS-2DE4225IW-DE</b>	2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS Up to 1920 x 1080@30fps resolution- Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	<b>IRR 92,260,000</b>	
88	<b>DS-2DE5220IW-AE</b>	2MP 20X Network IR PTZ Dome Camera - 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s - 150m IR Distance - Hi-PoE&24VAC	<b>IRR 147,400,000</b>	
89	<b>DS-2DE5230W-AE</b>	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	ناموجود	
90	<b>DS-2DE7184-AE</b>	2MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 100m IR Distance, Hi-PoE&24VAC	<b>IRR 96,100,000</b>	
91	<b>DS-2DE7220IW-AE</b>	22MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
92	<b>DS-2DE7230IW-AE</b>	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	

93	<b>DS-2DE7232IW-AE</b>	2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	<b>IRR 166,800,000</b>	
94	<b>DS-2DE7320IW-AE</b>	3MP 20x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 20x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	
95	<b>DS-2DE7330IW-AE</b>	3MP 30x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 30x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	
96	<b>DS-2DE7420IW-AE</b>	4MP 20x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,20x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
97	<b>DS-2DE7430IW-AE</b>	4MP 30x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,30x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
98	<b>DS-2DE7530IW-AE</b>	5MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
99	<b>PanoVu Mini Series IR Network PTZ Camera</b>			
100	<b>DS-2PT3326IZ-DE3(2.8-12mm)</b>	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 x 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° x 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 x 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4x optical zoom, 8x digital zoom	<b>IRR 94,000,000</b>	
101	<b>NVR-Monitor</b>			
102	<b>DS-7600NI-E1/A</b>	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	<b>IRR 109,000,000</b>	
103	<b>NVR 4 Channel</b>			
104	<b>DS-7104NI-Q1/M</b>	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 12,020,000</b>	
105	<b>DS-7104NI-Q1/4P/M</b>	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 19,850,000</b>	











106	<b>DS-7604NI-E1</b>	IP video input : 4-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
107	<b>DS-7604NI-E1/4P</b>	IP video input : 4-ch / <b>4-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
108	<b>DS-7604NI-Q1</b>	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 18,550,000</b>	
109	<b>DS-7604NI-Q1/4P</b>	IP video input : 4-ch / <b>4-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 26,500,000</b>	
110	<b>DS-7604NI-K1</b>	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
111	<b>DS-7604NI-K1/4P</b>	IP video input : 4-ch - <b>4-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
112	<b>NVR 8 Channel</b>			
113	<b>DS-7108NI-Q1/M</b>	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 15,110,000</b>	
114	<b>DS-7108NI-Q1/8P/M</b>	IP video input :8-ch / <b>8-ch POE</b> Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 28,860,000</b>	
115	<b>DS-7608NI-E2</b>	IP video input :8-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	<b>IRR 27,000,000</b>	
116	<b>DS-7608NI-E2/8P</b>	IP video input :8-ch / <b>8-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
117	<b>DS-7608NI-Q1</b>	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	<b>IRR 22,350,000</b>	
118	<b>DS-7608NI-Q1/8P</b>	IP video input : 8-ch / <b>8-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	










119	<b>DS-7608NI-Q2</b>	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
120	<b>DS-7608NI-K1</b>	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 22,990,000	
121	<b>DS-7608NI-K2/8P</b>	IP video input : 8-ch / <b>8-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
122	<b>NVR 16 Channel</b>			
123	<b>DS-7616NI-E2</b>	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
124	<b>DS-7616NI-E2/8P</b>	IP video input :16-ch / <b>8-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
125	<b>DS-7616NI-E2/16P</b>	IP video input :16-ch / <b>16-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
126	<b>DS-7616NI-Q1</b>	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 26,960,000	
127	<b>DS-7616NI-Q2</b>	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 28,210,000	
128	<b>DS-7616NI-Q2/16P</b>	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 57,460,000	
129	<b>DS-7616NI-K2</b>	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 31,350,000	
130	<b>DS-7616NI-K2/16P</b>	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
131	<b>DS-7716NI-E4</b>	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
132	<b>DS-7716NI-E4/16P</b>	IP video input :16-ch / <b>16-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	











133	<b>DS-7716NI-Q4</b>	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 60,330,000</b>	
134	<b>DS-7716NI-K4</b>	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 67,320,000</b>	
135	<b>DS-7716NI-K4/16P</b>	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>ناموجود</b>	
136	<b>NVR 32 Channel</b>			
137	<b>DS-7732NI-E4</b>	IP video input :32-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>ناموجود</b>	
138	<b>DS-7732NI-E4/16P</b>	IP video input :32-ch / <b>16-ch POE</b> Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 104,500,000</b>	
139	<b>DS-7732NI-Q4</b>	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 74,430,000</b>	
140	<b>DS-7732NI-Q4/16P</b>	IP video input : 32-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 107,850,000</b>	
141	<b>DS-7732NI-K4</b>	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>IRR 89,030,000</b>	
142	<b>DS-7732NI-K4/16P</b>	IP video input : 32-ch - <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	<b>ناموجود</b>	









Accessories				
Items	Description	User Price		
<b>Switches</b>				
1	<b>DS-3E0105P-E</b> L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	<b>IRR 8,625,000</b>		
2	<b>DS-3E0109P-E</b> L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	<b>IRR 21,970,000</b>		
3	<b>DS-3E0318P-E</b> L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	<b>IRR 50,270,000</b>		
4	<b>DS-3E0326P-E</b> L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	ناموجود		
5	<b>DS-3E1310P-E</b> L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	<b>IRR 23,230,000</b>		
6	<b>DS-3E1318P-E</b> 802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission,VLAN configurable Port trunk, multicast and port mirroring,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mouted design for convenient installation	ناموجود		
<b>Cables</b>				
8	<b>DS-1LN6-UE-W</b> UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	<b>IRR 28,450,000</b>		



9	DS-1LN6-UU	<p>UTP / CAT.6 / Indoor PVC / 23AWG  Full 305m  OFC / 0.565mm  CM Rating  Default Color: Orange</p>	IRR 31,310,000	
10	<b>Brackets</b>			
11	DS-1602ZJ	<p>Wall mount , Hik white , Aluminum alloy , 97×182×305mm  Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 4,150,000	
12	DS-1602ZJ-pole	<p>Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm ,  Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	ناموجود	
13	DS-1605ZJ	<p>Wall Mount bracket  Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras  Dimensions: Ø171.7 x 158 x 228.6mm</p>	ناموجود	
14	DS-1661ZJ	<p>Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: -  116.5×200mm-Weight: -600g</p>	IRR 4,560,000	
15	DS-1662ZJ	<p>Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm  Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 5,210,000	
16	DS-1663ZJ	<p>Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx  DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	ناموجود	
17	DS-1693ZJ	<p>Wall mount , Hik white , steel , 190×200×500mm , 5700g  Suitable for  PTZ positioner</p>	ناموجود	
18	DS-1681ZJ	<p>Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx  DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx</p>	IRR 1,520,000	
19	DS-1273ZJ-135B	<p>Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm  Suitable for:  DS-2CD27xx</p>	Call	

20	<b>Keyboard</b>			
21	<b>DS-1100KI</b>	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	ناموجود	
22	<b>DS-1005KI</b>	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	ناموجود	
23	<b>Tester</b>			
24	<b>IPC-4300H</b>	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	ناموجود	
25	<b>DS-TT-X41T-tester</b>	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 84,680,000	
26	<b>Access Control</b>			
27	<b>DS-K2804</b>	Four-door Access Controller, Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magneticx4, Door Switchx4, Case Inputx4; Output interface: Door Switch Relayx4, Alarm Relayx4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards information and 50,000 access control events	Call	
28	<b>DS-K1100 Series Card Reade</b>			
29	<b>DS-K1101MK</b>	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	Call	
30	<b>DS-K1102M</b>	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	Call	
31	<b>DS-K1102MK</b>	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	Call	
32	<b>DS-K1104M</b>	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	Call	

33	DS-K1801M	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
34	DS-K1801MK	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
35	<b>Card Sender</b>			
36	DS-K1F100-D8E	Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	Call	
37	<b>Pro Magnetic Lock</b>			
38	DS-K4T100	Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	Call	
39	DS-K4H250S	Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
40	DS-K4H250D	Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mAx2 24V/250mAx2	Call	
41	<b>Eco Magnetic Lock</b>			
42	DS-K4H188S	Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
43	<b>Pro Bracket for Magnetic Lock</b>			
44	DS-K4T100-U2	Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	Call	
45	DS-K4H250-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
46	DS-K4H250-U	U-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
47	<b>Eco Bracket for Magnetic Lock</b>			

48	DS-K4H188-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	Call	
49	<b>Door release button</b>			
50	DS-K7P01	aluminum alloy panel, metal button, Dimension(LxWxH): 86x86x20mm(3.39x3.39x0.79")	Call	
51	<b>DS-K1T8 Series</b>			
52	DS-K1T803MF	LCD Display Standalone Access Control Terminal, Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc	Call	
53	<b>DS-K1T200 Series</b>			
54	DS-K1T200MF-C	2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal, Built-in Mifare card reading module and 2 Megapixels camera, Max. 9500 fingerprints, Max. 100,000 cards No.and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
55	<b>DS-K1T105 Series</b>			
56	DS-K1T105M-C	2.8 inch LCD-TFT Screen Standalone Access Control Terminal, Built-in Mifare card (EM card) reading module, 2 Megapixels camera, Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
57	DS-K1T801M	Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
58	DS-K1T802M	LCD Display Screen Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
59	<b>Card</b>			
60	S50+TK4100	EM + Mifare	Call	
61	<b>Adapters</b>			
62	Power Adapter	12V/1A	IRR 440,000	



# HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923








ایمیل

Info@Hikvisiontehran.com












CONTACT US  
HIKVISIONTEHRAN.COM

## Hilook-DVR

Items	Description	User Price	
1	<b>THC-B120-P</b> 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	<b>IRR 5,050,000</b>	
2	<b>THC-B120-M</b> 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	<b>IRR 5,950,000</b>	
3	<b>THC-B140-P</b> 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	<b>IRR 5,200,000</b>	
4	<b>THC-B140-M</b> 4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	<b>IRR 6,800,000</b>	
5	<b>THC-B220</b> 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	<b>IRR 6,500,000</b>	
6	<b>THC-B220-M</b> 2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output- Full Metal	<b>IRR 8,100,000</b>	
7	<b>THC-B240</b> 4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	<b>IRR 7,200,000</b>	

8	<b>THC-B240-M</b>	4MP CMOS Sensor, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66, 2.8/3.6/6mm Lens,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	<b>IRR 9,100,000</b>	
9	<b>THC-T120-PC</b>	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	<b>IRR 4,350,000</b>	
10	<b>THC-T120</b>	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	<b>IRR 4,750,000</b>	
11	<b>THC-T120-M</b>	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	<b>IRR 6,050,000</b>	
12	<b>THC-T140-P</b>	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	<b>IRR 5,100,000</b>	
13	<b>THC-T140</b>	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	<b>IRR 5,800,000</b>	
14	<b>THC-T140-M</b>	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	<b>IRR 6,950,000</b>	
15	<b>THC-T220-P</b>	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	<b>IRR 4,500,000</b>	
16	<b>THC-T220-M</b>	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	<b>IRR 6,850,000</b>	
17	<b>THC-T240-P</b>	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	<b>IRR 6,100,000</b>	

18	<b>THC-T240-M</b>	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	<b>IRR 7,900,000</b>	
19	<b>Vari-Focal Series</b>			
20	<b>THC-B320-VF</b>	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,,DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	<b>IRR 10,800,000</b>	
21	<b>THC-B340-VF</b>	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	<b>IRR 13,600,000</b>	
22	<b>THC-D320-VF</b>	2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output-,IK10-Full Metal	<b>IRR 5,700,000</b>	
23	<b>THC-D340-VF</b>	4MP CMOS Sensor, EXIR Dome, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens,IK10. Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	<b>IRR 11,000,000</b>	
24	<b>THC-T320 VF</b>	2MP CMOS Sensor, 40m IR, EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	<b>IRR 7,300,000</b>	
25	<b>THC-T340-VF</b>	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	<b>IRR 10,500,000</b>	
26	<b>Turbo HD PTZ Camera</b>			
27	<b>PTZ-T4225I-D</b>	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25x optical zoom, 16x digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	<b>ناموجود</b>	
28	<b>PTZ-T4215I-D</b>	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 15x optical zoom, 16x digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	<b>ناموجود</b>	











29	<b>PTZ-T5225I-A</b>	1/2.8" HD progressive scan CMOS1920 × 1080 resolution 25x optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance3D intelligent positioning Switchable turbo HD and CVBS outputs	ناموجود	
30	<b>DVR 4 Channel</b>			
31	<b>DVR-204G-F1</b>	Recording Capability <b>HD1080p Lite</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, -1-ch Up to 960P resolution), <b>1 SATA</b> (6TB)interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- <b>HDMI output HD1080p-Metal</b>	<b>IRR 10,450,000</b>	
32	<b>DVR-204Q-F1</b>	Recording Capability <b>3MP</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), <b>1 SATA</b> (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920×1080P: 12 fps/ch, 260 1U case- <b>HDMI outputHD1080p-Metal</b>	<b>IRR 11,880,000</b>	
33	<b>DVR-204Q-K1</b>	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	<b>IRR 13,200,000</b>	
34	<b>DVR-204U-F1</b>	Recording Capability <b>5MP/3MP</b> <b>4-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>2-ch IP video input(up to 6MP resolution)</b> , <b>1 SATA</b> (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- <b>HDMI output HD1080p-Metal</b>	<b>IRR 18,900,000</b>	
35	<b>DVR-204U-K1</b>	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal	<b>IRR 20,500,000</b>	
36	<b>DVR 8 Channel</b>			
37	<b>DVR-208G-F1</b>	Recording Capability <b>HD1080p Lite</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input,- <b>2-ch Up to 960P resolution)</b> , <b>1 SATA</b> (6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case-- <b>HDMI output HD1080p-Metal</b>	<b>IRR 15,800,000</b>	
38	<b>DVR-208Q-F1</b>	Recording Capability <b>3MP</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, - <b>2-ch IP video input(up to HD1080p resolution)</b> , <b>1 SATA</b> (6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920×1080P: 12 fps/ch, 260 1U case- <b>HDMI output HD1080p-Metal</b>	<b>IRR 13,100,000</b>	











39	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 25,850,000	
40	DVR-208U-F1	Recording Capability <b>5MP/3MP</b> <b>8-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input- <b>4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB)</b> interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- <b>HDMI output 4K-Metal</b>	IRR 35,200,000	
41	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 39,500,000	
42	<b>Digital Video Recorder</b>			
43	DVR-216G-F1	Recording Capability <b>HD1080p Lite</b> <b>16-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, -2-ch Up to 960P resolution, <b>1 SATA (6TB)interface, HD1080p Lite @ 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal</b>	IRR 24,800,000	
44	DVR-216Q-F1	Recording Capability <b>3MP</b> <b>16-ch HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), <b>1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal</b>	IRR 35,200,000	
45	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 38,500,000	
	DVR-216Q-K2	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 44,000,000	
46	DVR-216U-F2	Recording Capability <b>5MP/3MP</b> <b>16-ch -HD-TVI/AHD/CVI/CVBS</b> video & 1-ch audio input,- <b>8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)-</b> interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case- <b>HDMI output 1ch 4K-Metal-</b>	IRR 69,100,000	








**DVR-216U-K2**

DVR 16 Channels HD 8 Megapixel, Interfaces input: 16 video / 1 Audio,  
( Support TVI - AHD – CVI - CVBS, HDMI, VGA Outputs, 2 USB  
Support H.265+ compression, 2SATA up to 8TB capacity per HDD, Up to 8-ch, 6MP IP  
cameras input, Up to 8 MP resolution for recording








**IRR 74,500,000**

Hilook-NVR			
Items	Description	User Price	
1	<b>IPC-B120</b> 1/2.8" progressive scan CMOS-1920 x 1080@30fps -2.8 mm fixed lens- H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 11,800,000	
2	<b>IPC-B120H</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 13,750,000	
3	<b>IPC-B140H</b> 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 16,300,000	
4	<b>IPC-B220</b> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 11,000,000	
5	<b>IPC-B220-D</b> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 12,100,000	
6	<b>IPC-T120</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR - H.264+&H.264-,2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 10,300,000	
7	<b>IPC-T120-D</b> 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 9,500,000	
8	<b>IPC-T220-H</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 12,100,000	

9	<b>IPC-T240H</b>	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,--Support mobile monitoring via Hik-Connect *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 14,800,000	
10	<b>IPC-D120</b>	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 11,200,000	
11	<b>IPC-D120H</b>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, --2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 14,300,000	
12	<b>IPC-D140H</b>	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, 120 dB WDR.	IRR 14,800,000	
13	<b>Vari-Focal Series</b>			
14	<b>IPC-B620H-V</b>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 24,750,000	
15	<b>IPC-B620H-Z</b>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 23,100,000	
16	<b>IPC-B640H-V</b>	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 28,600,000	
17	<b>IPC-B640H-Z</b>	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 31,300,000	
18	<b>IPC-T620-Z</b>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8-12mm VF lens-Eyeball: MetalCover: Plastic-IP67	ناموجود	
19	<b>IPC-D620H-V</b>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 21,500,000	

20	<b>IPC-D620H-Z</b>	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream-DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	<b>IRR 21,970,000</b>	
21	<b>IPC-D640H-V</b>	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	<b>IRR 2,700,000</b>	
22	<b>IPC-D640H-Z</b>	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	<b>IRR 23,800,000</b>	
23	<b>PanoVu Mini Series IR Network PTZ Camera</b>			
24	<b>PTZ-P332ZI-DE3</b>	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkage Up to 10 m IR radius Panoramic Camera Three 1/2.8" progressive scan CMOS I 3-ch 1920 x 1080@30fps resolution Horizontal FOV: 128.5° x 3 PTZ Camera 1/2.8" progressive scan CMOS I Up to 1920 x 1080@30fps resolution I 4x optical zoom, 8x digital zoom	<b>ناموجود</b>	
25	<b>IP PTZ Camera</b>			
26	<b>PTZ-N2204I-DE3</b>	1/2.8" progressive scan CMOS .Up to 1920 x 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance IK10, IP66 Support H.265+/H.265 video compression	<b>ناموجود</b>	
27	<b>PTZ-N2404I-DE3</b>	1/3" progressive scan CMOS .Up to 2560 x 1440@25fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance. IK10, IP66 Support H.265+/H.265 video compression	<b>ناموجود</b>	
28	<b>PTZ-N4215-DE3</b>	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illuminat Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	<b>ناموجود</b>	

29	<b>PTZ-N4215I-DE</b>	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compressionUp to 24 programmable privacy masks Support ROI	ناموجود	
30	<b>PTZ-N4225I-DE</b>	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IRUp to 100 m IR distance 25x optical zoom, 16x digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI	ناموجود	
31	<b>PTZ-N5225I-AE</b>	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 150 m IR distance 25x optical zoom, 16x digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 24 VAC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI Support smart detection	ناموجود	
32	<b>Network Video Recorder</b>			
33	<b>NVR-104-B</b>	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p	IRR 9,340,000	
34	<b>NVR-104-B/4P</b>	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB , 4 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	ناموجود	
35	<b>NVR-108-B</b>	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	ناموجود	
36	<b>NVR-108-B/8P</b>	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB ,8 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	IRR 21,500,000	
37	<b>NVR-104MH-C</b>	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 14,200,000	

38	<b>NVR-104MH-C/4P</b>	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) ,Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	<b>IRR 26,300,000</b>	
39	<b>NVR-108MH-C</b>	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	<b>IRR 18,900,000</b>	
40	<b>NVR-108M-C/8P</b>	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp),Output Bandwidth 80Mbps,- H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)--HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	<b>IRR 36,000,000</b>	
41	<b>NVR-108M-D/8P</b>	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	<b>IRR 32,000,000</b>	
42	<b>NVR-116MH-C</b>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	<b>IRR 21,800,000</b>	
43	<b>NVR-216MH-C</b>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	<b>IRR 26,000,000</b>	
44	<b>NVR-216MH-C/16P</b>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA( up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k,-Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	<b>IRR 53,900,000</b>	



HOME - Bussiness		
Items	Description	User Price
<b>Modem Router</b>		
1	<b>X6200-EU</b> Linksys X6200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 433Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	<b>IRR 12,400,000</b>
2	<b>XAC1200-EK</b> Linksys XAC1200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 867Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	<b>IRR 18,230,000</b>
3	<b>XAC1900-EK</b> Linksys XAC1900 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 1300Mbps + 600Mbps; 4 x 10/100/1000 Ports; 2 x USB Ports; MIMO3x3; External Antennas	<b>IRR 28,260,000</b>
<b>Wireless Router E-series</b>		
5	<b>E900-EE</b> Linksys E900 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	<b>IRR 2,990,000</b>
6	<b>E1200-M2</b> Linksys E1200 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	<b>IRR 4,490,000</b>
7	<b>E1700-EK</b> Linksys E1700 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100/1000 Ports; No USB; MIMO2x2; External Antennas	<b>IRR 5,430,000</b>
8	<b>E2500-M2</b> Linksys E2500 Wireless-N Router; 802.11a/b/g/n; Dual Band; Max 300Mbps; 4 x 10/100/100 Ports; 1xUSB; MIMO2x2; Internal Antennas	<b>IRR 6,550,000</b>
<b>Wireless Router EA-series</b>		
9		

10	<b>EA2750-M2</b>	Linksys EA2750 Wireless-N Router; 802.11a/b/g/n; Dual Band Concurrent; Max 300Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	<b>IRR 9,170,000</b>
11	<b>EA6100-EK</b>	Linksys EA6100 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100 Ports; 1xUSB; MIMO2x2; External Antennas	<b>IRR 9,260,000</b>
12	<b>EA6350-EK</b>	Linksys EA6350 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	<b>IRR 15,350,000</b>
13	<b>EA6900-M2</b>	Linksys EA6900 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO3x3; External Antennas	<b>IRR 21,930,000</b>
14	<b>EA7500-EU</b>	Linksys EA7500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO3x3; External Antennas	<b>IRR 25,270,000</b>
15	<b>EA8500-EU</b>	Linksys EA8500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1733Mbps + 800Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	<b>IRR 32,760,000</b>
16	<b>EA9500-EU</b>	Linksys EA9500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2166Mbps + 1000Mbps; 8x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	<b>IRR 53,360,000</b>
17	<b>Wireless Router WRT-series</b>		
18	<b>WRT1900ACS-EU</b>	Linksys WRT1900ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	<b>IRR 22,280,000</b>
19	<b>WRT1200AC-EU</b>	Linksys WRT1200AC Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO2x2; External Antennas	<b>IRR 17,780,000</b>
20	<b>WRT3200ACM-EU</b>	Linksys WRT3200ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2600Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	<b>IRR 35,560,000</b>
21	<b>WRT32X-EU</b>	LINKSYS WRT32X WIFI ROUTER,AC3200 DUAL-BAND WI-FI GAMING ROUTER WITH KILLER PRIORITIZATION ENGINE; 4 Gigabit ports; 4 detach Antenna; 2 USB Ports	<b>IRR 39,320,000</b>
22	<b>USB Adapter</b>		
23	<b>AE1200-EE</b>	Linksys AE1200 Wireless-N USB Adapter; Single Band; Max 300Mbps	<b>IRR 2,430,000</b>
24	<b>AE2500-EE</b>	Linksys AE2500 Wireless-N USB Adapter; Dual Band; Max 300Mbps	<b>IRR 3,900,000</b>

25	<b>AE6000-EE</b>	Linksys AE6000 Wireless-AC USB Adapter; Dual Band; Max 433Mbps	<b>IRR 3,900,000</b>
26	<b>WUSB6100M-EU</b>	Linksys WUSB6100M Wireless-AC USB Adapter; Dual Band; Max 433Mbps	<b>IRR 6,550,000</b>
27	<b>WUSB6300-EK</b>	Linksys WUSB6300 Wireless-AC USB Adapter; Dual Band; Max 867Mbps	<b>IRR 5,990,000</b>
28	<b>USB3GIG-EJ</b>	Linksys USB 3.0 Gigabit Ethernet Adapter	<b>IRR 2,990,000</b>
29	<b>Range Extender</b>		
30	<b>RE3000W-EK</b>	Linksys RE3000W Range Extender; Single Band; 802.11b/g/n; Max 300Mbps; 1x10/100 Port	<b>IRR 5,270,000</b>
31	<b>RE4100W-EU</b>	Linksys RE4100W Range Extender; Dual Band; 802.11a/b/g/n; Max 300Mbps; 1x10/100 Port	<b>IRR 6,360,000</b>
32	<b>RE6300-EU</b>	Linksys RE6300 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 433Mbps; 1x10/100/1000 Port	<b>IRR 9,300,000</b>
33	<b>RE6400-EU</b>	Linksys RE6400 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port	<b>IRR 9,730,000</b>
34	<b>RE6500-EU</b>	Linksys RE6500 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 4x10/100/1000 Port; Audio Jack; Desktop	<b>IRR 12,540,000</b>
35	<b>RE6700-EG</b>	Linksys RE6700 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port; Audio Jack; Power Out	<b>IRR 13,480,000</b>
36	<b>Switches ( HOME )</b>		
37	<b>SE2500-EU</b>	Linksys SE2500 Gigabit Switch; 5x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	<b>IRR 4,120,000</b>
38	<b>SE2800-EU</b>	Linksys SE2800 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	<b>IRR 5,782,000</b>
39	<b>SE4008</b>	Linksys SE4008 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving; Stacks over WRT1900AC	<b>IRR 6,550,000</b>
40	<b>Switches ( Business )</b>		
41	<b>LGS105-EU</b>	5-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	<b>IRR 4,100,000</b>

42	<b>LGS108-EU</b>	8-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	<b>IRR 4,900,000</b>
43	<b>LGS116-EU</b>	16-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop; Wall Mount; Fanless; Power Saving; Adapter Included	<b>IRR 15,110,000</b>
44	<b>LGS124-EU</b>	24-Ports Gigabit ,Unmanaged, QOS, Metal, RackMount; 24x10/100/1000 Ports	<b>IRR 21,520,000</b>
45	<b>LGS308-EU</b>	8-Ports Gigabit; Smart, Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	<b>IRR 9,770,000</b>
46	<b>LGS318-EU</b>	18-Ports Gigabit 2 Combo Ports (RJ45 + SFP) , Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON, VLAN 802.1Q	<b>IRR 22,590,000</b>
47	<b>LGS326-EU</b>	26-Ports Gigabit, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	<b>IRR 27,060,000</b>
48	<b>LGS528-EU</b>	28-Ports Gigabit , Layer 3 Static Routing, 28Ports , 2 Combo Ports (RJ45 + SFP) Advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE-	<b>IRR 43,760,000</b>
49	<b>LGS552-EU</b>	52-Ports Gigabit , Layer 3 Static Routing, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports:	<b>IRR 78,150,000</b>
50	<b>Switches POE</b>		
51	<b>LGS108P-EU</b>	8-Ports Gigabit ,Unmanaged, 4 Ports POE, 50W, QOS, Metal,Wall Mount	<b>IRR 13,020,000</b>
52	<b>LGS116P-EU</b>	Gigabit ,Unmanaged, 16-Port (8POE), 80W, QOS, Metal, Wall Mount	<b>IRR 21,160,000</b>
53	<b>LGS124P-EU</b>	Gigabit, Unmanaged, 24-Port (12POE), 120W, QOS, Metal, RackMount	<b>IRR 32,810,000</b>
54	<b>LGS308P-EU</b>	8-Ports Gigabit ,Smart, 8Port POE 802.3af & 802.3at, 72W, Advances QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	<b>IRR 18,310,000</b>
55	<b>LGS318P-EU</b>	Gigabit ,Smart, 18-Ports (16POE) 802.3af & 802.3at, 125W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON.VLAN 802.1Q	<b>IRR 46,650,000</b>
56	<b>LGS326P-EU</b>	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 192W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	<b>IRR 65,000,000</b>

57	<b>LGS326MP-EU</b>	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 384W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	<b>IRR 68,800,000</b>
58	<b>LGS528P-EU</b>	28-Ports Gigabit , Layer 3 Static Routing, 24Ports POE 192W Budget, 2 Combo Ports (RJ45 + SFP),, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE	<b>IRR 71,070,000</b>
59	<b>LGS552P-EU</b>	Gigabit , Layer 3 Static Routing, 52-Ports (48 POE) 375W, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 52GE	<b>IRR 117,230,000</b>
60	<b>Access Point</b>		
61	<b>LAPN300-EU</b>	Single Band; 802.11n; Max 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	<b>IRR 12,010,000</b>
62	<b>LAPN600-EU</b>	Dual Band; 802.11n; Max 300 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	<b>IRR 18,850,000</b>
63	<b>LAPAC1200-EU</b>	Dual Band; 802.11ac; Max 867 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	<b>IRR 23,250,000</b>
64	<b>LAPAC1750-EU</b>	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO 3x3	<b>IRR 31,650,000</b>
65	<b>LAPAC1750 PRO-EU</b>	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 2*GigaEthernet; MIMO 3x3; High Gain Antenna	<b>IRR 49,040,000</b>
66	<b>LAPAC2600-EU</b>	Linksys Business Dual-Band Access Point AC2600	<b>IRR 52,750,000</b>
67	<b>WAP300N-EE</b>	Dual Band; 802.11n;Max 300Mbps;Bridge; Adapter only; Desktop;1*Fast Ethernet ; MIMO 2*2	<b>IRR 5,610,000</b>
68	<b>WHW0302-ME new</b>	LINKSYS VELOP	<b>IRR 50,880,000</b>
69	<b>WAP750AC</b>	Linksys WAP750AC AC750 Wi-Fi Access Point	<b>IRR 8,930,000</b>
70	<b>VPN Router</b>		
71	<b>LRT214-EU</b>	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 1xWAN Port; Metal Case	<b>IRR 19,140,000</b>

72	<b>LRT224-EU</b>	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 2xWAN Port; Metal Case; Load Balance; Smart Backup; Aggregate WAN1 + WAN2	<b>IRR 19,930,000</b>
73	<b>Poe Injector</b>		
74	<b>LACPI30-EU</b>	Linksys PoE Injector; 802.3af and 802.3at; 30Watts; Gigabit Ethernet; Wall Mount	<b>IRR 5,470,000</b>



Equip Rack			
Items	Description	User Price	
<b>ER Standing Rack IP42</b>			
1	ERS - 4761	رک ۴۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۵۹,۵۰۰,۰۰۰
2	ERS - 4281	رک ۴۲ یونیت-عمق ۱۰۰-عرض ۸۰ - درب جلو مشبک، درب پشت ۲ لنگه مشبک	۷۲,۵۰۰,۰۰۰
3	ERS - 4261	رک ۴۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۵,۰۵۰,۰۰۰
4	ERS - 4268	رک ۴۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۲,۰۰۰,۰۰۰
5	ERS - 4266	رک ۴۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۶,۲۰۰,۰۰۰
6	ERS - 3761	رک ۳۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۴۱,۵۰۰,۰۰۰
7	ERS - 3868	رک ۳۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۶,۰۰۰,۰۰۰
8	ERS - 3866	رک ۳۸ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۳,۰۰۰,۰۰۰
9	ERS - 3261	رک ۳۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۹,۰۰۰,۰۰۰
10	ERS - 3268	رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۳۴,۷۰۰,۰۰۰

11	ERS - 3266	رک ۳۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۳۲,۰۰۰,۰۰۰
12	ERS - 2861	رک ۲۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۶,۲۰۰,۰۰۰
13	ERS - 2868	رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۳۱,۰۰۰,۰۰۰
14	ERS - 2866	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۷,۵۰۰,۰۰۰
15	ERS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۳۱,۰۰۰,۰۰۰
16	ERS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۷,۰۰۰,۰۰۰
17	ERS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۴,۲۰۰,۰۰۰
18	ERS - 1868	رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۴,۵۰۰,۰۰۰
19	ERS-1766	رک ۱۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۲۲,۷۰۰,۰۰۰
20	ERS-1468	رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۲,۰۰۰,۰۰۰
21	ERS-1466	رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۹,۸۰۰,۰۰۰
22	<b>ER Wall Mount</b>		
23	ERW - 1266	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۸,۷۰۰,۰۰۰
24	ERW - 0966	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۷,۱۰۰,۰۰۰
	ERW - 0666	رک دیواری - ۶ یونیت- عمق ۶۰ ، عرض ۶۰	۴,۷۰۰,۰۰۰
25	ERW - 0664	رک دیواری - ۶ یونیت- عمق ۴۵ ، عرض ۶۰	۴,۷۳۰,۰۰۰
26	ERW - 0465D	DVR رک دیواری - ۴ یونیت- عمق ۵۰ ، عرض ۶۰	Call
34	<b>ER OUTDOOR RACK</b>		
35	ERO - 0745	رک ۷ یونیت -عمق ۴۵ OUTDOOR	۲۳,۵۰۰,۰۰۰



36	ERO - 0966	OUTDOOR رک ۹ یونیت - عمق ۶۰	۲۷,۵۰۰,۰۰۰
37	ERO - 1266	OUTDOOR رک ۱۲ یونیت - عمق ۶۰	۳۶,۰۰۰,۰۰۰
38	ERO - 1866	OUTDOOR رک ۱۸ یونیت - عمق ۸۰	۴۸,۰۰۰,۰۰۰
39	<b>شامل تخفیف نمی‌گردد OUTDOOR لازم به ذکر است رک های</b>		
40	<b>ER MAIN FRAME</b>		
41	ERM - 4202	رک ۴۲ یونیت - آزمایشگاهی - دو پنل	C ALL
42	ERM - 4201	رک ۴۲ یونیت - آزمایشگاهی - تک پنل	C ALL
43	ERM - 3202	رک ۳۲ یونیت - آزمایشگاهی - دو پنل	C ALL
44	<b>Shelf</b>		
45	ERA - SSW	طبقه ثابت رک های دیواری	۷۷۰,۰۰۰
46	ERA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۱,۱۰۰,۰۰۰
47	ERA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۱,۵۰۰,۰۰۰
48	ERA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۱,۹۰۰,۰۰۰
49	ERA - SM 60	سینی متحرک رک ۶۰ سانتیمتر	۲,۵۰۰,۰۰۰
50	ERA - SM 80	سینی متحرک رک ۸۰ سانتیمتر	۲,۵۰۰,۰۰۰
51	ERA - SM 10	سینی متحرک رک ۱۰۰ سانتیمتر	۲,۵۰۰,۰۰۰
52	<b>Power Module</b>		
53	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۱,۱۰۰,۰۰۰
54	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۸۳۰,۰۰۰
55	<b>Accessories</b>		
56	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۱,۴۳۰,۰۰۰
57	ERA - SCR - 20	پیچ و کزنات مخصوص رک بسته ۱۰ تایی	۹۴,۰۰۰
58	ERA - TR - 20	حرارت سنچ یک یونیت دیجیتال تنظیم دما، رطوبت، ولتاژ و جریان	۱۲,۰۰۰,۰۰۰
59	ERA - FN - 20	فن پوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۹۵۰,۰۰۰
60	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ	۸۸۰,۰۰۰

61	ERA - CM - 20	نگهدارنده عمودی کابل	۹۹,۰۰۰
62	ERA - CM - 30	نگهدارنده کابل درپوش دار	۵۰۰,۰۰۰
63	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۳۹۰,۰۰۰
64	<b>Blank Panel</b>		
65	ERA - BLA - 10	بلانک پنل ، ۱ یونیت	۲۱۰,۰۰۰
66	ERA - BLA - 20	بلانک پنل ، ۲ یونیت	۲۶۰,۰۰۰
67	ERA - BLA - 30	بلانک پنل ، ۳ یونیت	۳۰۰,۰۰۰
68	ERA - BLA - 40	بلانک پنل ، ۴ یونیت	۳۷۴,۰۰۰
69	ERA - BLA - 50	بلانک پنل ، ۱ یونیت فرچه ای	۵۵۰,۰۰۰
70	<b>Doors</b>		
71	EDM - 4261	درب مشبک ۴۲ یونیت ساده عرض ۶۰ به همراه قفل	۴,۴۰۰,۰۰۰
72	EDM - 3801	تفاوت قیمت درب مشبک ۳۸ یونیت تک لنگه با درب شیشه ای	۴,۴۰۰,۰۰۰
73	EDM - 3201	تفاوت قیمت درب مشبک ۳۲ یونیت تک لنگه با درب شیشه ای	۴,۴۰۰,۰۰۰
74	EDM - 2801	تفاوت قیمت درب مشبک ۲۸ یونیت تک لنگه با درب شیشه ای	۴,۴۰۰,۰۰۰
لازم به ذکر است درب مشبک شامل تخفیف نمی گردد			